

INDOOR CEILING FAN WITH DOME LIGHT

by Hyperikon®



Voltage 110 V



Power Use 44 W/62 W



Lifespan 45.000+ Hrs



Blade Size 42"/52"



Iron Shell



Wooden Blades



Remote Controlled



4,450 CFM



Airflow Efficiency 71.79 CFM/W

- Device complies with Part 15 of the FCC Rules
- Device has been tested and found to comply with the limits for a class B digital device
- The driver range is 110V



- **\((888) 846-4973**
- info@hyperikon.com
- www.hyperikon.com

HYPERIKON.

Hyperikon® proudly presents a brand new member to the family! Our Ceiling Fan is an easy to install fixture and a fine addition to every room in your living area. With great airflow efficiency, and operating at 44W/62W, the Ceiling Fan has every bit of our well known expertise in customer care and technology. It comes in four colors, three mounting options, with a blade size of 42 or 52 inches, a lifespan of 45,000+ Hours, and our signature 5 year warranty.



SPECIFICATIONS

Hyperikon Code	Model Name	Electriciy Use	Voltage	Blade Size	Color	Airflow	Airflow Efficiency
FDRA4201	HyperFan42-DWH	44W	110V	42"	White	2,785 CFM	63 CFM/W
FDRA4202	HyperFan42-DBL	44W	110V	42"	Black	2,785 CFM	63 CFM/W
FDRA4203	HyperFan42-DBR	44W	110V	42"	Brown	2,785 CFM	63 CFM/W
FDRA4204	HyperFan42-DBN	44W	110V	42"	Brushed Nickel	2,785 CFM	63 CFM/W
FDRA5201	HyperFan52-DWH	62W	110V	52"	White	4,450 CFM	71.79 CFM/W
FDRA5202	HyperFan52-DBL	62W	110V	52"	Black	4,450 CFM	71.79 CFM/W
FDRA5203	HyperFan52-DBR	62W	110V	52"	Brown	4,450 CFM	71.79 CFM/W
FDRA5204	HyperFan52-DBN	62W	110V	52"	Brushed Nickel	4,450 CFM	71.79 CFM/W



MODEL DESIGN




Brushed Nickel



Three Mounting Options

- 1. Flush Mount
- 2. Downrod Mount
- 3. Angled Mount



White





WARNINGS AND CAUTIONS

- Suitable for large indoor living areas 20' x 20' or less.
- Blade tips should be at least 18 inches from any wall.
- This device is not intended for use with emergency exit fixtures or emergency exit lights.







