



Dependable. Reliable. Professional.

# FAST-GRIP™

## SELF-FUSING SILICONE TAPE

**SPECIALTY TAPE**



- Backing:** Self-Fusing Silicone
- Adhesive:** N/A
- Liner:** Clear Cellophane
- Specifications:** UL 510 Classified  
Meets A-A-59163 Type I and Type II
- Colors:** Black
- Available Size:** 1.12 in x 5 ft (28.5 mm x 1.52 m)

### Applications

- Cover sharp exposed edges on tools and equipment for safer operation
- Use on tools and sports equipment handles as a replacement grip or surface protection from scrapes and abrasions
- Protect hands and re-grips hand and garden tools
- Wrap pipes to protect against rust and corrosion

### Features

### Benefits

Self-Fusing Silicone	<ul style="list-style-type: none"> <li>• Initially repositionable to achieve a proper seal</li> <li>• Extreme temperature resistance (-65 to 500 °F)</li> <li>• Stretches up to 300%</li> <li>• Apply even in wet conditions for water and air-tight seals</li> <li>• Resists UV and chemical exposure</li> </ul>
Non-Adhesive	<ul style="list-style-type: none"> <li>• Cut away to remove</li> <li>• Leaves no messy residue behind</li> </ul>
Ridged Texture	<ul style="list-style-type: none"> <li>• Provides comfort for a non-slip grip</li> </ul>
UL 510 Classified	<ul style="list-style-type: none"> <li>• Insulates up to 8000 volts per wrap</li> <li>• Meets requirements for most electrical uses</li> </ul>

### Typical Test Values

	Standard UOM	Metric UOM	Test Method
<b>Total Thickness</b>	20 mils	508 µm	ASTM D-1000
<b>Tensile Strength</b>	700 psi		ASTM D-412
<b>Elongation</b>	300%		ASTM D-412
<b>Operating Temperature</b>	-65 to 500 °F	-54 to 260 °C	
<b>Dielectric Strength</b>	8000V per wrap		
<b>Tear Resistance</b>	65 psi		
Recommended Storage Conditions: 60 - 80 °F at 40-60% RH			
Standard Shelf Life (at 25 °C): 12 months from date of manufacture			

The information presented herein was prepared at BERRY GLOBAL, INC. (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To BERRY's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.



25 Forge Parkway Franklin, MA 02038  
1-800-343-7875 Fax 1-800-328-4822  
www.nashuatape.com