

El **Parche Húmedo de Caucho Rust-Oleum** es un cemento para techos con base de asfalto, multifibra, de calidad Premium combinado con aceites penetrantes y agentes plastificantes que se puede aplicar directamente sobre superficies frías, calientes, húmedas o bajo el agua. El **Parche Húmedo de Caucho** se puede utilizar para reparar y restaurar láminas y defectos en el techo tales como burbujas, grietas y perforaciones. También se puede utilizar para adherir capas de asfalto, membranas de láminas de betún asfáltico modificadas o rejillas de sellado, tejas, tragaluces y chimeneas. El **Parche Húmedo de Caucho** es resistente a las salpicaduras y se espesa fácilmente en condiciones frías.

DANGER! CONTAINS: Mineral Spirits. Vapor harmful. May affect the brain or nervous system causing dizziness, headache, or nausea. Causes nose and throat irritation. Causes eye irritation. Causes skin irritation. **NOTICE:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. **FIRST AID:** Keep away from heat and flame. Use only with adequate ventilation. Do not breathe vapors. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor levels are above applicable limits, wear an appropriate, properly fitting respirator during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. **IN CASE OF EYE CONTACT:** flush immediately with plenty of water for at least 15 minutes and get medical attention immediately; for skin, wash thoroughly with soap and water. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. **IF SWALLOWED:** Do not induce vomiting. Get medical attention immediately. **KEEP OUT OF REACH OF CHILDREN.**

WARNING: Cancer – www.P65Warnings.ca.gov.

¡PELIGRO! Contiene alcoholes minerales. El vapor es perjudicial. Puede afectar el cerebro o el sistema nervioso causando mareos, náuseas o dolor de cabeza. Provoca irritación nasal y de la garganta. Provoca irritación en los ojos. Provoca irritación en la piel. **AVISO:** Algunos informes han asociado la sobreexposición ocupacional repetida y prolongada a solventes con daño cerebral y al sistema nervioso permanentes. El uso indebido e intencional al concentrar e inhalar deliberadamente el contenido del producto puede ser perjudicial o mortal. **PRIMEROS AUXILIOS:** Mantenga lejos del calor y de las llamas. **Utilicelo solo con la ventilación adecuada.** No respire los vapores. Si le lloran los ojos, siente dolor de cabeza o mareos o si el monitoreo del aire muestra niveles de vapor superiores a los límites aplicables, utilice adecuadamente un respirador durante y después de la aplicación. Siga las instrucciones de uso del respirador proporcionadas por el fabricante. Evite el contacto con los ojos, la piel y la ropa. Lávese bien después de manipular el producto. **EN CASO DE CONTACTO CON LOS OJOS:** enjuague inmediatamente con abundante agua durante por lo menos 15 minutos y busque atención médica inmediata. En caso de contacto con la piel, lave bien con agua y jabón. Si experimenta dificultad al respirar, abandone el área en busca de aire fresco. Si la dificultad persiste, busque atención médica de inmediato. **EN CASO DE INGESTIÓN:** No induzca el vómito. Busque atención médica de inmediato. **MANTENGA EL PRODUCTO ALEJADO DEL ALCANCE DE LOS NIÑOS.** **ADVERTENCIA:** Cáncer www.P65Warnings.ca.gov.

ALMACENAMIENTO Y ELIMINACIÓN: En caso de derrame, contenga el material derramado y retínelo con absorbente inerte. Deseche el absorbente contaminado, el envase y el contenido sin usar de acuerdo con las regulaciones locales, estatales y nacionales.

MAX VOC < 250 g/L

351250



• TRUSTED QUALITY SINCE 1921 •

RUST-OLEUM®

EXTREME

RUBBERIZED WET ROOF REPAIR

PARCHE HÚMEDO DE CAUCHO

10 YEAR PERFORMANCE
10 AÑOS DESEMPEÑO

**REPAIRS ROOF LEAKS
ON WET & DRY SURFACES**

IMMEDIATE ALL-WEATHER REPAIRS

HEAVILY FIBERED FOR LONGER LASTING REPAIRS

**RUBBERIZED FOR INCREASED STRENGTH
AND FLEXIBILITY**

**USE ON COMMERCIAL ROOFS OR SHINGLED
RESIDENTIAL ROOFS**



**STOPS LEAKS
IN STANDING WATER**

3.3 Gallons/12.4 Liters

BLACK

Rust-Oleum Rubberized Wet Roof Repair is a premium quality, heavily fibered, asphalt-based roof cement blended with penetrating oils and plasticizing agents that can be applied directly to cold, hot, wet, dry or underwater surfaces. **Rubberized Wet Roof Repair** can be used to repair and restore flashings and roofing defects such as blisters, cracks, and punctures. It can also be used to adhere new asphalt ply, and modified bitumen membrane flashings or seal vents, shingles, skylights, and chimneys. **Rubberized Wet Roof Repair** resists sags and spreads easily in cold conditions.

DIRECTIONS

SURFACE PREPARATION: All surfaces must be clean, sound, and free from dirt, grease, oil, mold, algae, loose granules, loose gravel, loose paint, rust, excess chalk, and other foreign matter which could prevent proper adhesion.

APPLICATION: Apply with a trowel directly over cleaned substrate at a rate of 12 ft²/gallon or approximately 1/8" thick. When making roof repairs or stripping over the top of flashing laps, perform a 3-course repair consisting of one application of **Rubberized Wet Roof Repair** followed by an embedded strip of **Rust-Oleum Universal Patching Fabric** or other mesh, followed by a final application of **Rubberized Wet Roof Repair**.

COVERAGE: Approximately 12 ft²/gallon when applied at 1/8" thick. Actual rates will vary depending on ambient temperature and surface conditions.

DRY TIME: Product will reach a full cure in 24 hours. Environmental or site specific conditions may lead to variation in dry time.

CLEANUP: Mineral spirits. Wipe up splatters before they dry.

LIMITATIONS: Not for use on coal tar membranes. Repairs made to wet surfaces should be considered temporary as trapped moisture may expand when heated by the sun causing blisters and potentially new leaks. For permanent repairs, open up the area and allow it to dry thoroughly.

Performance Guarantee: Should this product fail due to a defect, unless expressly agreed otherwise by Rust-Oleum in writing, purchaser's sole and exclusive remedy is that Rust-Oleum Corporation will, at its option, either refund to the purchaser the amount paid for the product, or furnish at its expense sufficient product to restore a protective condition to the affected areas. Proof of purchase must be provided. At its discretion, Rust-Oleum may require inspection of the affected areas by a Rust-Oleum representative. Contact Rust-oleum Product Support at 844-888-0482. Refer to product number and batch code. Please visit rustoleum.com/roofing for further information regarding additional warranties that may be available for your roofing system. **NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY RUST-OLEUM, EXPRESS OR IMPLIED, STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING BUT NOT LIMITED TO MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.**

STORAGE AND DISPOSAL: If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

MAX VOC < 250 g/L

RUST-OLEUM CORPORATION

11 Hawthorn Pkwy., Vernon Hills, IL 60061

844-888-0482 rustoleum.com/roofing

Made in USA | Hecho en E.U.A.

©2019 Rust-Oleum Corporation 351383 0219



02/27/19	Shawn Barkhurst	ROF
345502_ROF_0010_351383_0219_3.3Gal_RO_RubberizedWetRoofRepair		
Principal Display Panel: 90.77"		Signal Word: n/a
Statement of Hazard: n/a		
Other Cautionary Material: n/a	Other Cautionary Material (Back label): .0937"	
Other Cautionary Material (Address): .0937"	Net Wt: .1875"	

All dimensions are based on the measurements within the label at 100% actual size.