

SHAKE WELL BEFORE USING (AGITE BIEN ANTES DE USAR)

Spectracide®

PRUNING SEAL

Sellador para poda

PRODUCT FACTS

WHAT IT DOES:

Helps protect trees and smaller plants from diseases that can enter through pruned areas. This product also effectively seals and waterproofs clay pots, wooden planters, rain gutters, roof flashings and small sections of asphalt driveways. Can also be used to coat the underside of a lawn mower deck to protect from debris damage.

QUESTIONS & COMMENTS:

Call 1-800-917-5438 or visit our website at www.spectracide.com

STOP READ ENTIRE LABEL BEFORE USE.

DIRECTIONS FOR USE

1. Shake well.
2. Hold can upright 6-9 inches from area to be sprayed.
3. Spray in short bursts to prevent dripping and runoff.
4. Clean nozzle after use by turning can upside down and pressing nozzle for about three seconds.

USE TIPS

1. When treating damaged or decayed limbs, cut back to sound wood first.
2. When sealing the inside of planters, spray lightly to prevent dripping.
3. When sealing small cracks or seams, make two applications. Apply the second coat after the first has completely dried.

CAUTION • CONTENTS UNDER PRESSURE.

Exposure to heat may cause bursting. Do not puncture, incinerate or store above 120°F. Avoid prolonged exposure to sunlight. Avoid breathing vapors or vapor mist. Contains petroleum distillates. If swallowed, do not induce vomiting. Call physician or Poison Control Center immediately. Eye irritant. In case of contact with eyes, flush thoroughly with water.

NOTICE: To the extent consistent with applicable law, buyer assumes all responsibility for safety and use not in accordance with directions.

Distributed by Spectrum Group, Division of United Industries Corp.
PO Box 142642, St. Louis, MO 63114-0642
11-11328 © 2010 UIC

†GUARANTEED RESULTS OR YOUR MONEY BACK

If you are not satisfied with this product for any reason, send your written request for a refund to the address above, together with the original dated store receipt showing the price you paid. Please allow 6-8 weeks for processing.

WHERE TO USE:

Protects pruned trees and shrubs and waterproofs and seals planters, clay pots, gutters and roof flashings.



Protects Pruned
Trees & Shrubs



Waterproofs
Planters



Seals
Gutters

ALTO LEA TODA LA ETIQUETA ANTES DE USAR.

MODO DE EMPLEO

1. Agite bien.
2. Sostenga la lata en posición vertical 6 a 9 pulgadas de la zona a rociar.
3. Rocíe en ráfagas cortas para evitar el goteo y el escurrimiento.
4. Limpie la boquilla después de usar volteando la lata de cabeza y presionando la boquilla por aproximadamente tres segundos.

CONSEJOS SOBRE EL USO

1. Cuando trate ramas dañadas o podridas, pódese primero hasta la madera sana.
2. Cuando selle el interior de maceteros, rocíe ligeramente para evitar el goteo.
3. Cuando selle grietas o hendiduras pequeñas, haga dos aplicaciones. Aplique la segunda capa después de que la primera se haya secado completamente.

PRECAUCIÓN • CONTENIDO BAJO PRESIÓN.

La exposición al calor puede causar explosiones. No lo perforo, incinerar ni lo guarde a temperaturas superiores a los 120°F. Evite la exposición prolongada a la luz solar. Evite respirar los vapores o la niebla. Contiene destilados de petróleo. Si se ingiere, no induzca el vómito.

Llame inmediatamente a un médico o un centro de control de envenenamientos. Irrita los ojos. En caso de contacto con los ojos, enjuague muy bien con agua.

NOTA: Hasta el grado que sea compatible con la legislación pertinente, el comprador asume toda la responsabilidad para seguridad y uso que no esté de acuerdo con las instrucciones.

¿Preguntas o comentarios?
Llame al 1-800-917-5438.



Federal regulations prohibit
CFC propellants in aerosols.

FPO UPC

0 71121 59000 8



Spectracide®



PRUNING SEAL

Sellador para poda

Protects Pruned Tree & Shrub Limbs

**Multiple
Outdoor Uses!**

**Waterproofs Clay Pots,
Eliminating Mineral Stains**



KEEP OUT OF REACH OF CHILDREN
CAUTION See back for additional
precautionary statements.
Contents Under Pressure

MANTÉNGASE FUERA DEL ALCANCE DE LOS NIÑOS
PRECAUCIÓN Consulte la parte posterior para conocer
las declaraciones preventivas adicionales.
Contenido Bajo Presión

*For terms of guarantee, see back panel.
Net Wt 13 oz (368 g)