

MATERIAL SAFETY DATA SHEET

MSDS001

Section 1. Chemical Product And Company Identification

Ultralife Part Number:	U9VL; U9VL-FP; U9VL-J; U9VLBUG; U9VLBUG-FP (Lectro)
Description:	Ultralife Lithium Power Cell
Size:	9.6 Volts
Customer Part Number:	N/A
Customer Description:	N/A
National Stock Code:	U9VL: 6135-01-369-9792

Manufactured by	<input type="checkbox"/> Ultralife Batteries (UK) Ltd.	<input checked="" type="checkbox"/> Ultralife Batteries, Inc.
	18 Nuffield Way	2000 Technology Pkwy
	Abington, Oxfordshire, OX14 1TG, England	Newark, NY 14513-2175
CAGE Code	U6734	0UU59

Emergency Telephone Number:	Chemtrec for Spills, Leaks, Fires
USA	1-800-424-9300
International	703-527-3887
Technical Contact Telephone Number:	1-800-332-5000

Section 2. Composition/Information on Ingredients

Chemical Name	CAS #	Exposure Limits	Percent of Content
Manganese Dioxide, MnO ₂	1313-13-9	None Listed	35 – 40
Lithium Metal, Li	7439-93-2	None Listed	1 – 4
Propylene Carbonate, C ₄ H ₆ O ₃	108-32-7	None Listed	8 – 10
1,3-Dioxolane, C ₃ H ₆ O ₂	646-06-0	None Listed	5 – 9
Lithium Hexafluoroarsenate, LiAsF ₆	29935-35-1	As: .01 mg/m ³	1 – 4

Important Note: The materials in this section may only represent a hazard if the integrity of the battery is compromised or if the battery is physically or electrically abused.

ULTRALIFE BATTERIES

FA1284 Rev: D 10/24/05

MSDS001

Rev.: J__

Date: MAR 06 2006

Section 3. Hazards Identification

- 3.1 Emergency overview: May leak and /or flame if opened, recharged, connected improperly, or disposed of in fire.
- 3.2 Potential health effects: Skin contact with may cause irritation and absorption. Contact with raw lithium may cause burns.
Routes of entry: Inhalation or ingestion of electrolyte may have toxic effects.
Acute exposure: Electrolyte may irritate skin and eyes.
Effects of chronic exposure: Electrolyte contains a teratogen.

Section 4. First Aid Measures

Electrolyte Contact

- Skin- Immediately flush with plenty of water for at least 15 minutes. If symptoms are present after flushing, get medical attention.
Eyes- Immediately flush with plenty of water for at least 15 minutes and get medical attention.

Lithium Metal Contact

- Skin- Remove particles of lithium from skin as rapidly as possible. Immediately flush with plenty of water for at least 15 minutes and get medical attention.
Eyes- Immediately flush with plenty of water for at least 15 minutes and get immediate medical attention.

Section 5. Fire Fighting Measures

Extinguishing Media:

- Copious amounts of cold water are an effective extinguishing medium for lithium batteries. Do not use warm or hot water.
Do not use Halon type extinguishing material.

Fire Fighting Procedures

- Use a positive pressure self-contained breathing apparatus if batteries are involved in a fire.
Full protective clothing is necessary.
During water application, caution is advised as burning pieces of lithium may be ejected from the fire.

Unusual Fire and Explosion Hazards

- Batteries may flame or leak potentially hazardous organic vapors if exposed to excessive heat or fire.

Hazardous combustion products

- Fire or excessive heat may produce hazardous decomposition products.
Damaged or opened batteries can result in rapid heating and the release of flammable vapors. Vapors are heavier than air and may travel along the ground or be moved by ventilation to an ignition source and flash back.

Section 6. Accidental Release Measures

Damaged batteries that are not hot or burning should be placed in a sealed plastic bag or container.

Section 7. Handling And Storage

Do not store batteries in a manner that allows terminals to short circuit.

Batteries should be separated from other materials and stored in a non-combustible, well ventilated, sprinkler-protected structure with sufficient clearance between walls and battery stacks. Do not place batteries near heating equipment, nor expose to direct sunlight for long periods

Batteries should be stored in a cool (below 70°F), dry area. Air conditioning or cooling is not required unless excessively high temperatures will be encountered. Elevated storage temperatures can result in reduced battery shelf life and service life, and should be avoided. Batteries should be kept as cool as possible in order to maximize shelf life and service life.

Batteries are not designed to be recharged. Charging a battery may result in electrolyte leakage and/ or cause the battery to flame.

Never disassemble a battery.

Should a battery unintentionally be crushed, thus releasing its contents, rubber gloves must be used to handle all battery components. Avoid inhalation of any vapors that may be emitted.

In the event of skin or eye exposure to the electrolyte, refer to Section 4, First Aid Measures.

More than a momentary short circuit will generally reduce the battery service life. Batteries with fuses will no longer be functional after being shorted.

Extended short circuiting creates high temperatures in the cell. High temperatures can cause burns in skin or cause the cell to flame.

Avoid reversing battery polarity within the battery assembly. To do so may cause cell to flame or to leak.

The use of old and new batteries or batteries of varying sizes and types in the same battery assembly should be avoided. The batteries' electrical characteristics and capabilities vary and damage may result to batteries or electrical equipment.

Section 8. Exposure Controls/Personal Protection

No engineering controls are required for handling batteries that have not been damaged.

Personal protective equipment for damaged batteries should include chemical resistant gloves and safety glasses. In the event of a fire, SCBA should be worn along with thermally protective outer garments.

ULTRALIFE BATTERIES

FA1284 Rev: D 10/24/05

MSDS001

Rev.: J__

Date: MAR 06 2006

Section 9. Physical And Chemical Properties

Not Applicable

Section 10. Stability And Reactivity

- (1) This product is stable under ordinary conditions of use and storage.
(2) Damaged batteries will react with water. Non-discharged batteries contain elemental Lithium. This is water reactive. This reaction gives off heat and hydrogen gas. A thermal reaction may occur.
(4) Hazardous decomposition products: Carbon Monoxide (CO), Hydrogen Fluoride (HF)

Section 11. Toxicological Information

- (1) Irritancy: The electrolytes contained in this battery can irritate eyes with any contact. Prolonged contact with the skin or mucous membranes may cause irritation.
(2) Sensitization: No information is available at this time.
(3) Carcinogenicity: No information is available at this time.
(4) Reproductive toxicity: No information is available at this time.
(5) Teratogenicity: This product contains a known teratogen as indicated in the chemical information in section 2.
(6) Mutagenicity: No information is available at this time.

Section 12. Ecological Information

Not applicable to this material/product.

Section 13. Disposal Considerations

Batteries must be completely discharged prior to disposal and/ or the terminals must be taped or capped to prevent short circuit. This product does not contain any materials listed by the United States EPA as requiring specific waste disposal requirements. When completely discharged, it is not considered hazardous. Disposal of large quantities of lithium power cells may be subject to Federal, State, or Local regulations. Consult your local, state and provincial regulations regarding disposal of these batteries.

Section 14. Transport Information

Product is shipped as:

Ground (DOT)	Air (IATA/ICAO)	Water(IMDG)
Non Hazardous	Non Hazardous	Non Hazardous

ULTRALIFE BATTERIES

FA1284 Rev: D 10/24/05

MSDS001

Rev.: J__

Date: MAR 06 2006

Special shipping information: This battery has been tested to Section 38.3 of 'UN Manual of Tests and Criteria'. The amount of Lithium contained in these batteries is below the limits set by the DOT in Section 49CFR173.185 and IATA A45. There is an exception to ship these with the following shipping label:

<p style="text-align: center;">LITHIUM BATTERIES</p> <p style="text-align: center;">Do not damage or mishandle this package If package is damaged, batteries must be quarantined, inspected and repacked. For emergency information, call CHEMTREC 1-800-424-9300 North America 1-703-527-3887 International</p>

These batteries cannot be shipped by passenger aircraft.

Section 15. Regulatory Information

USA: This MSDS meets/exceeds OSHA requirements.

Canada: This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all of the information required by those regulations.

International: This MSDS conforms to European Union (EU), the International Standards Organization (ISO) and the International Labour Organization (ILO) and as documented in ANSI (American National Standards Institute) Standard Z400.1-1993.

Section 16. Other Information

The information contained herein is furnished without warranty of any kind. Users should consider this data only as a supplement to other information gathered by them and must make independent determinations of the suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers.