

# Wilsonart® 600 Adhesive

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Trade name : Wilsonart® 600 Adhesive

Product form : Mixture

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Adhesive for laminate

### 1.3. Details of the supplier of the safety data sheet

Wilsonart LLC  
P.O. Box 6110  
10501 NW H. K. Dodgen Loop  
Temple, TX 76503  
Information phone: 800-433-3222 (USA)

### 1.4. Emergency telephone number

Emergency number : CHEMTREC: (800) 424-9300  
CHEMTREC (International): 703-527-3887

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### GHS-US classification

Flam. Liq. 2 H225  
Skin Irrit. 2 H315  
Eye Irrit. 2A H319  
Skin Sens. 1 H317  
Repr. 2 H361  
STOT SE 3 H336  
STOT RE 2 H373  
Asp. Tox. 1 H304

### 2.2. Label elements

#### GHS-US labelling

Hazard pictograms (GHS-US) :



GHS02

GHS07

GHS08

Signal word (GHS-US) :

**Danger**

Hazard statements (GHS-US) :

H225 - Highly flammable liquid and vapour  
H304 - May be fatal if swallowed and enters airways  
H315 - Causes skin irritation  
H317 - May cause an allergic skin reaction  
H319 - Causes serious eye irritation  
H336 - May cause drowsiness or dizziness

**Wilsonart® 600 Adhesive**

H361 - Suspected of damaging fertility. Suspected of damaging the unborn child  
H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS-US) :

- P201 - Obtain special instructions before use
- P202 - Do not handle until all safety precautions have been read and understood
- P210 - Keep away from heat, hot surfaces, open flames, sparks.  
- No smoking
- P233 - Keep container tightly closed
- P240 - Ground/bond container and receiving equipment
- P241 - Use explosion-proof electrical, lighting, ventilating equipment
- P242 - Use only non-sparking tools
- P243 - Take precautionary measures against static discharge
- P260 - Do not breathe mist, spray, vapours
- P264 - Wash hands, forearms and face thoroughly after handling
- P271 - Use only outdoors or in a well-ventilated area
- P272 - Contaminated work clothing must not be allowed out of the workplace
- P280 - Wear eye protection, protective clothing, protective gloves
- P301+P310 - IF SWALLOWED: Immediately call a doctor, a poison center
- P302+P352 - If on skin: Wash with plenty of soap and water
- P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
- P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
- P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- P308+P313 - If exposed or concerned: Get medical advice/attention
- P312 - Call a doctor, a poison center if you feel unwell
- P321 - Specific treatment (see first aid instructions on this label)
- P331 - Do NOT induce vomiting
- P332+P313 - If skin irritation occurs: Get medical advice/attention
- P333+P313 - If skin irritation or rash occurs: Get medical advice/attention
- P337+P313 - If eye irritation persists: Get medical advice/attention
- P362+P364 - Take off contaminated clothing and wash it before reuse
- P370+P378 - In case of fire: Use alcohol resistant foam, dry extinguishing powder, carbon dioxide (CO<sub>2</sub>) to extinguish
- P403+P233+P235 - Store in a well-ventilated place. Keep container tightly closed. Keep cool
- P405 - Store locked up
- P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

# Wilsonart® 600 Adhesive

## 2.3. Other hazards

No additional information available

## 2.4. Unknown acute toxicity (GHS-US)

No data available

### SECTION 3: Composition/information on ingredients

#### 3.1. Substance

Not applicable

#### 3.2. Mixture

Name	Product identifier	%
Distillates, petroleum, light distillate hydrotreating process, low-boiling	(CAS No) 68410-97-9	30 - 60
Toluene	(CAS No) 108-88-3	30 - 60
Methyl ethyl ketone	(CAS No) 78-93-3	10 - 30
Rosin	(CAS No) 8050-09-7	0.1 - 1

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- First-aid measures general : If exposed or concerned, get medical attention/advice. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before re-use. Never give anything to an unconscious person.
- First-aid measures after inhalation : IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical attention. If breathing is difficult, supply oxygen. If breathing has stopped, give artificial respiration.
- First-aid measures after skin contact : IF ON SKIN (or clothing): Remove affected clothing and wash all exposed skin with water for at least 15 minutes. If irritation develops or persists, get medical attention.
- First-aid measures after eye contact : IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do so. If pain, blinking, or irritation develops or persists, get medical attention. Continue rinsing.
- First-aid measures after ingestion : IF SWALLOWED: rinse mouth thoroughly. Do not induce vomiting without advice from poison control center or medical professional. Get medical attention immediately.

#### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. Causes serious eye irritation. Suspected of damaging fertility. Suspected of damaging the unborn child. May cause an allergic skin reaction. Causes skin irritation. Causes damage to organs through prolonged or repeated exposure.

**Wilsonart® 600 Adhesive**

Symptoms/injuries after inhalation	: May be fatal if swallowed and enters airways. May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: May cause an allergic skin reaction. Causes skin irritation.
Symptoms/injuries after eye contact	: Causes serious eye irritation.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways.
Chronic symptoms	: Suspected of damaging fertility. Suspected of damaging the unborn child. Causes damage to organs through prolonged or repeated exposure.

**4.3. Indication of any immediate medical attention and special treatment needed**

No additional information available

**SECTION 5: Firefighting measures****5.1. Extinguishing media**

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide.
Unsuitable extinguishing media	: Water.

**5.2. Special hazards arising from the substance or mixture**

Fire hazard	: Flammable liquid and vapour.
Explosion hazard	: Static discharge may serve as an ignition source for this product.

**5.3. Advice for firefighters**

Firefighting instructions	: Exercise caution when fighting any chemical fire. Do not dispose of fire-fighting water in the environment. Prevent human exposure to fire, fumes, smoke and products of combustion.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

General measures	: Evacuate area. Keep upwind. Ventilate area. Spill should be handled by trained clean-up crews properly equipped with respiratory equipment and full chemical protective gear (see Section 8). Avoid vapor formation. In case of spills, beware of slippery floors and surfaces. Eliminate all sources of ignition. Vapor may cause flash fires. Vapors are heavier than air and can travel long distances to ignition sources.
------------------	--

**6.1.1. For non-emergency personnel**

Protective equipment	: Wear Protective equipment as described in Section 8.
Emergency procedures	: Evacuate unnecessary personnel.

**6.1.2. For emergency responders**

Protective equipment	: Wear suitable protective clothing, gloves and eye or face protection. Approved supplied-air respirator, in case of emergency.
----------------------	---

**Wilsonart® 600 Adhesive**

**6.2. Environmental precautions**

Prevent entry to sewers and public waters. Avoid release to the environment.

**6.3. Methods and material for containment and cleaning up**

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for cleaning up : Remove all sources of ignition. Avoid breathing of vapors. Wear appropriate respirator and other protective clothing. Ventilate. Shut off source of leak only if safe to do so. Soak up with absorbent material, and place in non-leaking containers for proper disposal.

**6.4. Reference to other sections**

No additional information available

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

Precautions for safe handling : Keep away from heat, sparks and open flames. Use adequate ventilation and avoid repeated or prolonged skin contact. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Ground/bond container and receiving equipment. Prohibit smoking in storage area.

**7.2. Conditions for safe storage, including any incompatibilities**

Storage conditions : Store in a well-ventilated place. Keep container tightly closed. Isolate from oxidizers, heat, sparks, electrical equipment and open flame. Closed containers may explode if exposed to extreme heat. Store in a cool dry place. Prohibit smoking in storage area. Do not store with acids or oxidizers. Electrical service in storage area must be rated for flammable liquids.

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

<b>Rosin (8050-09-7)</b>	
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established

<b>Distillates, petroleum, light distillate hydrotreating process, low-boiling (68410-97-9)</b>	
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established

<b>Toluene (108-88-3)</b>	
ACGIH TWA (ppm)	20 ppm
Remark (ACGIH)	Visual impair; female repro;

**Wilsonart® 600 Adhesive**

<b>Methyl ethyl ketone (78-93-3)</b>	
ACGIH TWA (ppm)	200 ppm
ACGIH STEL (ppm)	300 ppm
OSHA PEL (TWA) (mg/m <sup>3</sup> )	590 mg/m <sup>3</sup>
OSHA PEL (TWA) (ppm)	200 ppm
OSHA PEL (STEL) (mg/m <sup>3</sup> )	885 mg/m <sup>3</sup>
OSHA PEL (STEL) (ppm)	300 ppm

**8.2. Exposure controls**

Appropriate engineering controls : Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof equipment with flammable materials. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment : Safety glasses. Gloves. Protective clothing. Insufficient ventilation: wear respiratory protection.



Hand protection : Use gloves chemically resistant to this material when prolonged or repeated contact could occur. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested glove materials are: Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol laminate, PVC or vinyl.

Eye protection : Wear eye protection, including chemical splash goggles and a face shield when possibility exists for eye contact due to spraying liquid or airborne particles.

Skin and body protection : Wear long sleeves, and chemically impervious PPE/coveralls to minimize bodily exposure.

Respiratory protection : Wear a NIOSH-approved (or equivalent) full-facepiece airline respirator in the positive pressure mode with emergency escape provisions. In case of inadequate ventilation or risk of inhalation of vapors, use suitable respiratory equipment with gas filter (type A2). Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

Physical state : Liquid  
 Appearance : Clear to light yellow liquid.  
 Color : Clear to light yellow.  
 Odor : strong. Solvent.  
 Odor Threshold : No data available

**Wilsonart® 600 Adhesive**

pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 79 °C (174 °F)
Flash point	: -6.1 °C Closed Cup (21.0 °F)
Auto-ignition temperature	: 204 °C for lowest known component - light hydrotreated distillate (399 °F)
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: 38 mm Hg at 20 °C (calculated)
Relative vapour density at 20 °C	: 3.14 for highest component - Toluene (Air = 1)
Relative density	: No data available
Density	: 7 lb/gal
Solubility	: Water: Not soluble in water
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: 0.8 - 11.5 vol % LEL - Light hydrotreated distillate; UEL - Methyl ethyl ketone

**9.2. Other information**

VOC content	: 671 g/l Calculated (Per Liter of Material)
Other properties	: Percent Volatile: 79%.

**SECTION 10: Stability and reactivity****10.1. Reactivity**

No additional information available

**10.2. Chemical stability**

Stable under recommended handling and storage conditions (see section 7).

**10.3. Possibility of hazardous reactions**

None known.

**10.4. Conditions to avoid**

Heat, flame. Ignition sources.

**10.5. Incompatible materials**

Strong acids and alkalis, oxidizing agents, reducing agents, copper and copper alloys.

## Wilsonart® 600 Adhesive

### 10.6. Hazardous decomposition products

Carbon oxides (CO, CO<sub>2</sub>). Various hydrocarbons.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

<b>Rosin (8050-09-7)</b>	
LD50 oral rat	7600 mg/kg
LD50 dermal rabbit	> 2500 mg/kg
LC50 inhalation rat (mg/l)	1.5 mg/l/4h

<b>Toluene (108-88-3)</b>	
LD50 oral rat	2600 mg/kg
LD50 dermal rabbit	12000 mg/kg
LC50 inhalation rat (mg/l)	12.5 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.  
 Serious eye damage/irritation : Causes serious eye irritation.  
 Respiratory or skin sensitisation : May cause an allergic skin reaction.  
 Germ cell mutagenicity : Not classified.  
 Carcinogenicity : Not classified.

<b>Toluene (108-88-3)</b>	
IARC group	3 - Not classifiable

Reproductive toxicity : Suspected of damaging fertility. Suspected of damaging the unborn child.  
 Specific target organ toxicity (single exposure) : May cause drowsiness or dizziness.  
 Specific target organ toxicity (repeated exposure) : May cause damage to organs through prolonged or repeated exposure.  
 Aspiration hazard : May be fatal if swallowed and enters airways.  
 Symptoms/injuries after inhalation : May be fatal if swallowed and enters airways. May cause drowsiness or dizziness.  
 Symptoms/injuries after skin contact : May cause an allergic skin reaction. Causes skin irritation.  
 Symptoms/injuries after eye contact : Causes serious eye irritation.  
 Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways.  
 Chronic symptoms : Suspected of damaging fertility. Suspected of damaging the unborn child. Causes damage to organs through prolonged or repeated exposure.

**Wilsonart® 600 Adhesive**

**SECTION 12: Ecological information**

**12.1. Toxicity**

Ecology - general : No data available.

**12.2. Persistence and degradability**

<b>Wilsonart 600 Adhesive</b>	
Persistence and degradability	The product is not biodegradable.

**12.3. Bioaccumulative potential**

No additional information available

**12.4. Mobility in soil**

No additional information available

**12.5. Other adverse effects**

No additional information available

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

Waste treatment methods : Do not discharge to public wastewater systems without permit of pollution control authorities. No discharge to surface waters is allowed without an NPDES permit.

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not allow the product to be released into the environment.

**SECTION 14: Transport information**

In accordance with DOT

Transport document description : UN1133 Adhesives, containing a flammable liquid, 3, II

UN-No.(DOT) : 1133

DOT NA no. : UN1133

Proper Shipping Name (DOT) : Adhesives, containing a flammable liquid

Department of Transportation (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Hazard Classes

Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : II - Medium Danger

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L

## Wilsonart® 600 Adhesive

DOT Vessel Stowage Location : B - (i) The material may be stowed “on deck” or “under deck” on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) “On deck only” on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

### Additional information

Other information : **Limited Quantity Exception**-flammable liquids in Packing Group II, inner packagings not over 1.0 L (0.3 gallons) net capacity each, packed in a strong outer packaging.

### Transport by sea

No additional information available

### Air transport

No additional information available

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

<b>Wilsonart 600 Adhesive</b>	
All components of this product are listed on the TSCA Inventory or are exempt	
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard Immediate (acute) health hazard Fire hazard

	<b>CAS #:</b>	<b>108-88-3 (Toluene)</b>
Section 302 (EHS) TPQ		lb
Section 304 EHS RQ		lb
CERCLA RQ		1000 lb
Section 313		Listed on US SARA Section 313

	<b>CAS #:</b>	<b>78-93-3 (Methyl ethyl ketone)</b>
Section 302 (EHS) TPQ		lb
Section 304 EHS RQ		lb
CERCLA RQ		5000 lb
Section 313		Not Listed

### 15.2. International regulations

#### CANADA

No additional information available.

### 15.3. US State regulations

#### California Proposition 65

WARNING! This product contains chemicals known to the state of California to cause cancer, birth defects, or other reproductive harm.

**Wilsonart® 600 Adhesive**

<b>Benzene (71-43-2)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	Yes	No	Yes	

<b>Toluene (108-88-3)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
No	Yes	No	No	

<b>Ethylbenzene (100-41-4)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	

<b>Magnesium oxide (1309-48-4)</b>				
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Massachusetts - Right To Know List				


<b>Toluene (108-88-3)</b>				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List				

<b>Methyl ethyl ketone (78-93-3)</b>				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List				

**SECTION 16: Other information**

NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard : 4 - Will rapidly or completely vaporize at normal pressure and temperature, or is readily dispersed in air and will burn readily.



## Wilsonart® 600 Adhesive

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.

### HMIS III Rating

Health : 2  
Flammability : 4  
Physical : 0  
Personal Protection :

**Changes to this Revision:** Revise to GHS requirements.

**Prepared By:** Environmental, Health, and Safety Department, Wilsonart LLC.  
Telephone: 254-207-7000  
Internet: [www.wilsonart.com](http://www.wilsonart.com)

### Notice to Reader

***To the best of our knowledge, the information contained herein is accurate. However, neither the above named manufacturer nor any of its subsidiaries assumes any liability whatsoever for accuracy or completeness of the information contained herein.***

***Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.***

---

END OF MSDS DOCUMENT