Product: Cabinet & Wood Cleaner - 3063 Revision Date: 27-Jan-2015

SECTION 1 – IDENTIFICATION

Product Identifier

Cabinet & Wood Cleaner Product Name:

3063 **Product Code:**

Recommended Use of the Chemical and Restrictions for Use

Recommended Use: Cleaner and polish. **Restrictions for Use:** Use only as directed.

Details of the Supplier

Manufacturer: Magic American

> 755 Tri-State Parkway Gurnee, IL 60031 800-328-9248

Emergency Phone Number

24-Hour Number: 1-800-535-5053 International: 1-352-323-3500

SECTION 2 – HAZARDS IDENTIFICATION

Classification

Hazard Class	Category
Flammable aerosol	2
Gasses under pressure- liquefied gas	N/A

Label Elements

Hazard Symbols(s):





Signal Word(s): Warning

Hazard Statement(s): Flammable aerosol. Contains gas under pressure; may explode if heated.

Precautionary Statement(s): Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn even after use. Protect from sunlight. Do not expose to temperature exceeding 50°C/122°F. Store in well-ventilated place.

Other Hazards

1% of the mixture consists of ingredient(s) of unknown acute toxicity.

SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS			
Chemical Name	CAS Number	Wt %	
Petroleum distillates, hydrotreated light	64742-47-8	10-30	
Butane	106-97-8	3-7	
Propane	74-98-6	1-5	

The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

SECTION 4 – FIRST AID MEASURES

First Aid Measures

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical advice/attention if you feel unwell.

Eye Contact: In case of contact, immediately flush eyes with plenty of water. Remove contact lenses, if worn. If irritation persists, get medical attention.

Document No.: 130529-5 Page 1 of 5

Confirms to OSHA Hazard Communication Standard (CFR 29 1910.1200) HazCom 2012

Product: Cabinet & Wood Cleaner - 3063

Revision Date: 27-Jan-2015

Ingestion: Do not induce vomiting. If victim is conscious and alert, give 2-4 cupfuls of milk or water. Never give anything

by mouth to an unconscious person. Get medical attention immediately.

Skin: If irritation occurs, flush skin with plenty of water. Get medical attention if irritation persists.

Most Important Symptoms and Effects (Acute and Delayed)

Inhalation: May cause respiratory tract irritation.

Eye Contact: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production,

with possible redness and swelling.

Ingestion: May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

Skin: May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.

Indication of any Immediate Medical Attention and Special Treatment Needed

Note to Physician: Treat symptomatically.

SECTION 5 – FIRE FIGHTING MEASURES

Extinguishing Media

Suitable: Powder, water spray, foam, carbon dioxide.

Unsuitable: None known.

Specific Hazards Arising from Chemical

Flammable aerosol. Products of combustion include but are not limited to: oxides of carbon. Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

Protective Equipment and Precautions for Firefighters

Containers may explode when heated. Cool closed containers exposed to fire with water. Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Personal Precautions: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental Precautions: See Section 12 for ecological information.

Methods and Material for Containment and Cleaning Up

Eliminate sources of ignition. Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE). Scoop up material and place in a disposal container. Provide ventilation.

SECTION 7 – HANDLING AND STORAGE

Precautions for Safe Handling

Handling: Keep away from sources of ignitions.-No smoking. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not swallow. When using do not eat, drink or smoke. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

General Hygiene Advice: Launder contaminated clothing before use. Wash hands before eating, drinking, or smoking.

Conditions for Safe Storage, Including any Incompatibilities

Storage Conditions: Keep out of reach of children. Do not expose to temperatures exceeding 50°C/122°F. Store away from direct sunlight or other heat sources. Store in a well-ventilated place.

Incompatible Materials: Strong oxidizing agents.

SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Document No.: 130529-5 Page 2 of 5

Confirms to OSHA Hazard Communication Standard (CFR 29 1910.1200) HazCom 2012

Product: Cabinet & Wood Cleaner - 3063 Revision Date: 27-Jan-2015

Exposure Guidelines:

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Petroleum distillates, hydrotreated light (64742-47-8)	Not available	Not available	Not available
Butane (106-97-8)	1000 ppm	Not available	Not available
Propane (74-98-6)	1000 ppm	1800 mg/m ³	Not available

Appropriate Engineering Controls

Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

Individual Protection Measures

Respiratory Protection: In case of insufficient ventilation, wear suitable respiratory equipment.

Skin and Body Protection: Wear suitable protective clothing.

Eye/Face Protection: Safety glasses or goggles are recommended when using product.

General Work/Hygienic Practices: Handle in accordance with good industrial hygiene and safety practice.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Gas pressurized liquid, white foam

Odor: Cherry

Odor threshold: Not determined.

pH: 4.1

Melting point/freezing point: Not determined

Initial boiling point and boiling range: Not determined

Flash point: Not determined

Evaporation rate: Not determined

Flammability (solid, gas): Flammable aerosol

Upper/lower flammability or explosive limits: Not determined

Vapor pressure: Not determined Vapor density: Not determined

Relative density: 0.94

Solubility(ies): Not determined

Partition coefficient (n-octanol/water): Not determined

Auto-ignition temperature: Not determined

Decomposition temperature: Not determined

Viscosity: 160 cps @ 40°C (100°F)

SECTION 10 – STABILITY AND REACTIVITY

Reactivity: Not reactive under normal conditions.

Chemical stability: Stable under recommended storage conditions. Flammable aerosol. Contents under pressure.

Container may explode if heated. Do not puncture. Do not burn.

Possibility of hazardous reactions: None under normal use.

Conditions to avoid: Heat. Incompatible materials. Sources of ignition.

Incompatible materials: Strong oxidizing agents.

Hazardous decomposition products: May include and are not limited to: oxides of carbon.

SECTION 11 - TOXICOLOGICAL INFORMATION

Document No.: 130529-5 Page 3 of 5

Confirms to OSHA Hazard Communication Standard (CFR 29 1910.1200) HazCom 2012

Product: Cabinet & Wood Cleaner - 3063

Information on Toxicological Effects

Likely Routes of Exposure: Inhalation, skin contact, eye contact, ingestion

Information Related to Physical, Chemical, and Toxicological Effects

See section 4 of this SDS.

Delayed and Immediate Effects as well as Chronic Effects from Short and Long-term Exposure

Carcinogenicity: NTP: No IARC: No OSHA: No

Numerical Measures of Toxicity

Product	
ATE (oral)	>2000 mg/kg, rat
ATE (dermal)	>2000 mg/kg, rabbit
ATE (inhalation)	>5mg/l/4h

Component Information:

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Petroleum distillates, hydrotreated light (64742-47-8)	>5000 mg/kg (rat)	>2000 mg/kg (rabbit)	>5.2 mg/l/4h (rat)
Butane (106-97-8)	Not available	Not available	658g/m ³ /4h (rat)
Propane (74-98-6)	Not available	Not available	658g/l/4h (rat)

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity: Not established

Persistence and degradability: Not established Bioaccumulative potential: Not established

Mobility in soil: No additional information available

Other adverse effects: No additional information available.

SECTION 13 – DISPOSAL CONSIDERATIONS

See section 8 of this SDS for exposure controls and personal protection.

Dispose of the product and container in accordance with all applicable local, state, and federal regulations.

SECTION 14 – TRANSPORT INFORMATION

Note: Classification changes based on quantity, packaging, and method of shipment. See current shipping paper for most up to date shipping information.

UN1950, Aerosols, flammable, 2.1 **DOT (Ground):** Limited quantity

IATA (Air): Regulated

IMDG (Vessel): Limited quantity

SECTION 15 – REGULATORY INFORMATION

All ingredients in this product are listed or are excluded from listing on the US Toxic Substances Act (TSCA) Chemical Substance Inventory.

This product is labeled in accordance with regulations administered by the Consumer Product Safety Commission (CPSC). The use pattern and exposure in the workplace are generally not consistent with those experienced by consumers. The requirements of the Occupational Safety and Health Administration (OSHA) applicable to this Safety Data Sheet differ from the requirements of the CPSC and as a result, this SDS may contain additional health hazard information not pertinent to consumer use and not found on the product label.

SECTION 16 - OTHER INFORMATION

Issue Date: 27-Jan-2015


Document No.: 130529-5 Release Date: 1/10/2014 Page 4 of 5

Revision Date: 27-Jan-2015

materials or in any process, unless specified in the text.

Cabinet & Wood Cleaner - 3063

Revision Date: 27-Jan-2015



Revision Date: 27-Jan-2015

End of Safety Data Sheet

transportation, disposal, and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designed and may not be valid for such material used in combination with any other

Document No.: 130529-5 Page 5 of 5