

**LogOX 3-in-1 Forestry Tool Instructions**  
(Use the LogOX tools only as instructed  
and for the intended purposes)

- 1) **Lifting Technique:** Stand beside a stove-length log with the handle facing outward. Bend knees slightly and lower the hook over the center of the log, until the chisel tip bottom of the tool and hook are firmly engaged with it. Lift the log.
- 2) **Release:** Place the thumb of your free hand into the notch of the hook, while swinging the log upward and forwards, then pull up on the hook to release the log away from you. Alternate "Tap and release" method: Tap the nose of the hook on another log, while simultaneously pushing the handle down and forward slightly. (Scan QR code for instructions).
- 3) **Loading a Splitter:** Small to medium logs- simply swing the log up onto the splitting rail and lift hook to release. For a larger log, bend slightly at the knees, hold the Hauler with both hands, and lift log onto the rail. Place Hauler into your LogOX Holster, or nearby, while operating machinery.
- 4) **Cant Hook Handle:** Attach to the Hauler, by sliding through its circular opening and securing with hitch pin above the hook. Hauler can be used as a stand-alone short cant hook. Attach cant handle for extra leverage when rolling larger logs over to complete cuts, in order to prevent chainsaw damage.
- 5) **Timberjack:** Attach to Hauler's base with two hitch pins. Combine LogOX cant handle and timberjack accessories to lift smaller diameter logs for quick, clean, cuts. Ensure the log you're lifting is stably balanced, before beginning to cut.

Thank you for purchasing the LogOX. For LogOX accessories please visit us at:

**WWW.THELOGOX.COM**  
**American Tools For Woodsmen™**