

TECHNICAL DATA DIGEST

HARRIS ACRYLIC WALL PRIMER INTERIOR/EXTERIOR

PRODUCT DESCRIPTION:	Harris Acrylic Wall Primer is an alkali resistant surface conditioner based on styrene acrylic resin. It provides a barrier coat for high pH surface. It also seals the surface preventing moisture to affect the finish coat, and avoid premature failures. It is recommended as a primer for new concrete surfaces, stucco, concrete, block, mortar joint surfaces, gypsum board and to seal loose chalk, in light condition, on previously painted surfaces. This primer is also sealer designed to consolidate light chalk and concrete dust on the surface, allowing a non-penetrating coating to adhere properly. Retards efflorescence and promote good paint adhesion.
PACKAGING:	1 Gallon and 5 Gallons Containers
FINISH:	Flat (0-5%) @ Geometry 60°
COLOR:	White
DENSITY:	11.30 LBS
VISCOSITY:	75-80 KU'S (KREBS-STORMER)
GRIND:	6 NS min.
TOTAL SOLIDS (by weight):	50.23%
TOTAL SOLIDS (by volume):	37.81%
NON VOLATILE VEHICLE:	24%
TOTAL NON-VOLATILE:	53%
PIGMENTS:	TiO ₂ 6.8% , Zinc Oxide 1%, Silicates 20%
DRYING TIME:	Set to touch between 20-30 minutes. Recoat 2 hours to recoat.

**TECHNICAL DATA DIGEST
HARRIS WALL PRIMER (Cont.)**

APPLICATION

SURFACE
PREPARATION:

Surfaces must be dry, clean and free of oil, grease, dirt and loose concrete.

NEW CONCRETE AND
PAINTED SURFACES:

All surfaces must be dry and free of oil, dust, etc., before painting. All surfaces previously coated with cement base water paints, should be washed before applying Harris Acrylic Wall Primer. Can be applied over light chalky surfaces.

THINNING:

Not recommended. Do not mix with solvent or thinned paints.

MILDEWED
SURFACES:

Clean by scrubbing with water containing 16 oz. household bleach and 2 oz. liquid detergent per gallon of water. Then, follow procedure as for new surfaces.

METHOD OF
APPLICATION:

To insure complete mixing stir thoroughly. Apply uniformly with brush, roller or spray. Porous or texture surfaces will require more primer. Avoid application in direct sun or on hot surfaces.

COVERAGE:

On smooth surfaces apply at a rate of approximately 350-400 sq. ft per gallon. Porous or texture surfaces will require more primer.

CLEANUP:

Wipe up drips and spatters with a wet cloth with soap and water; clean equipment with soapy water.

PRECAUTIONS:

Do not take internally. Close container after each use.
KEEP OUT OF THE REACH OF CHILDREN!