Page 1 of 6 Revision date: 08/17/2016

Section 1 - Product and Company Identification

Product Identifiers:

Product Name: Hot Shot Bed Bug Killer With Egg Kill

EPA Registration Number: 9688-327-8845

Product Use: Insecticide - Crawling Bug, Non-aerosol, Ready-To-Use

Details of the Supplier of the Safety Data Sheet:

Manufacturer/Supplier: Chemsico

Division of United Industries Corp.

P.O. Box 142642

St. Louis, MO 63114-0642

For medical emergencies: 1-800-917-5431 **For medical emergencies:** 1-800-633-2873

Section 2 - Hazards Identification

Conforms to Hazard Communication Standard 29 CFR 1910.1200.

GHS Classification of Substance or Mixture:

Physical Hazards GHS Classification Not classified as a physical hazard

Health Hazards GHS Classification Primary Eye Irritant – Category 2B

GHS Label Elements:

Hazard pictogram(s): None
Signal word: WARNING

Hazard statements: • Causes eye irritation

Precautionary Statements: • Wash hands thoroughly with soap and water after

handling. If in eyes: Rinse cautiously with soap and water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get

medical advice/attention.

Section 3 - Composition / Information on Ingredients

| Chemical Name | CAS# | Weight Percent |
|---------------|------------|----------------|
| Cypermethrin | 52315-07-8 | 0.20% |

Note: Ingredients not identified are proprietary or non-hazardous. Values are not product specifications.

Section 4 - First Aid Measures

Eye contact: Hold eye open and rinse slowly and gently with water for

15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing. Call a poison control

center or doctor for treatment advice.

Skin contact:No special requirementsInhalation:No special requirementsIngestion:No special requirements

Page 2 of 6 Revision date: 08/17/2016

Notes to physician: None

General advice: If you feel unwell, seek medical advice (show the label

where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect

themselves. Keep out of reach of children.

Section 5 - Fire Fighting Measures

Flammable properties: Not flammable by OSHA criteria. **Suitable extinguishing media:** Water fog, foam, CO₂, dry chemical

Unsuitable extinguishing media: Not available

Specific hazards arising from the

chemical: Container may melt and leak in heat of fire. Do not allow

run-off from firefighting to enter drains or water courses.

Protective equipment for firefighters: Firefighters should wear full protective clothing including

self-contained breathing apparatus.

Hazardous combustion products:

Sensitivity to mechanical impact:

Explosion data:

None known

Not available

Sensitivity to static discharge:

Not available

Personal precautions: Keep unnecessary personnel away. Do not touch or walk

through spilled material. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep people away from and upwind of spill/leak.

Section 6 - Accidental Release Measures

Personal precautions: Remove all sources of ignition. Wear personal protective

equipment. Wash thoroughly after handling.

For emergency responders: If specialized clothing is required to deal with the spillage,

take note of any information in Section 8 on suitable and

unsuitable materials.

Environmental precautions: Avoid dispersal of spilled material and runoff and contact

with soil, waterways, drains and sewers.

Methods for containment and

cleaning up:

Stop leak if without risk. Move containers from spill area. Before attempting clean up, refer to hazard data given above. Small spills may be absorbed with earth, sand or absorbent material swept up and placed in suitable, covered, and labeled containers. Prevent large spills from

entering sewers or waterways. Contact emergency services and supplier for advice. Never return spills in

original containers for re-use.

Section 7 - Handling and Storage

Precautions for safe handling: Put on appropriate personal protective equipment (see

Section 8). Do not use near heat, open flame or any other ignition source. Avoid contact with skin, eyes and clothing. Use an appropriate respirator when adequate ventilation

Page 3 of 6 Revision date: 08/17/2016

is not available. Avoid breathing vapors or spray mists of

the product.

Storage: Store product in a cool, dry place, out of reach of children.

Keep container closed when not in use. Keep away from food, drink and animal feedingstuffs. Keep tightly closed. Non-refillable container. Do not reuse or refill this container. Place in trash or offer for recycling if available.

Section 8 - Exposure Controls / Personal Protection

Exposure guidelines:

| Components with Occupational Exposure Limits | | | | | |
|--|-----|---------------------------------|--|-----------|-----------|
| Exposure Limits | | | | | |
| | | OSHA PEL ACGIH TLV Supplier OEL | | | plier OEL |
| Chemical name | | ppm mg/m³ ppm mg/m³ ppm m | | mg/m³ | |
| Cypermethrin | TWA | Not listed Not listed Not l | | ot listed | |

Engineering controls: General ventilation normally adequate.

Personal protective equipment:

Eye/Face protection: During application, prevent entry into eyes. Wear safety

glasses with side shields if using in large applications.

Skin and body protection: Wash hands after handling.

Respiratory protection: None required

General hygiene considerations: Handle in accordance with good industrial hygiene and

safety practice. When using, do not eat or drink. Wash hands before breaks and immediately after handling the

product.

Section 9 - Physical & Chemical Properties

Appearance: Hazy

Color: Light yellow Physical state: Liquid

Odor: Aromatic solvent, fragrance & pyrethroid

Odor threshold: No data available

pH: 4.8 – 6.0

Melting point:No data availableFreezing point:No data availableBoiling point:No data available

Flash point: >200°F

Evaporation rate: No data available

Flammability limits in air,

lower, % by volume:No data available

Flammability limits in air,

upper, % by volume: No data availableVapor pressure: No data availableVapor density: No data available

Page 4 of 6 Revision date: 08/17/2016

Relative density @ 20°C: 1.00

Octanol/water coefficient:No data availableAuto-ignition temperature:No data availableDecomposition temperature:No data availableSolubility:Soluble in water

% Volatile organic compounds: 0.2

Section 10 - Chemical Stability & Reactivity Information

Reactivity

Conditions to avoid: Do not mix with other chemicals.

Incompatible materials: Avoid strong oxidizers.

Chemical stability

Product stability: Stable under recommended storage conditions.

Other

Hazardous decomposition products: None known

Possibility of hazardous reactions: Hazardous polymerization does not occur.

Section 11 - Toxicological Information

Primary eye irritation: Causes moderate eye irritation (EPA tox. category III)

Primary skin irritation: Non-irritating (EPA tox. category IV)

Acute dermal: $LD_{50} > 5000 \text{ mg/kg (EPA tox. category IV)}$

Acute inhalation: $LC_{50} > 2 \text{ mg/L}$ (EPA tox. category IV)

Acute oral: $LD_{50} > 5000 \text{ mg/kg}$ (EPA tox. category IV)

Sensitization:

Chronic effects:

No data available

Carcinogenicity:

No data available

No data available

No data available

No data available

Reproductive effects:

No data available

Teratogenicity:

No data available

No data available

No data available

Section 12 - Ecological Information

Environmental effects: No data available

Aquatic toxicity: Toxic to aquatic organisms.

Persistence / degradability:

Bioaccumulation / accumulation:

Partition coefficient:

Mobility in environmental media:

Chemical fate information:

No data available

No data available

No data available

Page 5 of 6 Revision date: 08/17/2016

Section 13 - Disposal Considerations

Waste codes: Not available

Disposal instructions: Dispose in accordance with all applicable regulations.

Waste from residues/unused

products: Not available **Contaminated packaging:** Not available

Section 14 - Transportation Information

U.S. Department of Transportation

(DOT): Not regulated

IATA:

For quantities < 5kg/5L ship as: Not regulated

For quantities ≥ *5kg/5L ship as:* UN3082, Environmentally Hazardous Substance, Liquid,

N.O.S., (Cypermethrin), Marine Pollutant, Limited Quantity,

9, III

IMDG:

For quantities < 5kg/5L ship as: Not regulated

For quantities ≥ *5kg/5L ship as:* UN3082, Environmentally Hazardous Substance, Liquid,

N.O.S., (Cypermethrin), Marine Pollutant, Limited Quantity,

9, III

Section 15 - Regulatory Information

29 CFR 1910.1200 hazardous chemical

Occupational Safety and Health

Administration (OSHA): No

CERCLA (Superfund) reportable

quantity: Not available

Hazard categories

Superfund Amendments and Reauthorization Act of 1986 (SARA):

Immediate HazardNoDelayed HazardNoFire HazardNoPressure HazardNoReactivity HazardNo

Section 302 extremely hazardous

Substance: No
Section 311 hazardous chemical: No

Clean Air Act (CAA):

Clean Water Act (CWA):

Not available

State regulations: None

FIFRA labeling: This chemical is a pesticide product registered by the Environmental Protection

Agency and is subject to certain labeling requirements under federal pesticide law. These requirements differ from the classification criteria and hazard information required for safety data sheets, and for workplace non-pesticide chemicals. Following is the hazard information as required on the pesticide label:

Page 6 of 6 Revision date: 08/17/2016

Signal word: CAUTION

Precautionary statements:

Causes moderate eye irritation. Avoid contact with eyes or clothing. Wear protective eyewear. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco or using the toilet.

This product is toxic to fish and other aquatic organisms. To protect the environment, do not allow pesticide to enter or run off into storm drains, drainage ditches, gutters or surface waters. Applying this product in calm weather when rain is not predicted for the next 24 hours will help ensure that wind or rain does not blow or wash pesticide off treatment area.

Notification status: All ingredients of this product are listed or are excluded from listing on the U.S.

Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

California Prop. 65: This product does not contain any chemicals known to the state of California to

cause cancer, birth defects or any other reproductive harm.

Disclaimer: Information contained herein was obtained from sources considered technically

accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any

information contained in this document.

SECTION 16 - OTHER INFORMATION

HMIS ratings: Health Hazard 1 Flammability 0 Physical Hazard 0

Item number(s): HG-96441; HG-96442; HG-96443; HG-96518

Formula number(s): 21-1430 Issue date: 3/1/2016

Prepared by: Spectrum Group

Division of United Industries Corp.

P.O. Box 142642

St. Louis, MO 63114-0642

(800) 242-1166

SAFETY DATA SHEET

Revision Number 1

Issuing Date No data available

Revision Date 12-Jun-2013



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE **COMPANY/UNDERTAKING**

Product identifier

Product Name Alkaline Battery

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Alkaline battery

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Name Spectrum Brands, Inc. **Supplier Address** 3001 Deming Way Middleton WI 53562

USA

Supplier Phone Number Phone:703-527-3887

> Contact Phone1-479-254-1729 marcy.stokes@spectrumbrands.com

Emergency telephone number

2. HAZARDS IDENTIFICATION

Classification

Supplier Email

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200) This product is an article which is a sealed battery and as such does not require an MSDS per the OSHA hazard communication standard unless ruptured. The hazards indicated are for a ruptured battery.

| Acute toxicity - Oral | Category 4 |
|---|---------------------------|
| Acute toxicity - Inhalation (Gases) | Category 4 |
| Acute toxicity - Inhalation (Dusts/Mists) | Category 4 |
| Skin corrosion/irritation | Category 1 Sub-category A |
| Serious eve damage/eve irritation | Category 1 |



Specific target organ toxicity (repeated exposure)

Category 2

GHS Label elements, including precautionary statements

Emergency Overview

Signal word

Danger

Hazard Statements

Harmful if swallowed Harmful if inhaled

Causes severe skin burns and eye damage

May cause damage to organs through prolonged or repeated exposure



This product is an article which contains a chemical substance. Safety information is given for exposure to the article as sold. Intended use of the product should not result in exposure to the chemical substance This is a battery. In case of rupture: the above hazards exist.

Appearance Solid Physical State Solid Odor Odorless

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling Do not eat, drink or smoke when using this product Use only outdoors or in a well-ventilated area Do not breathe dust/fume/gas/mist/vapors/spray Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response

Immediately call a POISON CENTER or doctor/physician Specific treatment (see supplemental first aid instructions on this label)

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Immediately call a POISON CENTER or doctor/physician

Skin

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower Wash contaminated clothing before reuse

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing Call a POISON CENTER or doctor/physician if you feel unwell Immediately call a POISON CENTER or doctor/physician

Ingestion

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell Rinse mouth Do NOT induce vomiting

(U

Page 2/13

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

5% of the mixture consists of ingredient(s) of unknown toxicity

Other information

Toxic to aquatic life with long lasting effects

Interactions with Other Chemicals

Use of alcoholic beverages may enhance toxic effects.

3. COMPOSITION/INFORMATION ON INGREDIENTS

.

| Chemical Name | CAS No | Weight-% | Trade Secret |
|---------------------|-----------|----------|--------------|
| Manganese dioxide | 1313-13-9 | 15 - 40 | * |
| Steel | 7439-89-6 | 19-23 | * |
| Zinc | 7440-66-6 | 10 - 30 | * |
| Potassium hydroxide | 1310-58-3 | 5 - 10 | * |
| Graphite | 7782-42-5 | 3 - 7 | * |
| Barium sulfate | 7727-43-7 | 3 - 7 | * |

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

First aid measures

General Advice First aid is upon rupture of sealed battery.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Seek immediate

medical attention/advice.

Skin Contact Wash off immediately with soap and plenty of water while removing all

contaminated clothes and shoes. Seek immediate medical attention/advice.

Inhalation Remove to fresh air. If breathing has stopped, give artificial respiration. Get

medical attention immediately. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If

breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary

edema may occur. Get medical attention immediately if symptoms occur.

(III)

Page 3/13

Ingestion Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water.

Never give anything by mouth to an unconscious person. Call a physician or

poison control center immediately.

Self-protection of the first aider Ensure that medical personnel are aware of the material(s) involved, take

precautions to protect themselves and prevent spread of contamination. Avoid contact with skin, eyes or clothing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as

required. Wear personal protective clothing (see section 8).

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and Burning sensation. Coughing and/ or wheezing. Difficulty in breathing.

Effects

Indication of any immediate medical attention and special treatment needed

Notes to Physician Product is a corrosive material. Use of gastric lavage or emesis is

contraindicated. Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood pressure may occur with moist rales, frothy

sputum, and high pulse pressure.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

CAUTION: Use of water spray when fighting fire may be inefficient.

Specific Hazards Arising from the Chemical

The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of irritating gases and vapors.

Uniform Fire Code Corrosive: Other--Solid

Toxic: Solid

Oxidizer: Class 1--Solid

Hazardous Combustion Products

Carbon oxides.

Explosion Data

Sensitivity to Mechanical Impact No.

Sensitivity to Static Discharge No.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

(III)

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Attention! Corrosive material. Avoid contact with skin, eyes or clothing. Ensure adequate

ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Avoid generation of dust. Do not

breathe dust.

Other Information Refer to protective measures listed in Sections 7 and 8.

Environmental Precautions

Environmental Precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage

if safe to do so. Should not be released into the environment. Do not allow to enter into

soil/subsoil. Prevent product from entering drains.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning upPick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling In case of rupture: Handle in accordance with good industrial hygiene and safety practice.

Avoid contact with skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Use only with adequate ventilation and in closed systems. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash

before reuse. Do not breathe dust. Avoid generation of dust.

Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from

moisture. Store locked up. Keep out of the reach of children. Store away from other

materials.

Incompatible Products Acids. Bases. Oxidizing agent.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

| Chemical Name | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|---------------|-----------|----------|------------|

| Manganese dioxide | TWA: 0.02 mg/m ³ Mn | (vacated) Ceiling: 5 mg/m ³ | IDLH: 500 mg/m³ Mn |
|---------------------|---------------------------------------|---|--|
| 1313-13-9 | TWA: 0.1 mg/m ³ Mn | Ceiling: 5 mg/m ³ Mn | TWA: 1 mg/m ³ Mn |
| | | _ | STEL: 3 mg/m ³ Mn |
| Zinc | STEL: 10 mg/m ³ respirable | TWA: 5 mg/m ³ fume | IDLH: 500 mg/m ³ |
| 7440-66-6 | fraction | TWA: 15 mg/m ³ total dust | Ceiling: 15 mg/m ³ dust |
| | TWA: 2 mg/m ³ respirable | TWA: 5 mg/m ³ respirable | TWA: 5 mg/m ³ dust and fume |
| | fraction | fraction | STEL: 10 mg/m ³ fume |
| Potassium hydroxide | Ceiling: 2 mg/m ³ | (vacated) Ceiling: 2 mg/m ³ | Ceiling: 2 mg/m ³ |
| 1310-58-3 | | , , , | |
| Graphite | TWA: 2 mg/m ³ respirable | TWA: 15 mg/m ³ total dust | IDLH: 1250 mg/m ³ |
| 7782-42-5 | fraction all forms except graphite | synthetic | TWA: 2.5 mg/m ³ respirable |
| | fibers | TWA: 5 mg/m ³ respirable | dust |
| | | fraction synthetic | |
| | | (vacated) TWA: 2.5 mg/m ³ | |
| | | respirable dust natural | |
| | | (vacated) TWA: 10 mg/m ³ total | |
| | | dust synthetic | |
| | | (vacated) TWA: 5 mg/m ³ | |
| | | respirable fraction synthetic | |
| | | TWA: 15 mppcf natural | |
| Barium sulfate | TWA: 5 mg/m ³ inhalable | TWA: 15 mg/m ³ total dust | TWA: 10 mg/m ³ total dust |
| 7727-43-7 | fraction, particulate matter | TWA: 5 mg/m ³ respirable | TWA: 5 mg/m ³ respirable dust |
| | containing no asbestos and <1% | fraction | |
| | crystalline silica | (vacated) TWA: 10 mg/m ³ total | |
| | - | dust | |
| | | (vacated) TWA: 5 mg/m ³ | |
| | | respirable fraction | |

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life or Health

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d

962 (11th Cir., 1992) See section 15 for national exposure control parameters

Appropriate engineering controls

Engineering Measures Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection Face protection shield.

Skin and Body Protection Wear protective gloves and protective clothing. Long sleeved clothing. Chemical resistant

apron. Impervious gloves.

Respiratory Protection No protective equipment is needed under normal use conditions. If exposure limits are

exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or

smoke when using this product. Take off contaminated clothing and wash before reuse. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. For environmental protection, remove and wash all

contaminated protective equipment before re-use. Do not breathe dust.

9. PHYSICAL AND CHEMICAL PROPERTIES

(U)

Physical and Chemical Properties

Physical State Solid Appearance Solid

AppearanceSolidOdorOdorlessColorNo information availableOdor ThresholdNo information available

<u>Property</u> <u>Values</u> <u>Remarks Method</u>

No data available None known рΗ Melting / freezing point No data available None known None known Boiling point / boiling range No data available **Flash Point** No data available None known **Evaporation Rate** No data available None known Flammability (solid, gas) No data available None known

Flammability Limit in Air
Upper flammability limit
No data available

Lower flammability limit No data available Vapor pressure No data available None known Vapor density No data available None known **Specific Gravity** No data available None known **Water Solubility** Immiscible in water None known Solubility in other solvents No data available None known Partition coefficient: n-octanol/waterNo data available None known **Autoignition temperature** No data available None known **Decomposition temperature** No data available None known Kinematic viscosity No data available None known None known

Dynamic viscosityNo data availableExplosive propertiesNo data availableOxidizing PropertiesNo data available

Other Information

Softening Point

VOC Content (%)

Particle Size

No data available

No data available

No data available

Particle Size Distribution

(UL)

Page 7/13

Revision Date 12-Jun-2013 1101240 - Alkaline Battery

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Exposure to air or moisture over prolonged periods. Excessive heat.

Incompatible materials

Acids. Bases. Oxidizing agent.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information Product does not present an acute toxicity hazard based on known or supplied information.

In case of rupture:.

Inhalation Specific test data for the substance or mixture is not available. Corrosive by inhalation.

> (based on components). Inhalation of corrosive fumes/gases may cause coughing, choking, headache, dizziness, and weakness for several hours. Pulmonary edema may occur with tightness in the chest, shortness of breath, bluish skin, decreased blood pressure, and increased heart rate. Inhaled corrosive substances can lead to a toxic edema of the lungs. Pulmonary edema can be fatal. May cause irritation of respiratory tract. Harmful by

inhalation.

Eye Contact Specific test data for the substance or mixture is not available. Causes burns. (based on

components). Corrosive to the eyes and may cause severe damage including blindness.

Causes serious eye damage. May cause irreversible damage to eyes.

Skin Contact Specific test data for the substance or mixture is not available. Corrosive. (based on

components). Causes burns.

Ingestion Specific test data for the substance or mixture is not available. Causes burns. (based on

components). Ingestion causes burns of the upper digestive and respiratory tracts. May cause severe burning pain in the mouth and stomach with vomiting and diarrhea of dark blood. Blood pressure may decrease. Brownish or yellowish stains may be seen around the mouth. Swelling of the throat may cause shortness of breath and choking. May cause lung damage if swallowed. May be fatal if swallowed and enters airways. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea,

vomiting and diarrhea. May be harmful if swallowed.

Page 8/13

Component Information

| Chemical Name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|----------------------------------|---------------------|-------------|-----------------|
| Manganese dioxide 1313-13-9 | = 9000 mg/kg (Rat) | - | - |
| Potassium hydroxide 1310-58-3 | = 214 mg/kg (Rat) | - | - |
| Graphite 7782-42-5 | > 10000 mg/kg (Rat) | - | - |

Information on toxicological effects

Symptoms Erythema (skin redness). Burning. May cause blindness. Coughing and/ or wheezing.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Mutagenic Effects No information available.

Carcinogenicity Contains no ingredient listed as a carcinogen.

Reproductive Toxicity No information available.

STOT - single exposure No information available.

STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure. Based on

classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from

chronic or repeated exposure. (STOT RE).

Chronic Toxicity Chronic exposure to corrosive fumes/gases may cause erosion of the teeth followed by jaw

necrosis. Bronchial irritation with chronic cough and frequent attacks of pneumonia are common. Gastrointestinal disturbances may also be seen. Avoid repeated exposure. Prolonged exposure may cause chronic effects. May cause adverse effects on the bone

marrow and blood-forming system.

Target Organ Effects Respiratory system. Eyes. Skin. Gastrointestinal tract (GI). Blood. Central Nervous System

(CNS). Central Vascular System (CVS). Kidney. Cardiovascular system. Liver.

Aspiration Hazard No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)
785.00 mg/kg
ATEmix (inhalation-gas)
10,465.00 ppm (4 hr)
ATEmix (inhalation-dust/mist)
3.50 mg/l
ATEmix (inhalation-vapor)
26.00 ATEmix



Page 9/13

Revision Date 12-Jun-2013 1101240 - Alkaline Battery

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects.

| Chemical Name | Toxicity to Algae | Toxicity to Fish | Toxicity to Microorganisms | Daphnia Magna (Water Flea) |
|---------------------|---------------------------|----------------------------|-------------------------------|-------------------------------|
| Zinc | 96h EC50: 0.11 - 0.271 | 96h LC50: 2.16 - 3.05 mg/L | | 48h EC50: 0.139 - 0.908 |
| 7440-66-6 | mg/L (Pseudokirchneriella | (Pimephales promelas) 96h | | mg/L |
| | subcapitata) 72h EC50: | LC50: 0.211 - 0.269 mg/L | | |
| | 0.09 - 0.125 mg/L | (Pimephales promelas) 96h | | |
| | (Pseudokirchneriella | LC50: = 2.66 mg/L | | |
| | subcapitata) | (Pimephales promelas) 96h | | |
| | | LC50: = 30 mg/L (Cyprinus | | |
| | | carpio) 96h LC50: = 0.45 | | |
| | | mg/L (Cyprinus carpio) 96h | | |
| | | LC50: = 7.8 mg/L (Cyprinus | | |
| | | carpio) 96h LC50: = 3.5 | | |
| | | mg/L (Lepomis macrochirus) | | |
| | | 96h LC50: = 0.24 mg/L | | |
| | | (Oncorhynchus mykiss) 96h | | |
| | | LC50: = 0.59 mg/L | | |
| | | (Oncorhynchus mykiss) 96h | | |
| | | LC50: = 0.41 mg/L | | |
| | | (Oncorhynchus mykiss) | | |
| Potassium hydroxide | | 96h LC50: = 80 mg/L | | |
| 1310-58-3 | | (Gambusia affinis) | | |

Persistence and Degradability

No information available.

Bioaccumulation

| Chemical Name | Log Pow |
|----------------------------------|---------|
| Manganese dioxide 1313-13-9 | <0 |
| Potassium hydroxide 1310-58-3 | 0.83 |

Other adverse effects
No information available.

Page 10/13

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods

This material, as supplied, is not a hazardous waste according to Federal regulations (40)

CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local

regulations for additional requirements.

Contaminated Packaging Dispose of contents/containers in accordance with local regulations.

California Hazardous Waste Codes 181

This product contains one or more substances that are listed with the State of California as a hazardous waste.

| Chemical Name | California Hazardous Waste |
|---------------------|----------------------------|
| Zinc | Ignitable powder Toxic |
| 7440-66-6 | |
| Potassium hydroxide | Toxic |
| 1310-58-3 | Corrosive |
| Barium sulfate | Toxic soluble |
| 7727-43-7 | |

14. TRANSPORT INFORMATION

DOT NOT REGULATED

TDG Not regulated

MEX Not regulated

ICAO Not regulated

IATA Not regulated

IMDG/IMO Not regulated

RID Not regulated

ADR Not regulated

ADN Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA Complies

DSL All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory



DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

| Chemical Name | CAS No | Weight-% | SARA 313 - Threshold Values % |
|-------------------------------|-----------|----------|----------------------------------|
| Manganese dioxide - 1313-13-9 | 1313-13-9 | 15 - 40 | 1.0 |
| Zinc - 7440-66-6 | 7440-66-6 | 10 - 30 | 1.0 |
| Barium sulfate - 7727-43-7 | 7727-43-7 | 3 - 7 | 1.0 |

SARA 311/312 Hazard Categories

| Acute Health Hazard | No |
|-----------------------------------|----|
| Chronic Health Hazard | No |
| Fire Hazard | No |
| Sudden release of pressure hazard | No |
| Reactive Hazard | No |

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

| Chemical Name | CWA - Reportable Quantities | CWA - Toxic Pollutants | CWA - Priority Pollutants | CWA - Hazardous Substances |
|----------------------------------|--------------------------------|------------------------|---------------------------|-------------------------------|
| Zinc 7440-66-6 | | X | X | |
| Potassium hydroxide 1310-58-3 | 1000 lb | | | X |

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

| Chemical Name | Hazardous Substances RQs | Extremely Hazardous Substances RQs | RQ |
|----------------------------------|--------------------------|------------------------------------|---|
| Zinc 7440-66-6 | 1000 lb | | RQ 454 kg final RQ RQ 1000 lb final RQ |
| Potassium hydroxide 1310-58-3 | 1000 lb | | RQ 1000 lb final RQ RQ 454 kg final RQ |

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

.

| Chemical Name | New Jersey | Massachusetts | Pennsylvania | Rhode Island | Illinois |
|----------------------------------|------------|---------------|--------------|--------------|----------|
| Manganese dioxide 1313-13-9 | | | Χ | Χ | Χ |
| Zinc 7440-66-6 | Х | X | Х | Х | |
| Potassium hydroxide 1310-58-3 | X | X | Χ | X | |
| Barium sulfate 7727-43-7 | X | X | Χ | X | |
| Graphite 7782-42-5 | Χ | X | Χ | | |



International Regulations

Mexico

National occupational exposure limits

| Component | Carcinogen Status | Exposure Limits |
|-----------------------|-------------------|------------------------------------|
| Manganese dioxide | | Mexico: TWA= 0.2 mg/m ³ |
| 1313-13-9 (15 - 40) | | _ |
| Graphite | | Mexico: TWA= 2 mg/m ³ |
| 7782-42-5 (3 - 7) | | _ |

Mexico - Occupational Exposure Limits - Carcinogens

Canada

WHMIS Hazard Class

Non-controlled

16. OTHER INFORMATION

NFPA Health Hazards 0 Flammability 0 Instability 0 Physical and Chemical Hazards -

HMIS Health Hazards 0 Flammability 0 Physical Hazard 0 Personal Protection

Χ

Prepared By Product Stewardship

23 British American Blvd. Latham, NY 12110 1-800-572-6501

Revision Date 12-Jun-2013

Revision Note No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet

U

SAFETY DATA SHEET

Revision Number 1

Issuing Date No data available

Revision Date 12-Jun-2013



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE **COMPANY/UNDERTAKING**

Product identifier

Product Name Alkaline Battery

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Alkaline battery

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Name Spectrum Brands, Inc. **Supplier Address** 3001 Deming Way Middleton WI 53562

USA

Supplier Phone Number Phone:703-527-3887

> Contact Phone1-479-254-1729 marcy.stokes@spectrumbrands.com

Emergency telephone number

2. HAZARDS IDENTIFICATION

Classification

Supplier Email

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200) This product is an article which is a sealed battery and as such does not require an MSDS per the OSHA hazard communication standard unless ruptured. The hazards indicated are for a ruptured battery.

| Acute toxicity - Oral | Category 4 |
|---|---------------------------|
| Acute toxicity - Inhalation (Gases) | Category 4 |
| Acute toxicity - Inhalation (Dusts/Mists) | Category 4 |
| Skin corrosion/irritation | Category 1 Sub-category A |
| Serious eve damage/eve irritation | Category 1 |



Specific target organ toxicity (repeated exposure)

Category 2

GHS Label elements, including precautionary statements

Emergency Overview

Signal word

Danger

Hazard Statements

Harmful if swallowed Harmful if inhaled

Causes severe skin burns and eye damage

May cause damage to organs through prolonged or repeated exposure



This product is an article which contains a chemical substance. Safety information is given for exposure to the article as sold. Intended use of the product should not result in exposure to the chemical substance This is a battery. In case of rupture: the above hazards exist.

Appearance Solid Physical State Solid Odor Odorless

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling Do not eat, drink or smoke when using this product Use only outdoors or in a well-ventilated area Do not breathe dust/fume/gas/mist/vapors/spray Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response

Immediately call a POISON CENTER or doctor/physician Specific treatment (see supplemental first aid instructions on this label)

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Immediately call a POISON CENTER or doctor/physician

Skin

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower Wash contaminated clothing before reuse

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing Call a POISON CENTER or doctor/physician if you feel unwell Immediately call a POISON CENTER or doctor/physician

Ingestion

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell Rinse mouth Do NOT induce vomiting

(U

Page 2/13

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

5% of the mixture consists of ingredient(s) of unknown toxicity

Other information

Toxic to aquatic life with long lasting effects

Interactions with Other Chemicals

Use of alcoholic beverages may enhance toxic effects.

3. COMPOSITION/INFORMATION ON INGREDIENTS

.

| Chemical Name | CAS No | Weight-% | Trade Secret |
|---------------------|-----------|----------|--------------|
| Manganese dioxide | 1313-13-9 | 15 - 40 | * |
| Steel | 7439-89-6 | 19-23 | * |
| Zinc | 7440-66-6 | 10 - 30 | * |
| Potassium hydroxide | 1310-58-3 | 5 - 10 | * |
| Graphite | 7782-42-5 | 3 - 7 | * |
| Barium sulfate | 7727-43-7 | 3 - 7 | * |

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

First aid measures

General Advice First aid is upon rupture of sealed battery.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Seek immediate

medical attention/advice.

Skin Contact Wash off immediately with soap and plenty of water while removing all

contaminated clothes and shoes. Seek immediate medical attention/advice.

Inhalation Remove to fresh air. If breathing has stopped, give artificial respiration. Get

medical attention immediately. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If

breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary

edema may occur. Get medical attention immediately if symptoms occur.

(III)

Page 3/13

Ingestion Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water.

Never give anything by mouth to an unconscious person. Call a physician or

poison control center immediately.

Self-protection of the first aider Ensure that medical personnel are aware of the material(s) involved, take

precautions to protect themselves and prevent spread of contamination. Avoid contact with skin, eyes or clothing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as

required. Wear personal protective clothing (see section 8).

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and Burning sensation. Coughing and/ or wheezing. Difficulty in breathing.

Effects

Indication of any immediate medical attention and special treatment needed

Notes to Physician Product is a corrosive material. Use of gastric lavage or emesis is

contraindicated. Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood pressure may occur with moist rales, frothy

sputum, and high pulse pressure.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

CAUTION: Use of water spray when fighting fire may be inefficient.

Specific Hazards Arising from the Chemical

The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of irritating gases and vapors.

Uniform Fire Code Corrosive: Other--Solid

Toxic: Solid

Oxidizer: Class 1--Solid

Hazardous Combustion Products

Carbon oxides.

Explosion Data

Sensitivity to Mechanical Impact No.

Sensitivity to Static Discharge No.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

(III)

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Attention! Corrosive material. Avoid contact with skin, eyes or clothing. Ensure adequate

ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Avoid generation of dust. Do not

breathe dust.

Other Information Refer to protective measures listed in Sections 7 and 8.

Environmental Precautions

Environmental Precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage

if safe to do so. Should not be released into the environment. Do not allow to enter into

soil/subsoil. Prevent product from entering drains.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning upPick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling In case of rupture: Handle in accordance with good industrial hygiene and safety practice.

Avoid contact with skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Use only with adequate ventilation and in closed systems. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash

before reuse. Do not breathe dust. Avoid generation of dust.

Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from

moisture. Store locked up. Keep out of the reach of children. Store away from other

materials.

Incompatible Products Acids. Bases. Oxidizing agent.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

| Chemical Name | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|---------------|-----------|----------|------------|

| Manganese dioxide | TWA: 0.02 mg/m ³ Mn | (vacated) Ceiling: 5 mg/m ³ | IDLH: 500 mg/m³ Mn |
|---------------------|---------------------------------------|---|--|
| 1313-13-9 | TWA: 0.1 mg/m ³ Mn | Ceiling: 5 mg/m ³ Mn | TWA: 1 mg/m³ Mn |
| | | | STEL: 3 mg/m³ Mn |
| Zinc | STEL: 10 mg/m ³ respirable | TWA: 5 mg/m ³ fume | IDLH: 500 mg/m ³ |
| 7440-66-6 | fraction | TWA: 15 mg/m ³ total dust | Ceiling: 15 mg/m ³ dust |
| | TWA: 2 mg/m ³ respirable | TWA: 5 mg/m ³ respirable | TWA: 5 mg/m ³ dust and fume |
| | fraction | fraction | STEL: 10 mg/m ³ fume |
| Potassium hydroxide | Ceiling: 2 mg/m ³ | (vacated) Ceiling: 2 mg/m ³ | Ceiling: 2 mg/m ³ |
| 1310-58-3 | | , , , | 0 0 |
| Graphite | TWA: 2 mg/m ³ respirable | TWA: 15 mg/m ³ total dust | IDLH: 1250 mg/m ³ |
| 7782-42-5 | fraction all forms except graphite | synthetic | TWA: 2.5 mg/m ³ respirable |
| | fibers | TWA: 5 mg/m ³ respirable | dust |
| | | fraction synthetic | |
| | | (vacated) TWA: 2.5 mg/m ³ | |
| | | respirable dust natural | |
| | | (vacated) TWA: 10 mg/m ³ total | |
| | | dust synthetic | |
| | | (vacated) TWA: 5 mg/m ³ | |
| | | respirable fraction synthetic | |
| | | TWA: 15 mppcf natural | |
| Barium sulfate | TWA: 5 mg/m ³ inhalable | TWA: 15 mg/m ³ total dust | TWA: 10 mg/m ³ total dust |
| 7727-43-7 | fraction, particulate matter | TWA: 5 mg/m ³ respirable | TWA: 5 mg/m ³ respirable dust |
| | containing no asbestos and <1% | fraction | , |
| | crystalline silica | (vacated) TWA: 10 mg/m ³ total | |
| | | dust | |
| | | (vacated) TWA: 5 mg/m ³ | |
| | | respirable fraction | |

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life or Health

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d

962 (11th Cir., 1992) See section 15 for national exposure control parameters

Appropriate engineering controls

Engineering Measures Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection Face protection shield.

Skin and Body Protection Wear protective gloves and protective clothing. Long sleeved clothing. Chemical resistant

apron. Impervious gloves.

Respiratory Protection No protective equipment is needed under normal use conditions. If exposure limits are

exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or

smoke when using this product. Take off contaminated clothing and wash before reuse. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. For environmental protection, remove and wash all

contaminated protective equipment before re-use. Do not breathe dust.

9. PHYSICAL AND CHEMICAL PROPERTIES

(II)

Page 6/13

Physical and Chemical Properties

Physical State Solid Appearance Solid

AppearanceSolidOdorOdorlessColorNo information availableOdor ThresholdNo information available

<u>Property</u> <u>Values</u> <u>Remarks Method</u>

No data available None known рΗ Melting / freezing point No data available None known None known Boiling point / boiling range No data available **Flash Point** No data available None known **Evaporation Rate** No data available None known Flammability (solid, gas) No data available None known

Flammability Limit in Air
Upper flammability limit
No data available

Lower flammability limit No data available Vapor pressure No data available None known Vapor density No data available None known **Specific Gravity** No data available None known **Water Solubility** Immiscible in water None known Solubility in other solvents No data available None known Partition coefficient: n-octanol/waterNo data available None known **Autoignition temperature** No data available None known **Decomposition temperature** No data available None known Kinematic viscosity No data available None known None known

Dynamic viscosityNo data availableExplosive propertiesNo data availableOxidizing PropertiesNo data available

Other Information

Softening Point

VOC Content (%)

Particle Size

No data available

No data available

No data available

Particle Size Distribution

(UL)

Page 7/13

Revision Date 12-Jun-2013 1101240 - Alkaline Battery

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Exposure to air or moisture over prolonged periods. Excessive heat.

Incompatible materials

Acids. Bases. Oxidizing agent.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information Product does not present an acute toxicity hazard based on known or supplied information.

In case of rupture:.

Inhalation Specific test data for the substance or mixture is not available. Corrosive by inhalation.

> (based on components). Inhalation of corrosive fumes/gases may cause coughing, choking, headache, dizziness, and weakness for several hours. Pulmonary edema may occur with tightness in the chest, shortness of breath, bluish skin, decreased blood pressure, and increased heart rate. Inhaled corrosive substances can lead to a toxic edema of the lungs. Pulmonary edema can be fatal. May cause irritation of respiratory tract. Harmful by

inhalation.

Eye Contact Specific test data for the substance or mixture is not available. Causes burns. (based on

components). Corrosive to the eyes and may cause severe damage including blindness.

Causes serious eye damage. May cause irreversible damage to eyes.

Skin Contact Specific test data for the substance or mixture is not available. Corrosive. (based on

components). Causes burns.

Ingestion Specific test data for the substance or mixture is not available. Causes burns. (based on

components). Ingestion causes burns of the upper digestive and respiratory tracts. May cause severe burning pain in the mouth and stomach with vomiting and diarrhea of dark blood. Blood pressure may decrease. Brownish or yellowish stains may be seen around the mouth. Swelling of the throat may cause shortness of breath and choking. May cause lung damage if swallowed. May be fatal if swallowed and enters airways. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea,

vomiting and diarrhea. May be harmful if swallowed.

Page 8/13

Component Information

| Chemical Name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|----------------------------------|---------------------|-------------|-----------------|
| Manganese dioxide 1313-13-9 | = 9000 mg/kg (Rat) | - | - |
| Potassium hydroxide 1310-58-3 | = 214 mg/kg (Rat) | - | - |
| Graphite 7782-42-5 | > 10000 mg/kg (Rat) | - | - |

Information on toxicological effects

Symptoms Erythema (skin redness). Burning. May cause blindness. Coughing and/ or wheezing.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Mutagenic Effects No information available.

Carcinogenicity Contains no ingredient listed as a carcinogen.

Reproductive Toxicity No information available.

STOT - single exposure No information available.

STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure. Based on

classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from

chronic or repeated exposure. (STOT RE).

Chronic Toxicity Chronic exposure to corrosive fumes/gases may cause erosion of the teeth followed by jaw

necrosis. Bronchial irritation with chronic cough and frequent attacks of pneumonia are common. Gastrointestinal disturbances may also be seen. Avoid repeated exposure. Prolonged exposure may cause chronic effects. May cause adverse effects on the bone

marrow and blood-forming system.

Target Organ Effects Respiratory system. Eyes. Skin. Gastrointestinal tract (GI). Blood. Central Nervous System

(CNS). Central Vascular System (CVS). Kidney. Cardiovascular system. Liver.

Aspiration Hazard No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)
785.00 mg/kg
ATEmix (inhalation-gas)
10,465.00 ppm (4 hr)
ATEmix (inhalation-dust/mist)
3.50 mg/l
ATEmix (inhalation-vapor)
26.00 ATEmix



Page 9/13

Revision Date 12-Jun-2013 1101240 - Alkaline Battery

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects.

| Chemical Name | Toxicity to Algae | Toxicity to Fish | Toxicity to Microorganisms | Daphnia Magna (Water Flea) |
|---------------------|---------------------------|----------------------------|-------------------------------|-------------------------------|
| Zinc | 96h EC50: 0.11 - 0.271 | 96h LC50: 2.16 - 3.05 mg/L | | 48h EC50: 0.139 - 0.908 |
| 7440-66-6 | mg/L (Pseudokirchneriella | (Pimephales promelas) 96h | | mg/L |
| | subcapitata) 72h EC50: | LC50: 0.211 - 0.269 mg/L | | |
| | 0.09 - 0.125 mg/L | (Pimephales promelas) 96h | | |
| | (Pseudokirchneriella | LC50: = 2.66 mg/L | | |
| | subcapitata) | (Pimephales promelas) 96h | | |
| | | LC50: = 30 mg/L (Cyprinus | | |
| | | carpio) 96h LC50: = 0.45 | | |
| | | mg/L (Cyprinus carpio) 96h | | |
| | | LC50: = 7.8 mg/L (Cyprinus | | |
| | | carpio) 96h LC50: = 3.5 | | |
| | | mg/L (Lepomis macrochirus) | | |
| | | 96h LC50: = 0.24 mg/L | | |
| | | (Oncorhynchus mykiss) 96h | | |
| | | LC50: = 0.59 mg/L | | |
| | | (Oncorhynchus mykiss) 96h | | |
| | | LC50: = 0.41 mg/L | | |
| | | (Oncorhynchus mykiss) | | |
| Potassium hydroxide | | 96h LC50: = 80 mg/L | | |
| 1310-58-3 | | (Gambusia affinis) | | |

Persistence and Degradability

No information available.

Bioaccumulation

| Chemical Name | Log Pow |
|----------------------------------|---------|
| Manganese dioxide 1313-13-9 | <0 |
| Potassium hydroxide 1310-58-3 | 0.83 |

Other adverse effects
No information available.

Page 10/13

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods

This material, as supplied, is not a hazardous waste according to Federal regulations (40)

CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local

regulations for additional requirements.

Contaminated Packaging Dispose of contents/containers in accordance with local regulations.

California Hazardous Waste Codes 181

This product contains one or more substances that are listed with the State of California as a hazardous waste.

| Chemical Name | California Hazardous Waste |
|---------------------|----------------------------|
| Zinc | Ignitable powder Toxic |
| 7440-66-6 | |
| Potassium hydroxide | Toxic |
| 1310-58-3 | Corrosive |
| Barium sulfate | Toxic soluble |
| 7727-43-7 | |

14. TRANSPORT INFORMATION

DOT NOT REGULATED

TDG Not regulated

MEX Not regulated

ICAO Not regulated

IATA Not regulated

IMDG/IMO Not regulated

RID Not regulated

ADR Not regulated

ADN Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA Complies

DSL All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory



DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

| Chemical Name | CAS No | Weight-% | SARA 313 - Threshold Values % |
|-------------------------------|-----------|----------|----------------------------------|
| Manganese dioxide - 1313-13-9 | 1313-13-9 | 15 - 40 | 1.0 |
| Zinc - 7440-66-6 | 7440-66-6 | 10 - 30 | 1.0 |
| Barium sulfate - 7727-43-7 | 7727-43-7 | 3 - 7 | 1.0 |

SARA 311/312 Hazard Categories

| Acute Health Hazard | No |
|-----------------------------------|----|
| Chronic Health Hazard | No |
| Fire Hazard | No |
| Sudden release of pressure hazard | No |
| Reactive Hazard | No |

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

| Chemical Name | CWA - Reportable Quantities | CWA - Toxic Pollutants | CWA - Priority Pollutants | CWA - Hazardous Substances |
|----------------------------------|--------------------------------|------------------------|---------------------------|-------------------------------|
| Zinc 7440-66-6 | | X | X | |
| Potassium hydroxide 1310-58-3 | 1000 lb | | | Х |

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

| Chemical Name | Hazardous Substances RQs | Extremely Hazardous Substances RQs | RQ |
|----------------------------------|--------------------------|------------------------------------|---|
| Zinc 7440-66-6 | 1000 lb | | RQ 454 kg final RQ RQ 1000 lb final RQ |
| Potassium hydroxide 1310-58-3 | 1000 lb | | RQ 1000 lb final RQ RQ 454 kg final RQ |

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

.

| Chemical Name | New Jersey | Massachusetts | Pennsylvania | Rhode Island | Illinois |
|----------------------------------|------------|---------------|--------------|--------------|----------|
| Manganese dioxide 1313-13-9 | | | Χ | Χ | Χ |
| Zinc 7440-66-6 | Х | X | Х | Х | |
| Potassium hydroxide 1310-58-3 | X | X | Χ | X | |
| Barium sulfate 7727-43-7 | X | X | Χ | X | |
| Graphite 7782-42-5 | X | X | Χ | | |



International Regulations

Mexico

National occupational exposure limits

| Component | Carcinogen Status | Exposure Limits |
|-----------------------|-------------------|------------------------------------|
| Manganese dioxide | | Mexico: TWA= 0.2 mg/m ³ |
| 1313-13-9 (15 - 40) | | - |
| Graphite | | Mexico: TWA= 2 mg/m ³ |
| 7782-42-5 (3 - 7) | | - |

Mexico - Occupational Exposure Limits - Carcinogens

Canada

WHMIS Hazard Class

Non-controlled

16. OTHER INFORMATION

NFPA Health Hazards 0 Flammability 0 Instability 0 Physical and Chemical Hazards -

HMIS Health Hazards 0 Flammability 0 Physical Hazard 0 Personal Protection

Χ

Prepared By Product Stewardship

23 British American Blvd. Latham, NY 12110 1-800-572-6501

Revision Date 12-Jun-2013

Revision Note No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet

U