



新利達電池實業有限公司

NEW LEADER BATTERY INDUSTRY LTD.

香港九龍觀塘開源道 62 號駱駝漆大廈第一期四樓 A 座
FLAT A, 4/F., B1K 1, CAMELPAINT BLDG., 62 HOI YUEN ROAD, KWUN TONG, KOWLOON HONG KONG
TEL:(852) 2790 6280 FAX:(852) 2763 4104 Website:www.newleader.com.hk E-mail: sales@newleader.com.hk



Material Safety Data Sheet for R6P and R03P Battery

Document Number: QA 23321-2004 Revision:00

Page 1 of 5

IDENTITY (As Used on Label and List)

Note : Blank spaces are not permitted if any item is not applicable or no information is available, the space must be marked to indicate that.

Section I

Manufacturer's Name

New Leader Battery Industry Ltd.,

Emergency Telephone Number 2790 6280

Address (Number, Street, City State, and ZIP Code)

Telephone Number for information

852-2790 6280

Date of prepared and revision Jan 28, 09

Signature of Prepare (optional)

Section II - Hazardous Ingredients / Identity Information

Hazardous Components:

Description: Approximate % of total weight

Lead : <0.2 Wt%

Mercury : <0.0005t%

Cadmium : <0.0015 Wt%

Section III - Physical / Chemical Characteristics

Boiling Point

N.A. Specific Gravity (H₂O=1)

N.A.

Vapor Pressure (mm Hg)

N.A. Melting Point

N.A.

Vapor Density (AIR=1)

N.A. Evaporation Rate (Butyl Acetate)

N.A.

Solubility in Water

N.A.

Appearance and Odor

Cylindrical Shape, odorless



新利達電池實業有限公司

NEW LEADER BATTERY INDUSTRY LTD.

香港九龍觀塘開源道 62 號駱駝漆大廈第一期四樓 A 座
FLAT A, 4/F., B1K 1, CAMELPAINT BLDG., 62 HOI YUEN ROAD, KWUN TONG, KOWLOON HONG KONG

TEL:(852) 2790 6280 FAX:(852) 2763 4104 Website:www.newleader.com.hk E-mail: sales@newleader.com.hk



Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used)

N.A.

Flammable Limits N.A.

LEL N.A.

UEL N.A.

Extinguishing Media

N.A.

Special Fire Fighting Procedures

N.A.

Unusual Fire and Explosion

Hazards

Do not dispose of battery in fire -
may explode.

Do not short-circuit battery - may
cause burns.

Section V – Reactivity Data

Stability Unstable

Conditions to Avoid

Stable X

Incompatibility (Materials to Avoid)

Hazardous Decomposition or Byproducts

Hazardous

Polymerization May Occur Conditions to Avoid

Will Not Occur

X

Section VI - Health Hazard Data

Route(s) of Entry

Inhalation N.A.

Skin N.A.

Ingestion N.A.

Health Hazard (Acute and Chronic) / Toxicological information

In case of electrolyte leakage, skin will be itchy when contaminated with electrolyte.

In contact with electrolyte can cause severe irritation and chemical burns.

Inhalation of electrolyte vapors may cause irritation of the upper respiratory tract and lungs.



新利達電池實業有限公司

NEW LEADER BATTERY INDUSTRY LTD.

香港九龍觀塘開源道 62 號駱駝漆大廈第一期四樓 A 座
FLAT A, 4/F., B1K 1, CAMELPAINT BLDG., 62 HOI YUEN ROAD, KWUN TONG, KOWLOON HONG KONG

TEL:(852) 2790 6280 FAX:(852) 2763 4104 Website:www.newleader.com.hk E-mail: sales@newleader.com.hk



Section VII – First Aid Measures

Page 3 of 5

First Aid Procedures

If electrolyte leakage occurs and makes contact with skin, wash with plenty of water immediately.

If electrolyte comes into contact with eyes, wash with copious amounts of water for fifteen (15) minutes, and contact a physician.

If electrolyte vapors are inhaled, provide fresh air and seek medical attention if respiratory irritation develops. Ventilate the contaminated area.

Section VIII - Fire and Explosion Hazard Data

Flash Point (Method Used) N.A.

Ignition Temp. N.A.

Flammable Limits N.A.

LEL N.A.

UEL N.A.

Extinguishing Media

Carbon Dioxide, Dry Chemical or Foam extinguishers

Special Fire Fighting Procedures N.A.

Unusual Fire and Explosion Hazards

Do not dispose of battery in fire - may explode.

Do not short-circuit battery - may cause burns.

Section IX – Accidental Release or Spillage

Steps to Be Taken in Case Material is Released or Spilled

Batteries that are leakage should be handled with rubber gloves.

Avoid direct contact with electrolyte.

Wear protective clothing and a positive pressure Self-Contained Breathing Apparatus (SCBA).

Section X – Handling and Storage

Safe handling and storage advice

Batteries should be handled and stored carefully to avoid short circuits.

Do not store in disorderly fashion, or allow metal objects to be mixed with stored batteries.

Never disassemble a battery.

Do not breathe cell vapors or touch internal material with bare hands.

Keep batteries between -30°C and 35°C for prolong storage.



新利達電池實業有限公司

NEW LEADER BATTERY INDUSTRY LTD.

香港九龍觀塘開源道 62 號駱駝漆大廈第一期四樓 A 座
FLAT A, 4/F., B1k 1, CAMELPAINT BLDG., 62 HOI YUEN ROAD, KWUN TONG, KOWLOON HONG KONG

TEL:(852) 2790 6280 FAX:(852) 2763 4104 Website:www.newleader.com.hk E-mail: sales@newleader.com.hk



Section XI – Exposure Controls / Person Protection

- Occupational Exposure Limits: LTEP N.A.
- STEP N.A.
- Respiratory Protection (Specify Type) N.A.
- Ventilation Local Exhausts N.A.
- Special N.A.
- Mechanical (General) N.A.
- Other N.A.
- Protective Gloves N.A.
- Eye Protection
N.A.
- Other Protective Clothing or Equipment
N.A.
- Work / Hygienic Practices
N.A.
- Section XII – Ecological Information
N.A.

Section XIII – Disposal Method

Dispose of batteries according to government regulations.

Section XIV – Transportation Information

NL batteries are considered to be “Dry cell” batteries and are unregulated for purposes of transportation by the U.S. Department of Transportation (DOT), International Civil Aviation Administration (ICAO), International Air Transport Association (IATA) and International Maritime Dangerous Goods Regulations (IMDG). The only DOT requirement for shipping these batteries is special provision 130 which states: “Batteries, dry are not subject to the requirements of this subchapter only when they are offered for transportation in a manner that prevents the dangerous evolution of heat (For example, by the effective insulation of exposed terminals). As of 1/1/97 IATA requires that batteries being transported by air must be protected from short-circuiting and protected from movement that could lead to short-circuiting.



新利達電池實業有限公司

NEW LEADER BATTERY INDUSTRY LTD.

香港九龍觀塘開源道 62 號駱駝漆大廈第一期四樓 A 座
FLAT A, 4/F., B1k 1, CAMELPAINT BLDG., 62 HOI YUEN ROAD, KWUN TONG, KOWLOON HONG KONG

TEL:(852) 2790 6280 FAX:(852) 2763 4104 Website:www.newleader.com.hk E-mail: sales@newleader.com.hk



Section XV – Regulatory Information

Page 5 of 5

Special requirement be according to the local regulatories.

Section XVI – Other Information

The data in this Material Safety Data Sheet relates only to the specific material designated herein.

Section XVII – Measures for fire extinction

In case of fire, it is permissible to use any class of extinguishing medium on these batteries or their packing material. Cool exterior of batteries if exposed to fire to prevent rupture.

Fire fighters should wear self-contained breathing apparatus.