# TECHNICAL DATA SHEET



# INTERIOR WATER-BASE PRIMER

NO. 2002



### PRODUCT INFORMATION

KILZ MAX Interior Water-Base Primer is a primer, sealer, stain and odor blocker developed with new technology that's formulated to perform like oil-and shellac-based products. It tackles tough stains including medium to heavy water damage, rust, smoke, nicotine, grease, tannin, ink, pencil, felt marker, pet stains and more. KILZ MAX Primer also seals pet and smoke odors. Topcoat with latex or oil-based paint.

### **RECOMMENDED USES:**

Use on properly prepared interior surfaces, such as:

• Concrete Block/CMU

PlasterNon-Ferrous MetalsSubfloor

## • Drywall/Gypsum Board

Brick

#### **PRODUCT SPECIFICATIONS:**

Tint Bases/Max Tint Load:

No. L2002 128 oz. / 2 oz. **Resin Type:** Acrylic Modified Epoxy

Weight per Gallon: 11.6 lbs.

% Solids by Volume: 38.6%

% Solids by Weight: 54.9%

VOC: <75 g/L Flash Point: N/A Viscosity: 90 - 100 KU

**Recommended Film Thickness:** 

Wet: 5.3 mils / Dry: 2.0 mils @ 300 Sq. Ft./Gal. Wet: 4.0 mils / Dry: 1.5 mils @ 400 Sq. Ft./Gal.

**Coverage:** 300 - 400 Sq. Ft./Gal. depending on the surface texture, porosity and application method. Does not include the loss of material from spraying.

#### **APPLICATION:**

**Brush:** Nylon / Polyester Blend

**Roller:** 3/8" - 1/2" nap

Airless Spray: Fluid pressure of 2,500 - 3,200 psi

**Tip:** .015" - .021" **Filter:** 60 mesh

**Thinning:** Not recommended. Product is formulated for use

at package consistency only.

**Dry Time:** @ 77°F, 50% RH

Longer dry time required in cooler temperatures and in

higher humidity.

To Touch: 30 minutes
To Recoat: 1 hour

## **SURFACE PREPARATION:**

The surface must be clean, free of dust, grease, wax, peeling paint, mold, mildew and wallpaper paste. If washing is necessary, use a non-soapy detergent or a TSP substitute. Rinse well and allow to dry.

**Peeling or Checked Paint:** Scrape off loose paint and sand to a smooth surface. Sanding or removal of paint containing lead is hazardous.

**Glossy Surfaces:** For maximum adhesion, scuff sand the surface thoroughly before priming.

**Masonry, Brick, Stucco and Plaster:** KILZ MAX Interior Water-Base Primer may be used on clean, dry, aged masonry surfaces. New masonry must be allowed to cure (dry) at least 30 days before applying KILZ MAX Interior Water-Base Primer.

**Fire Restoration:** It is critical to clean smoke damaged surfaces thoroughly before priming.

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC.** Contact the National Lead Information Center at 1-800-424-LEAD or visit www.epa.gov/lead.

#### **CLEAN UP:**

Clean all tools and equipment with clean water. For disposal of empty containers and unused product, contact your household refuse collection service.

COMPLIES WITH THE BELOW AS OF 9/1/2014			
SCAQMD	YES	AIM	YES
CARB	YES	MPI#	39, 137
ОТС	YES	GREENGUARD®	YES
LADCO	YES	CHPS	YES

<sup>†</sup>Please visit www.usgbc.org/LEED for additional details. GREENGUARD is a registered trademark of UL Company.

# **CAUTIONS/LIMITATIONS:**

- IMPORTANT! Do not open can without reading instructions.
- Do not use when air and surface temperatures are below 50°F or above 90°F.
- Shelf life under normal conditions is two years unopened.
- KILZ MAX Primer has a unique formula and should never be intermixed with other products.
- Do not use on floors or horizontal surfaces prone to foot traffic.

### **GENERAL INFORMATION:**



**Warning!** Causes eye and skin irritation. Harmful if swallowed. Wear protective clothing, gloves, eye, and face protection. Do not eat, drink, or smoke when using this product. Take off contaminated clothing and wash it before reuse. Wash hands thoroughly after handling. Collect spillage and avoid release to the environment. Dispose of unused contents, container and other contaminated wastes in accordance with local, state, federal and provincial regulations.

**First aid:** If in eyes: Rinse cautiously with water for several minutes and remove contacts if present and easy to do. Continue rinsing and get medical attention if eye irritation persists. If on skin: Wash with plenty of soap and water. If swallowed: Rinse mouth and get medical attention if you feel unwell.