## **SAFETY DATA SHEET**



Date of issue/Date of revision 20 April 2017 Version 5.01

Section 1. Identification			
Product name	: GLN6413N GLIDDEN PREMIUM INTERIOR SEMI-GLOSS PAINT+PRIMER - BASE 3		
Product code	: 00380468		
Other means of identification	: Not available.		
Product type	: Liquid.		
Relevant identified uses of	of the substance or mixture and uses advised against		
Product use	: Industrial applications.		
Use of the substance/ mixture	: Coating.		
Uses advised against	: Not applicable.		
Manufacturer	: PPG Industries, Inc. One PPG Place Pittsburgh, PA 15272		
Emergency telephone number	: (412) 434-4515 (U.S.) (514) 645-1320 (Canada) 01-800-00-21-400 (Mexico)		

Technical Phone Number : 1-800-441-9695 (8:00 am to 5:00 pm EST)

## Section 2. Hazards identification

: Not applicable.		
: Not applicable.		
: Not applicable.		
: No known significant effects or critical hazards.		
: No signal word.		
Percentage of the mixture consisting of ingredient(s) of unknown	own toxicity	r: 6.1%
: Not classified.		
Standard (29 CFR 1910.1200), this SDS contains valuable in	nformation c	ritical to the
ts	<ul> <li>Standard (29 CFR 1910.1200), this SDS contains valuable in safe handling and proper use of the product. This SDS shoul for employees and other users of this product.</li> <li>Not classified.</li> <li>Percentage of the mixture consisting of ingredient(s) of unkn</li> <li>No signal word.</li> <li>No known significant effects or critical hazards.</li> <li>Inot applicable.</li> <li>Not applicable.</li> </ul>	<ul> <li>Not classified.</li> <li>Percentage of the mixture consisting of ingredient(s) of unknown toxicity</li> <li>No signal word.</li> <li>No known significant effects or critical hazards.</li> <li>Not applicable.</li> <li>Not applicable.</li> </ul>

Date of issue 20 April 2017

Version 5.01

Product name GLN6413N GLIDDEN PREMIUM INTERIOR SEMI-GLOSS PAINT+PRIMER - BASE 3

## Section 2. Hazards identification

Disposal	: Not applicable.
Supplemental label elements	: Sanding and grinding dusts may be harmful if inhaled. Emits toxic fumes when heated.
Hazards not otherwise classified	: None known.

## Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Product name	: GLN6413N GLIDDEN PREMIUM INTERIOR SEMI-GLOSS PAINT+PRIMER - BASE 3

Ingredient name	%	CAS number
Kaolin	≥5.0 - ≤10	1332-58-7

SUB codes represent substances without registered CAS Numbers.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

#### Description of necessary first aid measures

Eye contact	: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	<ul> <li>Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.</li> </ul>
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.
Most important sympt	oms/effects, acute and delayed
Potential acute health	<u>effects</u>
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs	<u>symptoms</u>
Eye contact	: No specific data.
Inhalation	: No specific data.
	United States Page: 2/11

Product name GLN6413N GLIDDEN PREMIUM INTERIOR SEMI-GLOSS PAINT+PRIMER - BASE 3

## Section 4. First aid measures

Skin contact	: No specific data.
Ingestion	: No specific data.

# Indication of immediate medical attention and special treatment needed, if necessaryNotes to physician: Treat symptomatically. Contact poison treatment specialist immediately if large<br/>quantities have been ingested or inhaled.Specific treatments: No specific treatment.Protection of first-aiders: No action shall be taken involving any personal risk or without suitable training.

#### See toxicological information (Section 11)

#### Section 5. Fire-fighting measures **Extinguishing media** Suitable extinguishing : Use an extinguishing agent suitable for the surrounding fire. media Unsuitable extinguishing : None known. media Specific hazards arising : In a fire or if heated, a pressure increase will occur and the container may burst. This from the chemical material is toxic to aquatic life. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain. Hazardous thermal 5 Decomposition products may include the following materials: decomposition products carbon oxides Special protective actions : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable for fire-fighters training. : Fire-fighters should wear appropriate protective equipment and self-contained breathing **Special protective** equipment for fire-fighters apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

Personal precautions, protect	tiv	e equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Version 5.01

Product name GLN6413N GLIDDEN PREMIUM INTERIOR SEMI-GLOSS PAINT+PRIMER - BASE 3

## Section 6. Accidental release measures

Methods and materials for containment and cleaning up

Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
	•

Large spill : Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

Precautions for safe handling	
Protective measures	: Put on appropriate personal protective equipment (see Section 8).
Special precautions	: If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Do not store below the following temperature: 5°C (41°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## Section 8. Exposure controls/personal protection

#### **Control parameters**

**Occupational exposure limits** 

Ingredient name	Exposure limits
Kaolin	ACGIH TLV (United States, 3/2016).
	TWA: 2 mg/m <sup>3</sup> 8 hours. Form: Respirable
	fraction
	OSHA PEL (United States, 6/2016).
	TWA: 5 mg/m <sup>3</sup> 8 hours. Form: Respirable
	fraction
	TWA: 15 mg/m <sup>3</sup> 8 hours. Form: Total dust

Key to abbreviations

United States Page: 4/11

### Product name GLN6413N GLIDDEN PREMIUM INTERIOR SEMI-GLOSS PAINT+PRIMER - BASE 3

## Section 8. Exposure controls/personal protection

А	<ul> <li>Acceptable Maximum Peak</li> </ul>			<ul> <li>Potential skin absorption</li> </ul>
ACGIH	IH = American Conference of Governmental Industrial Hygienists.		SR	<ul> <li>Respiratory sensitization</li> </ul>
С	<ul> <li>Ceiling Limit</li> </ul>		SS	<ul> <li>Skin sensitization</li> </ul>
F	= Fume		STEL	<ul> <li>Short term Exposure limit values</li> </ul>
IPEL	= Internal Permissible Exp	osure Limit	TD	= Total dust
OSHA	= Occupational Safety and	Health Administration.	TLV	= Threshold Limit Value
R	= Respirable		TWA	= Time Weighted Average
Z	= OSHA 29 CFR 1910.120	0 Subpart Z - Toxic and Hazardous Substances		
Consult	local authorities for a	cceptable exposure limits.		
Recom proced	imended monitoring lures	the ventilation or other control measure	ay be reas s and/o ld be ma ents for	quired to determine the effectiveness of r the necessity to use respiratory ade to appropriate monitoring standards.
controls		: Good general ventilation should be suff contaminants.	icient to	control worker exposure to airborne
<ul> <li>Environmental exposure controls</li> <li>Emissions from ventilation or work process equipment should be checked they comply with the requirements of environmental protection legislation. cases, fume scrubbers, filters or engineering modifications to the process will be necessary to reduce emissions to acceptable levels.</li> </ul>		ental protection legislation. In some nodifications to the process equipment		

#### Individual protection measures

Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection Skin protection	: Safety glasses with side shields.
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Version 5.01

## Product name GLN6413N GLIDDEN PREMIUM INTERIOR SEMI-GLOSS PAINT+PRIMER - BASE 3

## Section 9. Physical and chemical properties

#### **Appearance**

Physical state	1	Liquid.
Color	1	Various
Odor	1	Characteristic.
Odor threshold	1	Not available.
рН	1	8.6
Melting point	1	Not available.
Boiling point	1	100°C (212°F)
Flash point	1	Closed cup: Not applicable. [Product does not sustain combustion.]
Auto-ignition temperature	1	Not available.
Decomposition temperature	1	Not available.
Flammability (solid, gas)	1	Not available.
Lower and upper explosive (flammable) limits	:	Not available.
Evaporation rate	1	0.05 (butyl acetate = 1)
Vapor pressure	1	3.3 kPa (25 mm Hg) [room temperature]
Vapor density	1	Not available.
Relative density	1	1.07
Density(lbs / gal)	:	8.93
Solubility	1	Soluble in the following materials: cold water.
Partition coefficient: n-	:	Not available.
octanol/water		
Viscosity		Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)
Volatility		76% (v/v), 71.399% (w/w)
% Solid. (w/w)	4	28.601

## Section 10. Stability and reactivity

	United States Page: 6/11
Hazardous decomposition products	: Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Chemical stability	: The product is stable.
Reactivity	: No specific test data related to reactivity available for this product or its ingredients.

Product name GLN6413N GLIDDEN PREMIUM INTERIOR SEMI-GLOSS PAINT+PRIMER - BASE 3

## Section 11. Toxicological information

#### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Kaolin	LD50 Oral	Rat	>5000 mg/kg	-
Conclusion/Summary	: There are no data available on	the mixture itself.	•	ŀ
rritation/Corrosion				
Conclusion/Summary				
Skin	: There are no data available on	the mixture itself.		
Eyes	: There are no data available on	the mixture itself.		
Respiratory	: There are no data available on	the mixture itself.		
Sensitization				
Conclusion/Summary				
Skin	: There are no data available on	the mixture itself.		
Respiratory	: There are no data available on	the mixture itself.		
Mutagenicity				
Conclusion/Summary	: There are no data available on	the mixture itself.		
Carcinogenicity				
Conclusion/Summary	: There are no data available on	the mixture itself.		
Reproductive toxicity				
Conclusion/Summary	: There are no data available on	the mixture itself		
Feratogenicity				
Conclusion/Summary	: There are no data available on	the mixture iteelf		
Specific target organ toxicit				
Not available.	<u>y (single exposure)</u>			
Specific target organ toxicit	<u>y (repeated exposure)</u>			
Not available.				
arget organs	: Contains material which causes Contains material which may ca			
	respiratory tract, stomach.		e .ee	
Aspiration hazard				
Not available.				
formation on the likely rout	es of exposure			
Potential acute health effect	<u>S</u>			
Eye contact	No known significant effects or	critical hazards.		
Inhalation	: No known significant effects or			
Skin contact	: No known significant effects or			
Ingestion	: No known significant effects or			
<u>Dver-exposure signs/sympt</u>	-			
Eve contact	: No specific data.			
Eye contact				

Version 5.01

#### Product name GLN6413N GLIDDEN PREMIUM INTERIOR SEMI-GLOSS PAINT+PRIMER - BASE 3

## Section 11. Toxicological information

		- J	
Inhalation	:	No specific data.	
Skin contact	1	No specific data.	
Ingestion	1	No specific data.	
Delayed and immediate effect	<u>cts</u> :	and also chronic effects from short an	<u>d long term exposure</u>
Conclusion/Summary	:	cause irritation and reversible damage. vomiting. This takes into account, when	ure itself. If splashed in the eyes, the liquid may Ingestion may cause nausea, diarrhea and e known, delayed and immediate effects and a short-term and long-term exposure by oral, e and eye contact.
<u>Short term exposure</u>			
Potential immediate effects	1	There are no data available on the mixtu	ıre itself.
Potential delayed effects	1	There are no data available on the mixtu	ure itself.
<u>Long term exposure</u>			
Potential immediate effects	:	There are no data available on the mixtu	ure itself.
Potential delayed effects	1	There are no data available on the mixtu	ure itself.
Potential chronic health effe	<u>ects</u>		
General	1	No known significant effects or critical h	azards.
Carcinogenicity	:	No known significant effects or critical h	azards.
Mutagenicity	1	No known significant effects or critical h	azards.
Teratogenicity	1	No known significant effects or critical h	azards.
<b>Developmental effects</b>	:	No known significant effects or critical h	azards.
Fertility effects		No known significant effects or critical h	azards.
Numerical measures of toxic	<u>city</u>		
Acute toxicity estimates			
Route			ATE value
Oral			166933.3 mg/kg

## Section 12. Ecological information

#### **Toxicity**

Not available.

#### Persistence and degradability

Not available.

#### **Bioaccumulative potential**

Not available.

#### **Mobility in soil**

Version 5.01

Product name GLN6413N GLIDDEN PREMIUM INTERIOR SEMI-GLOSS PAINT+PRIMER - BASE 3

## Section 12. Ecological information

Soil/water partition coefficient (Koc)

: Not available.

## Section 13. Disposal considerations

**Disposal methods** 

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

## 14. Transport information

	DOT	IMDG	ΙΑΤΑ	
UN number	Not regulated.	Not regulated.	Not regulated.	
UN proper shipping name	-	-	-	
Transport hazard class (es)	-	-	-	
Packing group	-	-	-	
Environmental hazards Marine pollutant substances	No. Not applicable.	No. Not applicable.	No. Not applicable.	

#### Additional information

DOT : None identified. IMDG : None identified. : None identified. ΙΑΤΑ

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Version 5.01

Product name GLN6413N GLIDDEN PREMIUM INTERIOR SEMI-GLOSS PAINT+PRIMER - BASE 3

## Section 15. Regulatory information

#### **United States**

**United States inventory (TSCA 8b)** : All components are listed or exempted.

#### SARA 302/304

**SARA 304 RQ** : Not applicable.

**Composition/information on ingredients** 

No products were found.

#### SARA 311/312

Classification : Not applicable.

**Composition/information on ingredients** 

No products were found.

Additional environmental information is contained on the Environmental Data Sheet for this product, which can be obtained from your PPG representative.

## Section 16. Other information

#### Hazardous Material Information System (U.S.A.)

Flammability : 0 Physical hazards : 0 Health : 3 (\*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Asso	ociation (U.S.A.)
Health : 3 Flamma	bility : 0 Instability : 0
Date of previous issue	: 3/14/2017
Organization that prepared the MSDS	: EHS
Key to abbreviations	<ul> <li>ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations</li> </ul>

Indicates information that has changed from previously issued version.

Disclaimer

Date of issue 20 April 2017 Ve

Version 5.01

#### Product name GLN6413N GLIDDEN PREMIUM INTERIOR SEMI-GLOSS PAINT+PRIMER - BASE 3

## Section 16. Other information

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.