

Changzhou Yufeng Electrical Co., Ltd

Material Safety Data Sheet

Model No.: CR2032

- 1 -

Identity (As Used on Label and List) Lithium / Manganese Dioxide Cell	Part Number CR2032
--	-----------------------

Section I: Information of Manufacturer

Manufacturer's Name Changzhou Yufeng Electrical Co., Ltd	Emergency Telephone Number 0519-83885169
Address (Number, Street, City, State, and ZIP Code) Industrial Zone Xilin, Zhonglou District.Changzhou ,Jiangsu 213024	Telephone Number for information 0519-83885169
	Date of prepared and revision 2010-06
	Signature of Preparer (optional)

Section II: Hazardous Ingredients/Identity Information

Hazardous Description:	Components:	Approximate weight of content in one piece of the cell (mg)	Approximate % of total weight
	lithium	66	2.2%
	Manganese dioxide	840	28%
	Electrolyte	264	8.8%
	Lead		0 ppm
	Cadmium		0 ppm
	Mercury		0 ppm
	Cr+6		4 ppm
	PBB		0 ppm
	PBDE		0 ppm
	Others	1830	61%

Section III: Physical/Chemical Characteristics

Form NA	Specific Gravity (H2O =1) NA
Boiling Point NA	Melting Point NA
Vapor Pressure (mm Hg) NA	Evaporation Rate (Butyl Acetate=1) NA
Vapor Density (AIR=1) NA	Ph NA
Solubility in Water NA	Appearance and Odor NA

Changzhou Yufeng Electrical Co., Ltd

Material Safety Data Sheet

Model No.: CR2032

- 2 -

Section IV: Hazard classification

NA

Section V: Reactivity Data

Stability Yes= (X)	Unstable ()	Conditions to Avoid
	Stable (X)	

Incompatibility (Materials to Avoid)

Hazardous Decomposition or By products

NA

Hazardous Reactions Yes = (X)	May Occur ()	Conditions to Avoid
	Will Not Occur (X)	

Section VI: Health Hazard Data

Route(s) of Entry Yes=(X)	Inhalation? (NA)	Skin? (NA)	Ingestion? (NA)
---------------------------	---------------------	---------------	--------------------

Health Hazard (Acute and Chronic) / Toxicological in formation

In case of electrolyte leakage, skin will be itchy when contaminated with electrolyte.

Section VII – First Aid Measures

Firs aid Procedures

If electrolyte leakage occurs and makes contact with skin, wash immediately.

If electrolyte comes into contact with eyes, wash with copious amounts of water for fifteen minutes, and contact a physician.

Section VIII: Fire and Explosion Hazard Data

Flash Point (Method Used) NA	Ignition temp NA	Flammable Limits NA	LEL NA	UEL NA
----------------------------------	---------------------	------------------------	-----------	-----------

Extinguishing Media

NA

Special Fire Fighting Procedures

NA

Changzhou Yufeng Electrical Co., Ltd

Material Safety Data Sheet

Model No.: CR2032

- 3 -

Unusual Fire and Explosion Hazards

Do not dispose of battery in fire – may explode.

Do not short – circuit battery – may cause burns.

Section IX: Accidental Release or Spillage

Steps to Be Taken in Case Material is Released or Spilled

Batteries that are leaking should be handled with rubber gloves.

Avoid direct contact with electrolyte.

Section X: Handling and Storage

Safe handling and storage advice

The battery is extremely sensitive to adverse effects of humidity. Be sure to store them in a place that is dry and subject to little temperature change. Do not place near the boiler or radiator, nor expose to direct sun light. Do not dispose of the battery in fire. Do not charge the battery. Do not short- circuit the battery. Do not put in backward position. Do not store in disorderly fashion, or allow metal objects to be mixed with stored batteries. Do not disassemble the battery, handling in such manner can cause the battery to explode, leak and injury.

Section XI: Exposure Controls / Personal Protection

Occupational Exposure Limits :	LTEP	STEP
NA		NA

Respiratory Protection (Specify Type)
NA

Ventilation	Local Exhausts	Special
	NA	NA
	Mechanical (general)	Other
	NA	NA

Protective Gloves	Eye Protection
NA	NA

Other Protective Clothing or Equipment
NA

Work / Hygienic Practices
NA

Section XII: Ecological Information

Changzhou Yufeng Electrical Co., Ltd

Material Safety Data Sheet

Model No.: CR2032

- 4 -

NA

Section XIII: Disposal Method

Discard the method of handling: After the used battery is put for 2 days In common water (no pure water) , can press general garbage disposal.

Section XIV: Transportation Information

Lithium battery international transportation rules. Based on a United Nations recommendation, the regulation for lithium/lithium ion cells and batteries has been revised in the international Air Transport Association (IATA) dangerous goods regulations (DGR Rev.50).Each cell or battery pack meets the requirements of each test in the UN Manual of Tests and Criteria III, sub section 38.3(Guangzhou Vkan Certification and Testing Institute No.UN08-0440). The Cells / Batteries are "Not Restricted" Cargo

1. Must comply with Part 1of PI968-PI970 accordingly.
 2. For cells, the lithium content should not be more than 1 g; while for batteries, the aggregate lithium content should not be more than 2 g.
 3. For those Lithium metal cells / batteries contained in equipment, the equipment must be equipped with an effective means of preventing accidental activation.
-

Section XV: Regulatory Information

IATA Dangerous Goods Regulations.

ICAO Technical Instructions for the safe transport of dangerous goods by air.

Section XVI: Other Information

This MSDS is described on the basis of present materials, information and data, so, please notice that it will be revised by new information. Also this sheet is supplied to entrepreneurs as reference information in order to handle batteries safely. Please notice that entrepreneur have to deal with batteries as they think fit.

- References
- (1) UN Recommendations on the Transportation of Dangerous Goods Model Regulations (ST/SG/AC.10/1/rEV.12)
 - (2) Federal Resister / Vol.65, No. 174 / Thursday, September 7, 2000 / Notices
 - (3) IATA Dangerous Goods Regulations 50th Edition (2009)
-

Section XVII: Measures for fire extinction

Suitable fire extinguishing agent: CO₂, fire extinguisher, ABC dry powder extinguisher, sand, etc. Can't quench, a small amount of can cover with the sand first, burn and need to use the fire

Changzhou Yufeng Electrical Co., Ltd

Material Safety Data Sheet

Model No.: CR2032

- 5 -

extinguisher in a large amount. Much water can put out a fire was aroused a few battery. The fire fighter's special shelter is equipped: Wearing the air respirator, protects the helmet, glasses, etc.
