# SAFETY DATA SHEET



Lysol® Brand III Kills 99.9% of Viruses & Bacteria\*\* Disinfectant Spray

# 1. Product and company identification

: Lysol® Brand III Kills 99.9% of Viruses & Bacteria\*\* Disinfectant Spray **Product name** 

: Reckitt Benckiser LLC. **Distributed by** 

Morris Corporate Center IV

399 Interpace Parkway (P.O. Box 225) Parsippany, New Jersey 07054-0225

+1 973 404 2600

: 1-800-338-6167

**Emergency telephone** 

number (Medical)

**Emergency telephone** 

number (Transport)

: 1-800-424-9300 (U.S. & Canada) CHEMTREC Outside U.S. and Canada (North America), call Chemtrec:703-527-3887

Website: : http://www.rbnainfo.com

: Lysol® Brand III Kills 99.9% of Viruses & Bacteria\*\* Disinfectant Spray **Synonym** 

Cherry Blossom & Pomegranate Scent

Citrus Meadows Scent/Hawaii Sunset Essence Scent

Crisp Linen Scent/For Baby's room

Crisp Mountain Air Scent/Cool Adirondack Air Scent

•Early Morning Breeze Scent

•For Baby's Room Jasmine & Rain Scent

 Lemon Breeze Spring Waterfall Summer Breeze

Vanilla & Blossoms Scent

 Crisp Berry Scent Original Scent Garden Mist Scent

**Product use** : Disinfectant.

This SDS is designed for workplace employees, emergency personnel and for other conditions and situations where there is greater potential for large-scale or prolonged exposure, in accordance with the requirements of **USDOL** Occupational Safety and Health Administration.

This SDS is not applicable for consumer use of our products. For consumer use, all precautionary and first aid language is provided on the product label in accordance with the applicable government regulations, and shown in Section 15 of this SDS.

SDS# : D0224478 v10.0

Formulation #: : 1338-022 (0175933 v1.0) Original

1338-022 (8083521 v1.0) Original 1338-019 (0175919 v1.0) Country 1338-019 (8080039 v1.0) Campestre 1338-016 (0175935 v1.0) Summer Breeze

1338-018 (0175934 v1.0) Green Apple / Green Apple Breeze

1338-017 (0175927 v1.0) Kitchen (Citrus) 1338-021 (0175938 v1.0) Crisp Berry 1338-020 (0175932 v1.0) Garden Mist

SDS# : D0224478 v10.0 **Date of issue** : 05/01/2017 1/14 Code # : D0224478 US GHS

# 1. Product and company identification

1338-020 (8089468 v1.0) Bebe

1338-015 (0175918 v1.0) Spring Waterfall 1338-015 (0258756 v1.0) Blr Swf Ext Prd 1178-172 (0175917 v1.0) Crisp Linen 1178-172 (8089462 v1.0) Frescura 1178-172 (0242193 v1.0) Blr C/L Ext Prd 1338-026 (0175929 v1.0) Early Morning Breeze 1314-032 (0175926 v1.0) Citrus Meadows 1544-074 (0175943 v2.0) Vanilla & Blossoms 1314-038 (0175920 v1.0) Jasmine & Rain / Lavender e0002-161 (8159483 v1.0) Pomegranate Crush

1784-045A (0346500 v1.0) Crisp Mountain Air 1325-133 (0222651 v1.0) Amphyl

1338-023 (0175940 v1.0) Fresh / Oxygen

**EPA ID No.** : 777-99

**UPC Code / Sizes**: Sizes: 6 oz., 12 oz., 12.5 oz. and 19 oz. (Tin plate steel cans).

## 2. Hazards identification

Classification of the substance or mixture

: FLAMMABLE AEROSOLS - Category 2

GASES UNDER PRESSURE - Compressed gas

Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 2.4%

### **GHS label elements**

Hazard pictograms





Signal word : Warning

**Hazard statements**: Flammable aerosol.

Contains gas under pressure; may explode if heated.

**Precautionary statements** 

General : Keep out of reach of children. If medical advice is needed, have product container or

label at hand.

**Prevention**: Wear eye or face protection. Keep away from heat, sparks, open flames and hot

surfaces. - No smoking. Pressurized container: may burst if heated. Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source. Wash

hands thoroughly after handling.

Response : Not applicable.

Storage : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in

a well-ventilated place.

Disposal : Not applicable.

Supplemental label

elements

: None known.

**Hazards not otherwise** 

classified

: None known.

Code # : D0224478 US GHS SDS # : D0224478 v10.0 Date of issue : 05/01/2017 2/14

**Eye contact** 

Inhalation

# 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	%	CAS number
Ethyl alcohol	30 - 60	64-17-5
butane	1-5	106-97-8
propane	<2.5	74-98-6

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

## 4. First aid measures

#### **Description of necessary first aid measures**

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10

minutes. Get medical attention if irritation occurs.

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar,

tie, belt or waistband.

Skin contact : Flush contaminated skin with plenty of water. Remove contaminated clothing and

shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean

shoes thoroughly before reuse.

Ingestion : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and

keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately.

Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

**Eye contact** : May cause eye irritation upon direct contact with eyes.

Inhalation : No known significant effects or critical hazards. Skin contact : No known significant effects or critical hazards. Ingestion : No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

**Eye contact** : Adverse symptoms may include the following:

> irritation redness

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

**Skin contact** : No specific data. : No specific data. Ingestion

: D0224478 US GHS SDS# 3/14 Code # : D0224478 v10.0 **Date of issue** : 05/01/2017

## 4. First aid measures

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

**Specific treatments** 

: No specific treatment.

**Protection of first-aiders** 

: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

# 5. Fire-fighting measures

## **Extinguishing media**

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media

: None known.

Specific hazards arising from the chemical

: Flammable aerosol. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed. Runoff to sewer may create fire or explosion hazard.

Hazardous thermal decomposition products

 Decomposition products may include the following materials: carbon dioxide carbon monoxide

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders:

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** 

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Code # : D0224478 US GHS SDS # : D0224478 v10.0 Date of issue : 05/01/2017 4/14

## 6. Accidental release measures

#### Methods and materials for containment and cleaning up

#### **Small spill**

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

#### Large spill

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible. absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# 7. Handling and storage

#### Precautions for safe handling

#### **Protective measures**

: Put on appropriate personal protective equipment (see Section 8). Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not ingest. Avoid contact with eves, skin and clothing. Avoid breathing gas. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.

# including any incompatibilities

Conditions for safe storage, : Do not store above the following temperature: 50°C (122°F). Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Protect from sunlight. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination.

# 8. Exposure controls/personal protection

#### **Control**

#### Occupational exposure limits

Ingredient name	Exposure limits
Ethyl alcohol	ACGIH TLV (United States, 6/2013).  STEL: 1000 ppm 15 minutes.  OSHA PEL 1989 (United States, 3/1989).  TWA: 1000 ppm 8 hours.  TWA: 1900 mg/m³ 8 hours.  NIOSH REL (United States, 10/2013).  TWA: 1000 ppm 10 hours.  TWA: 1900 mg/m³ 10 hours.  OSHA PEL (United States, 2/2013).  TWA: 1000 ppm 8 hours.
butane	TWA: 1900 mg/m³ 8 hours.  OSHA PEL 1989 (United States, 3/1989).  TWA: 800 ppm 8 hours.  TWA: 1900 mg/m³ 8 hours.  NIOSH REL (United States, 10/2013).
ode # + D0224478 US GHS - SDS #	• D0224478 v10.0 Date of issue • 05/01/2017 5/14

Code # : D0224478 US GHS : D0224478 v10.0 **Date of issue** : 05/01/2017 5/14

propane

# 8. Exposure controls/personal protection

TWA: 800 ppm 10 hours. TWA: 1900 mg/m³ 10 hours.

ACGIH TLV (United States, 6/2013).

STEL: 1000 ppm 15 minutes.

OSHA PEL 1989 (United States, 3/1989).

TWA: 1000 ppm 8 hours. TWA: 1800 mg/m³ 8 hours.

NIOSH REL (United States, 10/2013).

TWA: 1000 ppm 10 hours. TWA: 1800 mg/m³ 10 hours. OSHA PEL (United States, 2/2013).

TWA: 1000 ppm 8 hours. TWA: 1800 mg/m<sup>3</sup> 8 hours.

# Appropriate engineering controls

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

# **Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with sideshields.

# Skin protection Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

## **Body protection**

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear antistatic protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

#### Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

#### **Respiratory protection**

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Code # : D0224478 US GHS SDS # : D0224478 v10.0 Date of issue : 05/01/2017 6/14

# 9. Physical and chemical properties

**Appearance** 

Physical state : Liquid. [Aerosol.]

Color : Clear.

Odor : Characteristic.
Odor threshold : Not available.

**PH** : 10.5 to 11.8 [Conc. (% w/w): 100%]

Melting point: Not available.Boiling point: Not available.

Flash point : Closed cup: 25.6°C (78.1°F)

Evaporation rate : Not available.
Flammability (solid, gas) : Not available.
Lower and upper explosive : Not available.

(flammable) limits

Vapor pressure : Not available.
Vapor density : Not available.

**Relative density** : 0.8667 to 0.8967 g/cm³ [20 to 25°C]

**Solubility** : Easily soluble in the following materials: cold water and hot water.

Partition coefficient: n-

octanol/water

: Not available.

Auto-ignition temperature : Not available.

Decomposition temperature : Not available.

Viscosity : Not available.

Flow time (ISO 2431) : Not available.

Aerosol product

products

Type of aerosol : Spray
Heat of combustion : 17.99 kJ/g
Ignition distance : <45.72 cm

## 10. Stability and reactivity

**Reactivity**: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability**: The product is stable.

**Possibility of hazardous**: Under normal conditions of storage and use, hazardous reactions will not occur. reactions

**Conditions to avoid** : Avoid all possible sources of ignition (spark or flame).

Incompatible materials : No specific data.

Hazardous decomposition : Under normal conditions of storage and use, hazardous decomposition products should

not be produced.

Code # : D0224478 US GHS SDS # : D0224478 v10.0 Date of issue : 05/01/2017 7/14

# 11. Toxicological information

### Information on toxicological effects

## **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
Ethyl alcohol	LC50 Inhalation Vapor LD50 Oral	Rat Rat	124700 mg/m³ 7 g/kg	4 hours
Lysol® Brand III Kills 99.9% of Viruses & Bacteria** Disinfectant Spray	LC50 Inhalation Vapor	Rat	>2.12 mg/l	4 hours Maximum attainable concentration

**Conclusion/Summary** 

: Not classified Harmful. \* Information is based on toxicity test result of the concentrate of a similar product.

#### **Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
Ethyl alcohol	Eyes - Moderate irritant	Rabbit	-	0.066666667 minutes 100 milligrams	-
	Eyes - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	100 microliters	-
	Eyes - Severe irritant	Rabbit	-	500 milligrams	-
	Skin - Mild irritant	Rabbit	-	400 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-
Lysol® Brand III Kills 99.9% of Viruses & Bacteria** Disinfectant Spray	Eyes - Cornea opacity	Rabbit	<1	72 hours	4 days
	Skin - Primary dermal irritation index (PDII)	Rabbit	0.3	4 hours	72 hours

#### **Conclusion/Summary**

Skin

: Slightly irritating to the skin. \*Information is based on toxicity test result of the concentrate of a similar product.

**Eyes** 

: Moderately irritating to eyes. \*Information is based on toxicity test result of the concentrate of a similar product.

Respiratory

: Based on available data, the classification criteria are not met.

#### **Sensitization**

Not available.

### **Mutagenicity**

Not available.

## Carcinogenicity

Not available.

## **Classification**

Product/ingredient name	OSHA	IARC	NTP
Ethyl alcohol	-	1	-

Code # : D0224478\_US GHS SDS # : D0224478 v10.0 Date of issue : 05/01/2017 8/14

# 11. Toxicological information

#### **Reproductive toxicity**

Not available.

### **Teratogenicity**

Not available.

#### Specific target organ toxicity (single exposure)

Not available.

#### Specific target organ toxicity (repeated exposure)

Not available.

#### **Aspiration hazard**

Not available.

Information on the likely

routes of exposure

: Not available.

#### Potential acute health effects

**Eye contact**: May cause eye irritation upon direct contact with eyes.

Inhalation
 Skin contact
 No known significant effects or critical hazards.
 Ingestion
 No known significant effects or critical hazards.
 No known significant effects or critical hazards.

#### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following:

irritation redness

**Inhalation** : Adverse symptoms may include the following:

respiratory tract irritation

coughing

Skin contact : No specific data.

Ingestion : No specific data.

#### Delayed and immediate effects and also chronic effects from short and long term exposure

**Short term exposure** 

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Teratogenicity : No known significant effects or critical hazards.

Code # : D0224478 US GHS SDS # : D0224478 v10.0 Date of issue : 05/01/2017 9/14

# 11. Toxicological information

**Developmental effects** 

: No known significant effects or critical hazards.

**Fertility effects** 

: No known significant effects or critical hazards.

## **Numerical measures of toxicity**

**Acute toxicity estimates** 

Not available.

# 12. Ecological information

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
Ethyl alcohol	Acute EC50 17.921 mg/l Marine water Acute EC50 2000 μg/l Fresh water Acute LC50 25500 μg/l Marine water Acute LC50 42000 μg/l Fresh water Chronic NOEC 4.995 mg/l Marine water Chronic NOEC 0.375 ul/L Fresh water	Algae - Ulva pertusa Daphnia - Daphnia magna Crustaceans - Artemia franciscana - Larvae Fish - Oncorhynchus mykiss Algae - Ulva pertusa Fish - Gambusia holbrooki - Larvae	96 hours 48 hours 48 hours 4 days 96 hours 12 weeks

#### Persistence and degradability

Not available.

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
Ethyl alcohol	-0.35	-	low
butane	2.89	-	low
propane	1.09	-	low

#### **Mobility in soil**

Soil/water partition coefficient (Koc)

: Not available.

#### Other adverse effects

: No known significant effects or critical hazards.

# 13. Disposal considerations

#### **Disposal methods**

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

Code # : D0224478 US GHS SDS # : D0224478 v10.0 Date of issue : 05/01/2017 10/14

# 14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
DOT Classification	UN1950	Aerosols, flammable	2.1	-	$\Diamond$	Limited quantity
TDG Classification	UN1950	Aerosols, flammable	2.1	-		Limited quantity
Mexico Classification	UN1950	Aerosols, flammable	2.1	-		Limited quantity
IMDG Class	UN1950	Aerosols, flammable	2.1	-		Limited quantity
IATA-DGR Class	UN1950	Aerosols, flammable	2.1	-	2	See DG List

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the

PG\*: Packing group

# 15. Regulatory information

U.S. Federal regulations

: TSCA 8(a) PAIR: 2-methylpropan-2-ol

TSCA 8(a) CDR Exempt/Partial exemption: Not determined

United States inventory (TSCA 8b): Not determined.

Clean Water Act (CWA) 311: ammonia

Clean Air Act (CAA) 112 regulated flammable substances: butane; propane

Clean Air Act Section 112

(b) Hazardous Air **Pollutants (HAPs)**  : Not listed

Clean Air Act Section 602 **Class I Substances** 

: Not listed

Clean Air Act Section 602

: Not listed

**Class II Substances** 

**DEA List I Chemicals** (Precursor Chemicals) : Not listed

**DEA List II Chemicals** (Essential Chemicals) : Not listed

**SARA 302/304** 

Code # **Date of issue** : 05/01/2017 11/14 : D0224478\_US GHS SDS# : D0224478 v10.0

# 15. Regulatory information

#### **Composition/information on ingredients**

No products were found.

SARA 304 RQ : Not applicable.

**SARA 311/312** 

Classification : Fire hazard

Sudden release of pressure

#### **Composition/information on ingredients**

Name	%	hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
Ethyl alcohol butane propane	5 - 10	Yes. Yes. Yes.	No. Yes. Yes.	No. No. No.	Yes. No. No.	No. No. No.

State regulations

Massachusetts : The following components are listed: ETHYL ALCOHOL; BUTANE; PROPANE

New York : None of the components are listed.

New Jersey : The following components are listed: ETHYL ALCOHOL; ALCOHOL; BUTANE;

**PROPANE** 

Pennsylvania: The following components are listed: DENATURED ALCOHOL; BUTANE; PROPANE

<u>Canada</u>

WHMIS (Canada) : Class B-2: Flammable liquid

Class B-5: Flammable aerosol.

**Canadian lists** 

**Canadian NPRI** : The following components are listed: Ethanol; Butane (all isomers); Propane

**CEPA Toxic substances**: None of the components are listed.

Canada inventory : Not determined.

Label elements

Signal word: : CAUTION

**Hazard statements** : Causes moderate eye irritation

**Precautionary measures**: Do not get in eyes, on skin, or on clothing. Wash with soap and water.

Keep out of the reach of children.

CONTENTS UNDER PRESSURE. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120  $^{\circ}$ F. Keep away from heat, sparks,

open flames and hot surfaces. - No smoking.

Hazard statements :




Flammable

Code # : D0224478 US GHS SDS # : D0224478 v10.0 Date of issue : 05/01/2017 12/14

## 16. Other information

Hazardous Material Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910. 1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)



#### NFPA (30B) aerosol Flammability Level 1

Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Key to abbreviations

: ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

Date of issue : 05/01/2017

Date of previous issue : 26/06/2015.

Version : 1

Prepared by : Reckitt Benckiser LLC.

Product Safety Department

1 Philips Parkway

Montvale, New Jersey 07646-1810 USA.

FAX: 201-476-7770

Code # : D0224478 US GHS SDS # : D0224478 v10.0 Date of issue : 05/01/2017 13/14

## 16. Other information

**Revision comments** 

: Addition of the compressed gas pictogram on section 2 and section 1 for Parsippany address

▼ Indicates information that has changed from previously issued version.

#### **Notice to reader**

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.



RB is a member of the CSPA Product Care Product Stewardship Program.

Code # : D0224478\_US GHS SDS # : D0224478 v10.0 Date of issue : 05/01/2017 14/14