

D500-2 Series Aluminum Multi Section Extension Ladders



The D500-2 aluminum extension ladders have a duty rating of 375 lbs and feature the exclusive ALFLO® rung joint for a TWIST-PROOF® performance every time. The end caps are mar resistant and notched for easy separation of sections. Both the base and the fly sections can be used separately. Internal guides increase the ease of operation when raising and lowering. The feet are heavy-duty, self-aligning and free swinging for hard or penetrable surfaces. Rugged spring-loaded locks operate smoothly. TRACTION-TRED® D-rungs are slip resistant. Duty rating changes to 300 lbs for 36 ft-48 ft models.

Features

- Alflo rung joint for Twist-Proof performance
- Heavy duty shoe with slip-resistant tread and spur plate
- Interlocking side rails
- Mar-resistant molded end caps
- Modified I-beam rails
- Removable section for use as a single ladder
- Rope and pulley system
- Rope clamp ties rope to rung
- Slip-resistant Traction-Tred D-rungs
- Spring loaded locks

Specifications

Model No.	Size	Reach Height	Max Working Length	Max. Open Extended Length	Load Capacity
D520-2	20 ft	20 ft	17 ft	17 ft	375 lbs
D524-2	24 ft	23 ft	21 ft	21 ft	375 lbs
D528-2	28 ft	27 ft	25 ft	25 ft	375 lbs
D532-2	32 ft	31 ft	29 ft	29 ft	375 lbs
D536-2	36 ft	34 ft	32 ft	32 ft	300 lbs
D540-2	40 ft	37 ft	35 ft	35 ft	300 lbs
D544-2	44 ft	41 ft	39 ft	39 ft	300 lbs
D548-2	48 ft	45 ft	43 ft	43 ft	300 lbs