PROFESSIONAL STRENGTH PAINT & VARNISH STRIPPER

Visit EZstrip.ca today for detailed instructions and project demos!

CARE & USAGE INSTRUCTIONS







Shake well before use. Apply (brush, roll on, or spray) a liberal coating of EZ Strip. For layered paint, wait ten minutes before applying a second coat of EZ Strip. **Cover area with plastic film to prevent drying. Do not let EZ Strip dry out as it will stop working, if EZ Strip does dry out, re-apply.**

Determine performance time time using these guidelines: **Most Painted Surfaces:** 30 minutes to 1 hour **Multi-layered paint:** 1 hour to overnight **Stain, floor wax, and varnish:** 15 to 30 minutes **Polyurethane and acrylic:** 1 to 2 hours

Use a scraping blade to remove softened material and discard safely. Finish removal using a scouring pad or a stainless steel scouring ball with warm water to remove remainder of softened material.

To finish, wipe with a damp cloth. <u>Area must be neutralized with water</u> or <u>EZ Strip will continue to work.</u> Allow surface to dry completely before sanding or painting. *For best performance use EZ Strip above 10°C (50° F). Do not use in direct sunlight. Do not freeze. May etch some plastics.

How To Video



Disposal: Allow liquid to evaporate and residue to dry outdoors. Then dispose of in accordance with local, state and federal regulations Avoid Contact with Eyes. If injested drink plenty of water.