Issuing DateNo data availableRevision Date29-Sep-2015Revision Number2



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name Lithium Ion rechargeable battery

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use LITHIUM ION BATTERIES

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Name Hangzhou Skyrich Power CO. LTD

Supplier Address 118 Linban Rd.

HangZhou Zhejiang 310022 China

Supplier Phone Number Phone: 0086 571 88132007

Supplier Email sales@skyrichpower.com

Emergency telephone number

Company Emergency Phone

0086 571 88144451

Number

2. HAZARDS IDENTIFICATION

Classification

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200). This product is an article which is a sealed battery and as such does not require an MSDS per the OSHA hazard communication standard unless ruptured. The hazards indicated are for a ruptured battery.



Acute toxicity - Dermal	Category 4
Skin corrosion/irritation	Category 1 Sub-category B
Serious eye damage/eye irritation	Category 1
Specific target organ toxicity (repeated exposure)	Category 1

GHS Label elements, including precautionary statements

Emergency Overview

Signal word Danger

Hazard Statements

Harmful in contact with skin

Causes severe skin burns and eye damage



This product is an article which contains a chemical substance. Safety information is given for exposure to the article as sold. Intended use of the product should not result in exposure to the chemical substance. This is a battery. In case of rupture: the above hazards exist.

Appearance No information available Physical state Solid Odor No information available

Precautionary Statements - Prevention

Wear protective gloves/protective clothing/eye protection/face protection Do not breathe dust/fume/gas/mist/vapors/spray

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Precautionary Statements - Response

Specific treatment (see .? on this label)

Immediately call a POISON CENTER or doctor/physician

Specific treatment (see supplemental first aid instructions on this label)

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Immediately call a POISON CENTER or doctor/physician

Skin

Call a POISON CENTER or doctor/physician if you feel unwell

Wash contaminated clothing before reuse

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing Immediately call a POISON CENTER or doctor/physician

Ingestion

IF SWALLOWED: Rinse mouth. DO NOT induce vomiting



Page 2/13

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

54 % of the mixture consists of ingredient(s) of unknown toxicity

Other information

May be harmful if swallowed Very toxic to aquatic life with long lasting effects

Interactions with Other Chemicals

No information available.

3. COMPOSITION/INFORMATION ON INGREDIENTS

.

Chemical Name	CAS No	Weight-%	Trade Secret
Copper	7440-50-8	10 - 30	*
Graphite	7782-42-5	7 - 13	*
Phosphate(1-), hexafluoro-, lithium	21324-40-3	5 - 10	*
Ethylene carbonate	96-49-1	5 - 10	*
Aluminum	7429-90-5	5 - 10	*

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

First aid measures

General Advice First aid is upon rupture of sealed battery.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep

eve wide open while rinsing. Do not rub affected area. Remove contact lenses, if present

and easy to do. Continue rinsing. Seek immediate medical attention/advice.

Skin contact Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes. Seek immediate medical attention/advice.

Inhalation Remove to fresh air. If breathing has stopped, give artificial respiration. Get medical

attention immediately. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur. Get medical attention

immediately if symptoms occur.

Ingestion Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water. Never give



Page 3/13

anything by mouth to an unconscious person. Call a physician or poison control center immediately.

Self-protection of the first aider

Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid contact with skin, eyes or clothing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required. Wear personal protective clothing (see section 8).

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and

Effects

Coughing and/ or wheezing. Itching. Burning sensation.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Product is a corrosive material. Use of gastric lavage or emesis is contraindicated.

Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood

pressure may occur with moist rales, frothy sputum, and high pulse pressure.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of irritating gases and vapors.

Hazardous Combustion Products

Carbon oxides.

Explosion Data

Sensitivity to Mechanical Impact No.

Sensitivity to Static Discharge No.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.



Page 4/13

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Attention! Corrosive material. Avoid contact with skin, eyes or clothing. Ensure adequate

ventilation. Use personal protective equipment as required. Evacuate personnel to safe

areas. Keep people away from and upwind of spill/leak.

Other Information Refer to protective measures listed in Sections 7 and 8.

Environmental precautions

Environmental precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage

if safe to do so. Should not be released into the environment. Do not allow to enter into

soil/subsoil. Prevent product from entering drains.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling In case of rupture: Handle in accordance with good industrial hygiene and safety practice.

Avoid contact with skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Use only with adequate ventilation and in closed systems. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash

before reuse.

Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from

moisture. Store locked up. Keep out of the reach of children. Store away from other

materials.

Incompatible Products Acids. Bases. Oxidizing agent.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH	
Copper	TWA: 0.2 mg/m ³ fume TWA: 1	TWA: 0.1 mg/m ³ fume	IDLH: 100 mg/m ³ dust, fume	
7440-50-8	mg/m³ Cu dust and mist	TWA: 1 mg/m ³ dust and mist	and mist	



			TWA: 1 mg/m ³ dust and mist	
		(vacated) TWA: 0.1 mg/m ³ Cu dust, fume, mist	TWA: 0.1 mg/m ³ fume	
Graphite	TWA: 2 mg/m ³ respirable	TWA: 15 mg/m ³ total dust IDLH: 1250 mg/m ³		
7782-42-5	fraction all forms except graphite	synthetic	TWA: 2.5 mg/m ³ respirable	
	fibers	TWA: 5 mg/m ³ respirable	dust	
		fraction synthetic		
		(vacated) TWA: 2.5 mg/m ³		
		respirable dust natural		
		(vacated) TWA: 10 mg/m ³ total		
		dust synthetic		
		(vacated) TWA: 5 mg/m ³		
		respirable fraction synthetic		
		TWA: 15 mppcf natural TWA: 2.5 mg/m ³ F		
Phosphate(1-), hexafluoro-, lithium	osphate(1-), hexafluoro-, lithium TWA: 2.5 mg/m ³ F			
21324-40-3		TWA: 2.5 mg/m ³ dust		
		(vacated) TWA: 2.5 mg/m ³		
Aluminum	TWA: 1 mg/m ³ respirable	TWA: 15 mg/m ³ total dust	TWA: 10 mg/m ³ total dust	
7429-90-5	fraction	TWA: 5 mg/m ³ respirable	TWA: 5 mg/m ³ respirable dust	
		fraction		
		(vacated) TWA: 15 mg/m³ total		
		dust		
		(vacated) TWA: 5 mg/m ³		
		respirable fraction (vacated)		
		TWA: 5 mg/m ³ Al Aluminum		

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits NIOSH IDLH Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d

962 (11th Cir., 1992)

Appropriate engineering controls

Engineering Measures Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection Face protection shield.

Skin and body protection Wear protective gloves and protective clothing. Long sleeved clothing. Chemical resistant

apron. Impervious gloves.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are

exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice. Avoid contact with

skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Take off contaminated clothing and wash before

reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical state Solid



Page 6/13

None

Odor

Appearance Aluminum laminated battery with

exposed terminals for electrical

connections

Color Different colors available Odor Threshold None

PropertyValuesRemarksMethodpHNo data availableNone known

Melting / freezing point
No data available
None known

Flammability Limit in Air

Upper flammability limit
Lower flammability limit
No data available
Vapor pressure
No data available

None known Vapor density No data available None known **Specific Gravity** No data available None known Water Solubility Insoluble in water. None known Solubility in other solvents No data available None known Partition coefficient: n-octanol/waterNo data available None known **Autoignition temperature** No data available None known **Decomposition temperature** No data available None known Kinematic viscosity No data available None known Dynamic viscosity No data available None known

Explosive properties

Oxidizing properties

No data available
No data available

Other Information

Softening Point
VOC Content (%)
Particle Size
No data available
No data available
No data available

Particle Size Distribution

Nominal Voltage 12.8V Rated Capacity 3000mAh Watt Hour 38.4Wh

10. STABILITY AND REACTIVITY

Reactivity

None

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Exposure to air or moisture over prolonged periods.

Incompatible materials

Acids. Bases. Oxidizing agent.

Hazardous Decomposition Products

Carbon oxides.



Page 7/13

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information Product does not present an acute toxicity hazard based on known or supplied information.

In case of rupture:.

Inhalation Specific test data for the substance or mixture is not available. Corrosive by inhalation.

(based on components). Inhalation of corrosive fumes/gases may cause coughing, choking, headache, dizziness, and weakness for several hours. Pulmonary edema may occur with tightness in the chest, shortness of breath, bluish skin, decreased blood pressure, and increased heart rate. Inhaled corrosive substances can lead to a toxic edema of the lungs.

Pulmonary edema can be fatal. May cause irritation of respiratory tract.

Eye contact Specific test data for the substance or mixture is not available. Causes burns. (based on

components). Corrosive to the eyes and may cause severe damage including blindness.

Causes serious eye damage. May cause irreversible damage to eyes.

Skin contact Specific test data for the substance or mixture is not available. Corrosive. (based on

components). Causes burns. May be absorbed through the skin in harmful amounts.

Harmful in contact with skin.

Ingestion Specific test data for the substance or mixture is not available. Causes burns. (based on

components). Ingestion causes burns of the upper digestive and respiratory tracts. May cause severe burning pain in the mouth and stomach with vomiting and diarrhea of dark blood. Blood pressure may decrease. Brownish or yellowish stains may be seen around the mouth. Swelling of the throat may cause shortness of breath and choking. May cause lung damage if swallowed. May be fatal if swallowed and enters airways. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea,

vomiting and diarrhea.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Graphite > 10000 mg/kg (Rat)		-	-
7782-42-5			

Information on toxicological effects

Symptoms Erythema (skin redness). Burning. May cause blindness. Coughing and/ or wheezing.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Mutagenic Effects No information available.

Carcinogenicity Contains no ingredient listed as a carcinogen.

Reproductive toxicityNo information available.

STOT - single exposure No information available.

STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure. Based on



classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from

chronic or repeated exposure. (STOT RE).

Chronic Toxicity No known effect based on information supplied.

Target Organ Effects Respiratory system. Eyes. Skin. Gastrointestinal tract (GI).

Aspiration Hazard No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)
2,461.00 mg/kg
ATEmix (dermal)
1,533.00 mg/kg (ATE)
ATEmix (inhalation-dust/mist)
716.00 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life. Very toxic to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Copper 7440-50-8		96h LC50: 0.0068 - 0.0156 mg/L (Pimephales promelas) 96h LC50: = 0.112 mg/L (Poecilia reticulata) 96h LC50: = 0.3 mg/L (Cyprinus carpio) 96h LC50: = 0.8 mg/L (Cyprinus carpio) 96h LC50: = 1.25 mg/L (Lepomis macrochirus) 96h LC50: = 0.052 mg/L (Oncorhynchus mykiss) 96h LC50: = 0.2 mg/L (Pimephales promelas)		48h EC50: = 0.03 mg/L

Persistence and Degradability

No information available.

Bioaccumulation

No information available

Other adverse effects

No information available.

(UL)

Page 9/13

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methodsThis material, as supplied, is not a hazardous waste according to Federal regulations (40)

CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local

regulations for additional requirements.

Contaminated Packaging Dispose of contents/containers in accordance with local regulations.

California Hazardous Waste Codes 141

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Copper 7440-50-8	Toxic
Aluminum 7429-90-5	Ignitable powder

14. TRANSPORT INFORMATION

Note:

The transportation of primary lithium cells and batteries is regulated by the International Civil Aviation Organization, International Air Transport Association, International Maritime Dangerous Goods Code and the US Department of Transportation. The batteries must meet the following criteria for shipment: 1. Air shipments must meet the requirements listed in Special Provision A45 of the International Air Transport Association Dangerous Goods Regulations. 2. Meet the requirements for the US Department of Transportation listed in 49 CFR 173.185. 3. The transport of primary lithium batteries is prohibited aboard passenger aircraft. Refer to the Federal Register December 15, 2004 (Hazardous Materials; Prohibited on the Transportation of Primary Lithium Batteries and Cells Aboard Passenger Aircraft; Final Rule)

Lithium batteries shipped as "Lithium batteries", "Lithium batteries packed with equipment", or "Lithium batteries contained in equipment" may not be classified as "Dangerous Goods" when shipped in accordance with "special provision A45 of IATA-DGR" or "special provision 188 of IMO-IMDG Code"

The Li-Ion Battery have been tested under provisions of the UN Manual of Tests and Criteria, Part III, sub-section 38.3 and are classified as non-dangerous goods.

DOT NOT REGULATED
Proper Shipping Name NON-REGULATED

Hazard Class N/A Emergency Response Guide 147

Number

MEX Not regulated

MEX Not regulated

ICAO Not regulated

Not regulated

Not regulated



Proper Shipping Name NON REGULATED

Hazard Class N/A

IMDG/IMO Not regulated

Hazard Class N/A EmS-No. F-A, S-I

RID Not regulated

ADR Not regulated

ADN Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA Complies

DSL All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Copper - 7440-50-8	7440-50-8	10 - 30	1.0
Aluminum - 7429-90-5	7429-90-5	5 - 10	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	No
Chronic Health Hazard	No
Fire Hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	Chemical Name CWA - Reportable Quantities		CWA - Priority Pollutants	CWA - Hazardous Substances
Copper 7440-50-8		X	X	

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Copper	5000 lb		RQ 5000 lb final RQ
7440-50-8			RQ 2270 kg final RQ

US State Regulations



California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

.

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Copper	Χ	X	Χ	X	Χ
7440-50-8					
Graphite	Χ	X	X		
7782-42-5					
Ethylene carbonate		X	X		
96-49-1					
Dimethyl carbonate	X	X	X		
616-38-6					
Aluminum	X	X	Χ	X	
7429-90-5					

International Regulations

Mexico

National occupational exposure limits

Component	Carcinogen Status	Exposure Limits
Copper		Mexico: TWA= 1 mg/m ³
7440-50-8 (10 - 30)		Mexico: TWA= 0.2 mg/m ³
		Mexico: STEL= 2 mg/m ³
Graphite		Mexico: TWA= 2 mg/m ³
7782-42-5 (7 - 13)		
Aluminum		Mexico: TWA= 10 mg/m ³
7429-90-5 (5 - 10)		

Mexico - Occupational Exposure Limits - Carcinogens

Canada

WHMIS Hazard Class

Non-controlled

16. OTHER INFORMATION

NFPA Health Hazards 1 Flammability 0 Instability 0 Physical and Chemical Hazards - HMIS Health Hazards 0 Flammability 0 Physical Hazard 0 Personal Protection

Prepared By Product Stewardship

23 British American Blvd. Latham, NY 12110

1-800-572-6501 29-Sep-2015

Revision Note No information available

Disclaimer

Revision Date

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text



Page 12/13

End of Safety Data Sheet



