

SPECIFICATIONS:

PRODUCT NAME	Rechargeable Ride-on Lawnmower
COMMERCIAL NAME	ERIDER
TYPE	BATTERY POWERED
MODEL	WB76E
Drive Motor	Forward--Neutral--Reverse
Drive system	Electric
Battery Capacity– Volts & Amphour Rating	72V/18AH battery
Ground Speed (approx.)	Forward Max.3.7 mph, Reverse Max. 3.1 mph
DECK	
Deck Material	Metal
Deck Construction	Metal
Number of spindles	2
Blade Tip Speed	2800 min ⁻¹
Spindle Material	Steel motor shaft
Deck Drive	Cutting motors:DC72V/800W Qty.: 2
Deck Engagement	Electric-Blade mounted directly to motor shaft
Deck Lift System	Hand operated
Cutting width	30” (76cm)
Cutting position and heights (1/2/3/4/5/6/7/8/9/10)	1(1in), 2(1.26in), 3(1.65in), 4(1.95in), 5(2.32in) 6(2.72in), 7(3.1in), 8(3.46in), 9(3.78in), 10(4.1in),
WHEELS	
Front / Rear	11” x 4.00-5NHS / 13” x 5.00-6NHS
FEATURES	
Safety Certification	2006/42/EC, 2014/30/EU, 2000/14/EC, UL60730, UL2753+ANSI B71.1, UL2595, EN ISO 12100:2010
Headlights	N/A
Seat	Fixed with springs
Hour meter	N/A
MACHINE DIMENSION	
Weight	Net weight:309lbs/140 kg (Lithium polymer battery)
Length (inches)	58.3 (1480mm)
Width (inches)	38.6 (980mm) with discharge deflector
Height (inches)	39.6 (1016mm)
ATTACHMENTS	
Charger	72V/3A Certified Smart Charger
Grass catcher	N/A
Grass deflector	Included
Sound pressure level Lpa:	76.2dB(A), Kpa=3dB(A)
Measured sound power level Lwa:	89.69dB(A), Kwa= 3dB(A)
Guaranteed sound power level:	92dB(A)
Hand-arm vibration (left/right):	left : 0.445m/s2 / right : 0.338m/s2, (K=1.5m/s2)
Whole body vibration:	0.707m/s2, (K=1.5m/s2)
Hardware Version	V 1.0
Software Version	V 1.0
Blade type	76E F13010 (2 pcs)