

**VULKEM 116 GRAY**Version 2.  
REVISION DATE: 08/08/2008

Print Date 04/21/2010

**SECTION 1 - PRODUCT IDENTIFICATION**

Trade name : VULKEM 116 GRAY  
 Product code : 426712 323

COMPANY : Tremco Incorporated  
 3735 Green Road  
 Cleveland, OH 44122

Telephone : (216) 292-5000 8:30 - 5:00 EST  
 Emergency Phone: : (216) 765-6727 8:30 - 5:00 EST  
 After Hours: Chemtrec 1-800-424-9300

Product use : Sealant

**SECTION 2 - HAZARDS IDENTIFICATION****Emergency Overview**

Gray. Non-sag gunnable paste. May cause slight irritation to the respiratory system. May cause nausea, headaches, and dizziness. May cause drowsiness, weakness, and fatigue. May cause allergic respiratory sensitization. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention. Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel.

**Acute Potential Health Effects/ Routes of Entry**

Inhalation : May cause slight irritation to the respiratory system. May cause nausea, headaches, and dizziness. May cause drowsiness, weakness, and fatigue. May cause allergic respiratory sensitization.

Eyes : Direct contact may cause mild irritation.

Ingestion : May cause gastrointestinal irritation, nausea, and vomiting.

Skin : May cause sensitization resulting in irritation, itching and redness.

**Aggravated Medical Conditions**

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

**Chronic Health Effects**

Overexposure may cause dermatitis, asthma, skin and respiratory sensitization and decreased lung function. Prolonged or repeated contact/exposure to aromatic petroleum distillates may cause defatting, drying, and irritation of the skin, dermatitis, and central nervous system (CNS) effects. Inhalation of crystalline silica (quartz) can cause cancer based on animal data, and IARC concludes sufficient evidence in humans (Group 1). Prolonged and repeated overexposure to free crystalline silica dust above the TLV level may cause scarring of the lungs with cough and shortness of breath. A delayed lung injury, silicosis may result from breathing free silica. Fillers are encapsulated and not expected to be released from product under normal conditions of use. Prolonged or repeated exposure to mineral spirits (petroleum naphtha or stoddard solvent) may cause defatting, drying, and irritation of the skin, dermatitis, central nervous system (CNS) effects, and adverse liver, kidney, and lung effects.

**Target Organs:** Skin, Eye, Ingestion, Lung

**SECTION 3 - PRODUCT COMPOSITION**

Chemical Name	CAS-No.	Weight %
---------------	---------	----------

**VULKEM 116 GRAY**

Version 2.

Print Date 04/21/2010

REVISION DATE: 08/08/2008

Aromatic Polyisocyanate Resin	NJ TSRN# 51721300-5270P	30.0 - 60.0
Diisodecyl phthalate	26761-40-0	15.0 - 40.0
Calcium Carbonate (Limestone)	1317-65-3	10.0 - 30.0
Tackifier	NJ TSRN# 51721300-5272P	5.0 - 10.0
Thickener	NJ TSRN# 51721300-5300P	3.0 - 7.0
Titanium dioxide	13463-67-7	3.0 - 7.0
Petroleum distillates	64742-47-8	1.0 - 5.0
Butyl benzyl phthalate	85-68-7	- <1.0
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	- <1.0
2,4-Toluene diisocyanate	584-84-9	- <0.1
Toluene-2,6-Diisocyanate	91-08-7	- <0.1
o-Cresol	95-48-7	- <0.1

**SECTION 4 - FIRST AID MEASURES**

Get immediate medical attention for any significant overexposure.

- Inhalation : Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention. Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel.
- Eye contact : Flush with water for at least 15 minutes while holding eye lids apart. Get medical attention immediately.
- Skin contact : Clean area of contact thoroughly using soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
- Ingestion : Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

**SECTION 5 - FIRE FIGHTING MEASURES**

- Flash point : 150 F, 66 C
- Method : Tag Closed Cup
- Lower explosion limit : 0.60 %(V) Solvent
- Upper explosion limit : 7 %(V) Solvent
- Autoignition temperature : Not available.
- Extinguishing media : If water fog is ineffective, use carbon dioxide, dry chemical or foam.
- Hazardous combustion products : Carbon monoxide and carbon dioxide can form. Hydrocyanic acid and nitrogen oxides can form.
- Protective equipment for firefighters : Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA).

**SECTION 6 - ACCIDENTAL RELEASE MEASURES**

Use appropriate protective equipment. Avoid contact with material. Scrape up and transfer to appropriate container for disposal.

**SECTION 7 - HANDLING AND STORAGE**

Prevent inhalation of vapor, ingestion and contact with skin, eyes and clothing. Preferably use entire contents in

**VULKEM 116 GRAY**

Version 2.

Print Date 04/21/2010

REVISION DATE: 08/08/2008

one continuous work session. Do not smoke, weld, generate sparks, or use flame near container. Change soiled work clothes frequently. Clean hands thoroughly after handling Do not store or use near food. Keep container closed when not in use. Since emptied containers retain product residue and vapor, observe precautions even after container is emptied. Store under dry warehouse conditions away from heat and all ignition sources.

**SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**
**Personal protection equipment**

- Respiratory protection : Wear appropriate, properly fitted NIOSH/MSHA approved organic vapor or supplied air respirator when airborne contaminant level(s) are expected to exceed exposure limits indicated on the MSDS. Follow manufacturer's directions for respirator use.
- Hand protection : Use suitable impervious nitrile or neoprene gloves and protective apparel to reduce exposure.
- Eye protection : Wear appropriate eye protection. Use safety glasses if eye contact is likely.
- Skin and body protection : Use disposable or impervious clothing if work clothing contamination is likely. Remove and wash contaminated clothing before reuse.
- Protective measures : Use professional judgment in the selection, care, and use.
- Engineering measures : Use general ventilation and/ or local exhaust to reduce the airborne contaminant concentration below the exposure limit listed in the MSDS

**Exposure Limits**

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Regulation</u>	<u>Limit</u>	<u>Form</u>
Calcium Carbonate (Limestone)	1317-65-3	OSHA PEL: OSHA PEL: ACGIH TWA: ACGIH TWA: OSHA TWA: OSHA TWA:	5 mg/m3 15 mg/m3 3 mg/m3 10 mg/m3 15 mg/m3 5 mg/m3	Respirable fraction. Total dust. Respirable particles. Inhalable particles. Total dust. Respirable fraction.
Titanium dioxide	13463-67-7	ACGIH TWA: OSHA PEL: OSHA TWA: OSHA TWA:	10 mg/m3 15 mg/m3 15 mg/m3 5 mg/m3	Total dust. Total dust. Respirable fraction.
Petroleum distillates	64742-47-8	ACGIH TWA: ACGIH TWA:	200 mg/m3 200 mg/m3	Non-aerosols total hydrocarbon vapor Non-aerosols total hydrocarbon vapor
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	OSHA TWA: OSHA TWA: OSHA PEL: OSHA PEL: ACGIH TWA:	0.1 mg/m3 0.3 mg/m3 15 mg/m3 5 mg/m3 0.025 mg/m3	Respirable. Total dust. Total dust. Respirable fraction. Respirable fraction.
2,4-Toluene diisocyanate	584-84-9	ACGIH TWA: ACGIH STEL:	0.005 ppm 0.02 ppm	

**VULKEM 116 GRAY**

Version 2.

Print Date 04/21/2010

REVISION DATE: 08/08/2008

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Regulation</u>	<u>Limit</u>	<u>Form</u>
Toluene-2,6-Diisocyanate	91-08-7	ACGIH TWA: ACGIH STEL:	0.005 ppm 0.02 ppm	
o-Cresol	95-48-7	ACGIH TWA: OSHA PEL:	5 ppm 22 mg/m3	

**SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

Form	: Non-sag gunnable paste
Color	: Gray
Odor	: Petroleum Solvent
pH	: Not available.
Vapour pressure	: Not available.
Vapor density	: Heavier than air
Melting point/range	: Not available.
Freezing point	: Not available.
Boiling point/range	: 280 °F, 138 °C
Water solubility	: Insoluble
Specific Gravity	: 1.1344
% Volatile Weight	: 7 %

**SECTION 10 - REACTIVITY / STABILITY**

Substances to avoid	: Amines. Water or moisture and oxidizing agents. Alcohols. Strong acids. Strong bases.
Stability	: Material is stable under normal storage, handling, and use.
Hazardous polymerization	: Will not occur.

**SECTION 11 - TOXICOLOGICAL INFORMATION**

Butyl benzyl phthalate, CAS-No.: 85-68-7	
Acute oral toxicity (LD-50 oral)	13,500 mg/kg ( Rat )
2,4-Toluene diisocyanate, CAS-No.: 584-84-9	
Acute oral toxicity (LD-50 oral)	5,800 mg/kg ( Rat )
Acute inhalation toxicity (LC-50)	14 mg/l for 4 h ( Rat ) 10 mg/l for 4 h ( Mouse ) 13 mg/l for 4 h ( Guinea pig ) 11 mg/l for 4 h ( Rabbit )
o-Cresol, CAS-No.: 95-48-7	
Acute oral toxicity (LD-50 oral)	940 mg/kg ( Rabbit ) 1,800 mg/kg ( Rabbit ) 121 mg/kg ( Rat ) 344 mg/kg ( Mouse ) 1,350 mg/kg ( Rat )
Acute inhalation toxicity (LC-50)	0.179 mg/l for 2 h ( Mouse )
Acute dermal toxicity (LD-50 dermal)	620 mg/kg ( Rat ) 890 mg/kg ( Rabbit ) 620 mg/kg ( Mouse )

**VULKEM 116 GRAY**Version 2.  
REVISION DATE: 08/08/2008

Print Date 04/21/2010

**SECTION 12 - ECOLOGICAL INFORMATION**

No Data Available

**SECTION 13 - DISPOSAL CONSIDERATIONS**

Disposal Method : Waste not regulated under RCRA. Dispose of in compliance with state and local regulations.

**SECTION 14 - TRANSPORTATION / SHIPPING DATA**TDG / DOT Shipping Description:  
NOT REGULATED**SECTION 15 - REGULATORY INFORMATION****North American Inventories:**All components are listed or exempt from the TSCA inventory.  
This product or its components are listed on, or exempt from the Canadian Domestic Substances List.**U.S. Federal Regulations:**

SARA 313 Components : None present or none present in regulated quantities.

SARA 311/312 Hazards : Acute Health Hazard  
Chronic Health Hazard  
Fire Hazard

## OSHA Hazardous Components :

Diisodecyl phthalate	26761-40-0
Calcium Carbonate (Limestone)	1317-65-3
Titanium dioxide	13463-67-7
Petroleum distillates	64742-47-8
Butyl benzyl phthalate	85-68-7
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7
2,4-Toluene diisocyanate	584-84-9
Toluene-2,6-Diisocyanate	91-08-7
o-Cresol	95-48-7

OSHA Status: Considered : Irritant  
hazardous based on the : Sensitizer  
following criteria: : Carcinogen

OSHA Flammability : IIIA

Regulatory VOC (less water and : 80 g/l  
exempt solvent)

VOC Method 310 : 2 %

Chemical is listed as an IARC, NTP, OSHA, or ACGIH Carcinogen:

**VULKEM 116 GRAY**

Version 2.

Print Date 04/21/2010

REVISION DATE: 08/08/2008

Butyl benzyl phthalate 85-68-7  
 Crystalline Silica (Quartz)/ Silica Sand 14808-60-7

**U.S. State Regulations:**

MASS RTK Components : Calcium Carbonate (Limestone) 1317-65-3  
 Titanium dioxide 13463-67-7  
 Petroleum distillates 64742-47-8  
 Crystalline Silica (Quartz)/ Silica Sand 14808-60-7  
 2,4-Toluene diisocyanate 584-84-9  
 Toluene-2,6-Diisocyanate 91-08-7  
 o-Cresol 95-48-7

Penn RTK Components : Aromatic Polyisocyanate Resin NJ TSRN# 51721300-5270P  
 Diisodecyl phthalate 26761-40-0  
 Calcium Carbonate (Limestone) 1317-65-3  
 Tackifier NJ TSRN# 51721300-5272P  
 Thickener NJ TSRN# 51721300-5300P  
 Titanium dioxide 13463-67-7  
 Petroleum distillates 64742-47-8  
 2,4-Toluene diisocyanate 584-84-9

NJ RTK Components : Aromatic Polyisocyanate Resin NJ TSRN# 51721300-5270P  
 Diisodecyl phthalate 26761-40-0  
 Calcium Carbonate (Limestone) 1317-65-3  
 Tackifier NJ TSRN# 51721300-5272P  
 Thickener NJ TSRN# 51721300-5300P  
 Titanium dioxide 13463-67-7  
 Petroleum distillates 64742-47-8  
 Butyl benzyl phthalate 85-68-7  
 Crystalline Silica (Quartz)/ Silica Sand 14808-60-7

WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm:

26761-40-0	Diisodecyl phthalate
85-68-7	Butyl benzyl phthalate
14808-60-7	Crystalline Silica (Quartz)/ Silica Sand
584-84-9	2,4-Toluene diisocyanate
91-08-7	Toluene-2,6-Diisocyanate
1333-86-4	Carbon Black
100-41-4	Ethylbenzene

**SECTION 16 - OTHER INFORMATION**

**HMIS Rating :**

Health	2
Flammability	2
Reactivity	0
PPE	

0 = Minimum  
 1 = Slight  
 2 = Moderate  
 3 = Serious  
 4 = Severe



**VULKEM 116 GRAY**

Version 2.  
REVISION DATE: 08/08/2008

Print Date 04/21/2010

**Further information:**

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

**Prepared by: Rich Mikol**

**Legend**

- |  |  |
|--|--|
| ACGIH - American Conference of Governmental Hygienists                         | PEL - Permissible Exposure Limit                         |
| CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act | RCRA - Resource Conservation and Recovery Act            |
| DOT - Department of Transportation   | RTK - Right To Know                                      |
| DSL - Domestic Substance List  | SARA - Superfund Amendments and Reauthorization Act      |
| EPA - Environmental Protection Agency  | STEL - Short Term Exposure Limit                         |
| HMIS - Hazardous Materials Information System                                  | TLV - Threshold Limit Value                              |
| IARC - International Agency for Research on Cancer                             | TSCA - Toxic Substances Control Act                      |
| MSHA - Mine Safety Health Administration                                       | TWA - Time Weighted Average                              |
| NDSL - Non-Domestic Substance List   | V - Volume   |
| NIOSH - National Institute for Occupational Safety and Health                  | VOC - Volatile Organic Compound                          |
| NTP - National Toxicology Program  | WHMIS - Workplace Hazardous Materials Information System |
| OSHA - Occupational Safety and Health Administration                           |  |