

# 17025SSA

## 6" IC Super-Sloped Ceiling Airtight Housing

### Product Description

Suitable for new construction in residential and commercial applications. Designed for slope ceiling installation for ceilings from 7/12 to 12/12 pitch. The socket pivots to allow the lamp to be aimed straight down regardless of ceiling pitch. IC rated. Suitable for direct contact with insulation. 150 watt maximum lamp rating

#### Housing

Aluminum construction provides greater heat dissipation. Washington State Energy Code approved to meet restricted airflow requirements. Airtight housing limits the exchange of air between ceiling plenum and heated/cooled areas. Integral thermal protector guards against improper lamping and misuse of insulation materials. Adjustable socket bracket assures proper and consistent lamp positioning. 7 5/8" height allows use in 2" x 8" joist construction.

#### Plaster Frame

Housing is secured to plaster frame with screws and can be removed for access to junction box. Housing adjusts from 1/2" to 1 1/2" to accommodate ceiling thickness.

#### Junction Box

Listed for through branch circuit wiring and includes several 3/4" knockouts. Four pryouts with integral strain relief simplify Romex installation. Supplied with three push-in wire connectors.

#### Hanger Bars

Heavy-gauge NICOR captive hanger bars provide greater stability, allowing housing to be positioned at any point within a 24" joist span, then locked in place with set screws. Unique hanger bar lip design helps align can to joist. Four double-headed captive nails provide for ease of installation. Bars can be repositioned 90° on plaster frame without tools. Bars fit onto T-bar spine for quick alignment and can be permanently secured. Score lines allow bars to be shortened without tools to accommodate a 12" joist span.

### Ordering Information

Catalog Number	Description
17022RA	6" IC Super-Sloped Ceiling Airtight Housing

Project

Catalog

Type

