



## DUSK-TO-DAWN PHOTOCELL SWITCH REPLACEMENT INSTRUCTIONS

*Please read carefully and save these instructions, as you may need them at a later date.*

### CAUTION

Turn off the main power at the circuit breaker before replacing the photocell, in order to prevent possible shock.

### GENERAL

All electrical connections must be in accordance with local and National Electrical Code (N.E.C.) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician.

Remove the parts from the box and make sure that no parts are missing by referencing the illustrations on the installation instructions.

### FIXTURE UNINSTALLATION

1. **CAUTION:** Turn off the power at the main circuit breaker box prior to performing the photocell replacement to prevent possible shock.
2. Remove the fixture from the wall by loosening the fixture's thumb nuts. Carefully pull the fixture from the wall. Leave the existing mounting bracket on the outlet box. Untwist the wire nuts to disconnect the fixture from the building/ house supply wires. **Keep the thumb nuts and wire nuts.**

### UNINSTALLING THE EXISTING PHOTOCELL SWITCH

3. Loosen the decorative nut. Untwist the wire nut to disconnect the photocell wire from the black fixture wire.
4. Pull the photocell switch from the fixture canopy. Discard the photocell switch. **Keep the wire nut and decorative nut.**

### INSTALLING THE NEW PHOTOCELL SWITCH

5. Insert the new photocell neck through hole that was vacated by the old photocell switch. Adjust the hex nut on the neck, such that enough of the neck protrudes out from the hole to allow the decorative nut to thread onto the neck.
6. Using one of the wire nuts, attach the short wire of the photocell switch to the black wire of the fixture.

### REINSTALLING THE FIXTURE

7. Using one of the wire nuts, attach the long wire of the photocell switch to the black supply wire of the building/house. Using the last wire nut, attach the white fixture wire to the white supply wire.
8. Carefully push the wire connections into the outlet box. Place the fixture over the outlet box and secure it onto the mounting bracket using the thumb nuts.
9. Turn on the power at the main circuit breaker box.

INSTALLATION IS NOW COMPLETED

