

Clear Silicone Sealant, 500 F High Heat RTV

1 PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: Clear Silicone Sealant, 500 F High Heat RTV

SDS Number: 35

Product Code: 76C, 76CT, 76C-6

Revision Date: 6/19/2019

Version:

Product Description: High Heat (up to 500 F intermittent) room temperature vulcanizing silicone sealant; acetoxy cure.

Product Use: High heat sealant

Supplier Details: Rutland Products

7 Crabtree Road Jacksonville, IL 62650

Contact: Faith Nergenah, Brian Miller

Phone: 217-245-7810 **Fax:** 217-245-1194

Email: faith@rutland.com, bmiller@rutland.com

Web: www.rutland.com

Emergency: CHEMTREC (800) 424-9300

HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

None, None, None

2

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: NONE

GHS Hazard Pictograms:

No GHS pictograms indicated for this product

GHS Hazard Statements:

H000 - None

GHS Precautionary Statements:

P233 - Keep container tightly closed.

P271 - Use only outdoors or in a well-ventilated area.

P273 - Avoid release to the environment.

P501 - Dispose of contents/container in accordance with local, regional, state and federal regulations.

Hazards not Otherwise Classified (HNOC) or not Covered by GHS

Route of Entry: Eyes; Skin; Ingestion

Skin Contact: May cause irritation.

Eye Contact: May cause irritation.

Ingestion: Ingestion is not an applicable route of entry for intended use.

Not a hazardous substance or mixture.

3 COMPOSITION/INFORMATION OF INGREDIENTS

SDS Number: 35 Page: 1 / 4 Revision Date: 6/19/2019



Clear Silicone Sealant, 500 F High Heat RTV

Chemical Ingredients:	
CAS#	% Chemical Name:
7631-86-9 64742-46-7	Silica, amorphous Distillates, petroleum, hydrotreated middle
70131-67-8	Siloxanes and Silicones, di-Me, hydroxy-terminated

Percentages withheld, Trade secret.

4 FIRST AID MEASURES

Inhalation: Remove to fresh air. Seek medical attention if cough or other symptoms develop or persist.

Skin Contact: Wash with plenty of water. Get medical attention if irritation develops or persists.

Eve Contact: Immediately flush eyes with plenty of water. After initial flushing, remove contact lenses and continue flushing for at

least 15 minutes. If effects occur, consult a physician, preferably an ophthalmologist. May cause injury due to

mechanical action.

Ingestion: Not a direct hazard. Not considered dangerous. Bring to the attention of a physician.

5 FIRE FIGHTING MEASURES

Flammability: Not classified as a flammability hazard.

Flash Point: > 100 C (212 F) **Flash Point Method:** Closed cup **Burning Rate:** Not Available **Autoignition Temp:** Not Available

Use regular dry chemical, alcohol resistant foam, carbon dioxide or water - choose the one most appropriate for type of surrounding fire.

ACCIDENTAL RELEASE MEASURES 6

Absorb spilled material and place in appropriate container for disposal.

7 HANDLING AND STORAGE

Handling Precautions: Use with adequate ventilation. Avoid contact with eyes. Avoid prolonged and repeated contact with skin.

Wash thoroughly after handling. Keep away from food and drinking water.

Keep container closed to prevent drying out. Store in a cool, well ventilated area. **Storage Requirements:**

8 **EXPOSURE CONTROLS/PERSONAL PROTECTION**

Engineering Controls: A system of local and/or general exhaust is recommended to keep employee exposures as low as

possible.

Personal Protective Wear protective clothing, including long sleeves and gloves, to prevent skin contact. Thoroughly wash

Equipment: clothing before reuse.

PHYSICAL AND CHEMICAL PROPERTIES 9

Appearance: clear, translucent paste

Concentration:

Acetic Acid **Physical State:** Paste Odor: **Odor Threshold:** Not Available Molecular Formula: Not Available **Particle Size:** Not Available Solubility: insoluble **Softening Point:** Spec Grav./Density: 1.007 Not Available **Percent Volatile:** Not Available Viscosity: Not Available **Saturated Vapor** Not Available **Heat Value:** Not Available

SDS Number: 35 Page: 2/4 Revision Date: 6/19/2019



Clear Silicone Sealant, 500 F High Heat RTV

Boiling Point: Not Available

Flammability: Not classified as a flammability hazard.

Partition Coefficient: Not Available **Vapor Pressure:** Not Available pH: Not Available Evap. Rate: Not Available Molecular weight: Not Available **Decomp Temp:** Not Available Freezing/Melting Pt.: Not Available Flash Point: >100 C (>212 F) Octanol: Not Available Vapor Density: Not Available

VOC: Not Available **Bulk Density:** Not Available **Auto-Ignition Temp:** Not Available UFL/LFL: Not Available

10 STABILITY AND REACTIVITY

Reactivity: This product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical Stability: Product is stable under normal conditions.

Conditions to Avoid: Premature exposure to air or moisture initiates curing and the release of acetic acid vapors.

Materials to Avoid: Strong Oxidizing Agents;

Hazardous Decomposition: Combustion will produce carbon oxides, silicon oxides and formaldehyde.

Hazardous Polymerization: Will not occur.

TOXICOLOGICAL INFORMATION 11

No data available.

12 **ECOLOGICAL INFORMATION**

No information available

13 **DISPOSAL CONSIDERATIONS**

Dispose of this product in accordance with all applicable local, state and federal regulations.

14 TRANSPORT INFORMATION

Not Regulated

15 **REGULATORY INFORMATION**

RQ (CAS#) Substance - Reg Codes

Silica, amorphous (7631-86-9) MASS, NJHS, PA, TSCA

Distillates, petroleum, hydrotreated middle (64742-46-7) TSCA

Siloxanes and Silicones, di-Me, hydroxy-terminated (70131-67-8) TSCA

This product does not contain chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm.

Regulatory Code Legend

MASS = MA Massachusetts Hazardous Substances List NJHS = NJ Right-to-Know Hazardous Substances PA = PA Right-To-Know List of Hazardous Substances

TSCA = Toxic Substances Control Act

16 OTHER INFORMATION

PREPARED BY: Brian Miller

SDS Number: 35 Page: 3/4 Revision Date: 6/19/2019



Clear Silicone Sealant, 500 F High Heat RTV

MANUFACTURER DISCLAIMER: The information presented herein is believed to be accurate but is not warranted. Recipients are advised to confirm in advance that the information is current, applicable and suitable to their circumstances.

Revision Date: 6/19/2019

SDS Number: 35 Page: 4 / 4 Revision Date: 6/19/2019