

FLEX GLUE FAQs

Q: Can Flex Glue be used underwater?

A: Yes, you can apply Flex Glue underwater and it will even cure underwater.

Q: Can it be used as a sealant?

A: Flex Glue is an excellent sealant. It can fill large voids and is great for applications with uneven surfaces.

Q: Can Flex Glue be painted?

A: Yes, once fully cured, it can be painted.

Q: What is the difference between Flex Glue in the squeeze tube vs. the Pro Formula Cartridge?

A: All sizes have amazing instant grab technology and our Pro Formula has even more instant grab.

Q: Is Flex Glue resistant to mold and mildew?

A: Yes, it is.

Q: Is Flex Glue UV resistant?

A: Yes, it is.

Q: Can it be used on porous surfaces?

A: Yes, Flex Glue is designed to be super thick. It bonds to porous substrates such as brick, concrete, mortar and so much more.

Q: Can I smooth or tool it once it has been applied?

A: Yes, Flex Glue can be tooled or re-positioned within 10 minutes of initial application. It will dry to the touch in 1 hour.

Q: How long does it take for the product to fully cure?

A: Flex Glue fully cures in 24 – 48 hours and reaches a maximum strength in seven days.

Q: In what temperatures can Flex Glue be applied?

A: For easy application, we recommend applying it in temperatures between 0°F – 150°F.

Q: What temperatures can Flex Glue withstand?

A: Once applied, it can withstand a wide range of temperatures from -40°F up to 200°F.

Q: How do I clean up after using Flex Glue before it cures?

A: Before it cures, Flex Glue can be cleaned with a dry cloth. If necessary, most residues can be removed with isopropyl alcohol.

Q: Can I remove Flex Glue once it's dry?

A: Once dried, Flex Glue can be removed with sharp tools similar to a chisel. However, it may not be possible to separate bonded materials without damaging the surfaces.

Q: Can I use it on drinking water, rain barrels, fish tanks etc.?

A: Flex Glue has not been tested on potable water sources.

Q: How many linear feet can I get out from a tube of Flex Glue?

A: Depending on the thickness of the bead, Flex Glue will provide the following:

MINI 0.75 oz. (white): up to 3.75 linear feet

4 oz. squeeze tube (clear): up to 20 linear feet

6 oz. squeeze tube (white): up to 30 linear feet

9 oz. Pro Formula (clear): up to 45 linear feet

10 oz. Pro Formula (white): up to 50 linear feet

Q: Will Flex Glue Clear retain its clarity once fully cured?

A: Yes, it dries to a crystal-clear bond.

Q: Will Flex Glue shrink during the curing process?

A: Flex Glue will not shrink, crack or peel.