

Industry's Best Subfloor Warranty

SUBFLOOR

Construction Adhesive

Titebond® PROvantage™ Subfloor Construction Adhesive is a professional strength formula that is specifically designed for subfloor installations and general plywood use. It provides a permanent bond that remains flexible, reduces nailing and prevents squeaky floors. It offers a strong initial tack and excellent bond strength. It is covered under the 25 Year Silver Subfloor Warranty against subfloor squeaks and pops.

PROvantage VOC-Compliant Solvent

- VOC-compliant
- Bridges gaps
- Reduces nailing
- Strong, fast grab
- Exceptional durability
- Wet & frozen lumber
- Extrudes 0°F to 100°F
- Prevents squeaks

Recommended For
Subfloor installations, general plywood use, as well as filling gaps and irregularities in the subfloor.

Specifications & Certifications
Exceeds APA AFG-01, ASTM D3498 and ASTM C557.

Compatible Materials
Common building materials, including wood, engineered lumber, particleboard, OSB and wet, frozen and treated lumber.



Titebond®
THE PRO'S ADVANTAGE



Ordering/Sku Information

Size	Part Number	UPC	Case UPC	Weight	Units Per Package	Packages Per Pallet
10 Oz. Cartridge	5481	037083054811	10037083054818	11.60 lbs.	12	108
28 Oz. Cartridge	5482	037083054828	10037083054825	30.85 lbs.	12	44
52 Gallon Drum	5488	NA	NA	616.35 lbs.	1	4

Technical Information

- **Application Temperature:** 0°F to 100°F
- **Service Temperature:** -20°F to 120°F
- **Working Time:** Approximately 20 minutes for a 1/4" bead

Physical Properties

- **Type:** Proprietary synthetic polymer
- **State:** Thixotropic medium-viscosity mastic
- **Color:** Light beige
- **Solids:** 64%
- **Viscosity:** 125,000 cps
- **VOC:** < 50 g/L
- **Weight/Gallon:** 10.6 lbs.
- **Flashpoint:** < 0°F
- **Freeze/Thaw Stability:** Will not freeze
- **Storage Life:** 18 months in tightly closed containers at 75°F
- **Odor:** Solvent (strong)

User Tips

Not designed for continuous submersion or for use on plastics, polystyrene or polyethylene foams. Do not adhere one non-porous material to another as this will slow or prevent drying.

Directions

PREP: Surfaces must be clean and free of any material that may prevent adequate adhesion.

APPLICATION: Cut tip straight across for 1/4" to 3/8" bead. Puncture inner seal and place in cartridge gun. Apply adhesive to each furring strip, stud or floor joist to be covered. **Adhere materials within 15 minutes.** Position material to be bonded and press firmly for full contact with adhesive. **Note:** For subfloors, apply adhesive to joists for one sheet at a time. Nail or screw each sheet as recommended by the American Plywood Association.

CLEANUP: Tools and adhesive may be cleaned with acetone or mineral spirits. Follow solvent vendor's precautions.

Coverage

Size	1/8" bead	1/4" bead	3/8" bead
10 Oz. Cartridge	129 ft.	30 ft.	14 ft.
28 Oz. Cartridge	355 ft.	86 ft.	39 ft.

PROvantage
VOC-Compliant Solvent

Visit Titebond.com for the most up-to-date product information.

Franklin International



Columbus, Ohio 43207 614.443.0241 Technical Service 1.800.347.4583 © 2019 01386_3777bcm FF1163

