

Feeding The Cable Into The Drain

Manual Operation

Confirm that at least 12" (30cm) of cable is in the drain and that the cable outlet of the drain cleaner is within 12" (30cm) of the drain opening. Move the handgrip away from the drum to release chuck from the cable. With your gloved hand, grip the cable close to the drain cleaner and feed the cable into the drain opening. This can be done either with the cable rotating (ON/OFF switch ON) or not. Rotating the cable while feeding into the drain does a better job of cleaning the drain and makes advancing the cable easier. Do not expose more than 12" (30cm) of cable.

As feeding the cable becomes more difficult, the chuck can be used to better grip and feed the cable. Move the handgrip towards the drum to grip the cable with the chuck. With the cable rotating (ON/OFF switch ON) move the drain cleaner towards the drain opening to push the cable down the drain. Release the ON/OFF switch. Move the handgrip away from the drum to release the chuck from the cable. Grip the cable with your gloved hand to prevent it from pulling out of the drain and pull the drain cleaner back so that no more than 12" (30cm) of cable is exposed. Repeat the above steps to continue advancing the cable in this manner. (See Figures 8-9.)



Figure 8 – Move Hand Grip Toward Drum To Grip Cable With Chuck



Figure 9 – Push Cable Down Drain Line

AUTOFEED Operation

Confirm that at least 12" (30cm) of cable is in the drain and that the cable outlet of the drain cleaner is no more than 6" (15cm) from the drain opening. Move the handgrip away from drum to disengage the chuck from the cable. Do not engage the chuck while using the AUTOFEED. Press the ON/OFF switch to start the machine. To advance the cable into the drain, depress the advance feed lever. The rotating cable will work its way into the drain. Do not allow the cable to build up outside the drain, bow or curve. This can allow the cable to twist, kink or break.



Figure 10 – Feeding Cable With AUTOFEED

If it is difficult to get the cable through a trap or other fitting, the following methods or combinations of methods can be used.

- First, sharp thrusts of the cable, both with and without the cable rotating, can help the cable through a trap.
- A second method is to run the drain cleaner in REV (REVERSE) rotation for several seconds while pushing on the cable. Only do this long enough to get the cable started through the trap. Running the cable in reverse can damage the cable.
- If these options don't work, consider using a smaller diameter or more flexible cable, or a different drain cleaner.

Cleaning The Drain

As you feed the cable into the drain, you may see the cable slow down or build up outside the drain. You may feel the cable start to wind or load up (the drain cleaner may want to twist or move sideways). This may be a transition in the drain (trap, elbow, etc.), build up in the drain (grease, etc.) or the actual blockage. Feed the cable slowly and carefully. Do not let cable build up

outside the drain. This can cause the cable to twist, kink or break.

Pay attention to the amount of cable that has been fed into the drain. Feeding cable into a larger drain or similar transition may cause the cable to kink or knot and prevent removal from the drain. Minimize the amount of cable fed into the transition to prevent problems.

The cables are not attached to the inner drum. Use care when feeding out the last 5 to 7 feet (1.5m to 2.13m) of the cable, to insure that it does not come out of the machine.

If using a cable with the "Speed Bump" feature (See Figure 11) this indicates that there is only about five more feet (1.5m) of usable cable.



Figure 11 – C-13-IC SB Cable With Cable End Indicator Speedbump Is Approx. 84" (2.1m) From Back End Of Cable

Working The Blockage

If the end of the cable stops turning, it is no longer cleaning the drain. If the end of the cable becomes lodged in the blockage and power is maintained to the drain cleaner, the cable will start to wind up (the drain cleaner or cable may want to twist, squirm or move sideways). If the cable end stops turning or if the cable starts to wind up, pull the cable back from the obstruction:

- **Manual Operation** – with the chuck gripping the cable, pull back on the drain cleaner to free the cable end from the blockage.
- **AUTOFEED Operation** – depress the retrieve feed lever to free the cable end from the blockage.

Don't keep the cable rotating if the cable is stuck in a blockage. If the cable end stops turning and the drum keeps rotating, the cable can twist kink or break.

Once the cable end is free of the blockage and turning again, you can slowly feed the cable end back into the blockage. Do not try to force the cable end through the blockage. Let the spinning end "dwell" in the blockage to completely break it up. Work the tool in this manner until you have moved completely past the blockage (or blockages) and the drain is flowing. If needed, the AUTOFEED feed levers do not need to be used, and the K-45 can be used manually. If using an AUTOFEED machine manually, pulling rearward on the handgrip will cause the chuck to grip the cable.

While working the blockage, the cable and tool may become clogged with debris and cuttings from the blockage. This can prevent further progress. The cable and tool need to be retrieved from the drain and the debris removed. *See section on "Retrieving the Cable".*

Handling A Stuck Tool/Cable End

If the cable end stops turning and cannot be pulled back from the blockage, release the ON/OFF switch while firmly holding the drain cleaner. The motor will stop and the cable and drum may turn backwards until energy stored in the cable is relieved. Do not pull the drain cleaner further than 12" (30cm) from the drain - the cable may twist, kink or break. Keep your finger off of the ON/OFF switch.

Freeing A Stuck Tool

If the cable end is stuck in the blockage, release the ON/OFF switch, pull the handgrip toward the drum to grip the cable and try pulling the cable loose from the blockage. Be careful not to damage the cable or tool while pulling on the cable. If the cable will not come free from the blockage, place the FOR/REV switch in the REV position, and with the handgrip toward the drum to grip the cable, press the ON/OFF switch for several seconds and pull on the cable until it is free of the blockage. Do not operate the machine in the REV position any longer than required to free the cable end from the blockage or cable damage can occur (with FOR/REV switch in REV position the AUTOFEED Advance feed lever will retrieve cable). Place the FOR/REV switch in the FOR position and continue cleaning the drain.

Retrieving The Cable

Once the drain is open, start a flow of water down the drain to flush the debris out of the line. This can be done by running a hose down the drain opening, turning on a faucet in the system or other methods. Pay attention to the water level, as the drain could plug again.

With water flowing through the drain, retrieve the cable from the line. The flow of water will help to clean the cable as it is retrieved. The FOR/REV switch should be in the FOR position – do not retrieve the cable with the switch in the REV position, this can damage the cable.

- **Manual Operation** – Pull the handgrip forward to release the chuck from the cable. With your gloved hand, grip the cable close to the drain opening and retrieve the cable back into the drum. This can be done either with the cable rotating or not. Rotating the cable while retrieving does a better job of cleaning the drain and makes retrieving the cable easier. Do not expose more than 12" (30cm) of cable.

The chuck can be used to better grip the cable during

retrieval. Move the handgrip towards the drum to grip the cable with the chuck. With the cable rotating (ON/OFF switch ON) move the drain cleaner away from the drain opening (but do not expose more than 12" (30cm) of cable). Release the ON/OFF switch. Move the handgrip away from the drum to release the chuck from the cable. Grip the cable with your gloved hand close to the drain opening (to prevent it from pushing back into the drain) and push the drain cleaner over the cable back into the drum. Repeat the above steps to continue retrieving the cable in this manner.

- **AUTOFEED Operation** – Confirm that the cable outlet of the drain cleaner is no more than 6" (15cm) from the drain opening. Pull the handgrip away from the drum to disengage the chuck from the cable. Do not engage the chuck while using the AUTOFEED. Press the ON/OFF switch to start the machine. To retrieve the cable, depress the retrieve feed lever. The rotating cable will work its way out of the drain.

Pay attention to the cable during retrieval as the cable end can still become stuck.

Release the ON/OFF switch before the cable end comes out of the drain. Do not pull the end of the cable from the drain while the cable is rotating. The cable can whip around and cause serious injury. Pull the remaining cable from the drain with gloved hands and feed back into the drain cleaner. If needed, change the tool and continue cleaning following the above process. Several passes through a line are recommended for complete cleaning.

With dry hands unplug the machine.

Maintenance Instructions

WARNING

FOR/OFF/REV switch should be OFF and machine unplugged before performing any maintenance.

Always wear safety glasses and RIDGID drain cleaning gloves and other appropriate protective equipment when performing any maintenance.

Cables

Cables should be thoroughly flushed with water after every use to prevent damaging effects of sediment and drain cleaning compounds. Flush cable with water and drain debris from drum by tipping machine forward after every use to remove sediment, etc. which can corrode cable.

To help prevent corrosion during storage, cables can be coated with RIDGID Cable Rust Inhibitor. Once the cable is clean and dry, pull the cable from the drum. While manually feeding the cable back into the drum, wipe the Cable Rust Inhibitor on the cable with a cloth.

Do not apply the Cable Rust Inhibitor to a rotating cable. The cloth and your hand can become entangled in the cable, and Cable Rust Inhibitor can be slung from rotating cable.