⚠ WARNING
⚠ AVISO

Children can fall into bucket and drown.
Keep children away from bucket with even a small amount of liquid.

Los niños corren peligro de caerse dentro del balde y ahogarse.
Mantener a los niños lejos de los baldes, incluso cuando sólo tengan una pequeña cantidad de líquido.

ROKREZ GARAGE FLOOR COATING PROVIDES A VIRTUALLY INDESTRUCTIBLE, CHEMICAL & STAIN RESISTANT, HIGH GLOSS FINISH FOR THE ULTIMATE IN CONCRETE FLOORING PROTECTION.

ROKREZ CONCRETE BONDING TECHNOLOGY INCREASES THE STRENGTH OF EXISTING CONCRETE AND PROVIDES MAXIMUM HARDNESS AND ADHESION. THE EASY-TO-USE PROFESSIONAL-GRADE FORMULA IS 20X STRONGER THAN OTHER DIY FLOOR COATINGS AND OFFERS UNMATCHED DURABILITY.

THE CONVENIENT ALL-IN-ONE ROKREZ KIT IS DESIGNED READY-TO-USE ON ANY CLEAN INTERIOR CONCRETE SURFACE. THE LOW ODOR, SELF-LEVELING FORMULA DELIVERS A SPECTACULAR FINISH THAT WILL LAST FOR YEARS.

VISIT ROKREZ.COM FOR INSTRUCTIONAL VIDEOS, FAQS, AND TIPS

QUESTIONS? 866.515.8775

CAUTIONS: CONTAINS AMINE. USE ONLY WITH ADEQUATE VENTILATION. TO AVOID OVEREXPOSURE, OPEN WINDOWS AND DOORS OR USE OTHER MEANS TO ENSURE FRESH AIR ENTRY DURING APPLICATION AND DRYING. IF YOU EXPERIENCE EYE WATERING, HEADACHES, OR DIZZINESS, INCREASE FRESH AIR, OR WEAR RESPIRATORY PROTECTION (NIOSH APPROVED) OR LEAVE THE AREA. AVOID CONTACT WITH EYES AND SKIN. USE PROTECTIVE GLOVES WHEN USING. WASH HANDS AFTER USE.

READ AND FOLLOW WARNING LABELS ON ALL COMPONENTS. DO NOT TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN.
SEE MATERIAL SAFETY DATA SHEET WITHIN SIMIRON.COM.

FOR EMERGENCY INFORMATION, CALL INFOTRAC 1-800-535-5053

⚠ WARNING: CANCER AND REPRODUCTIVE HARM - WWW.P65WARNING.CA.GOV

FIRST AID: EYE CONTACT: HOLD EYELIDS APART AND FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION. SKIN CONTACT: WASH WITH SOAP AND WATER. GET MEDICAL ATTENTION IF IRRITATION DEVELOPS OR PERSISTS. INHALATION: IF YOU EXPERIENCE DIFFICULTY IN BREATHING, LEAVE THE AREA TO OBTAIN FRESH AIR. IF CONTINUED DIFFICULTY IS EXPERIENCED, GET MEDICAL ASSISTANCE IMMEDIATELY. INGESTION: IF SWALLOWED, DO NOT INDUCE VOMITING. CALL A PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

SIMIRON, INC. WARRANTS THIS PRODUCT TO BE FREE FROM DEFECT IN THE MATERIAL THAT AFFECTS ITS PERFORMANCE FOR A PERIOD OF ONE YEAR (FROM DATE OF PURCHASE). SIMIRON WILL REPLACE AT NO CHARGE THE QUANTITY OF THE COATING THAT SIMIRON DETERMINES HAS FAILED TO PERFORM. AS THE SOLE AND EXCLUSIVE REMEDY FOR ANY BREACH OF THIS WARRANTY AND/OR ANY OTHER DEFECT OR FAILURE OF THE COATING. PROOF OF PURCHASE IS REQUIRED. COST OF LABOR FOR APPLICATION OF ANY PRODUCT SPECIFICALLY IS EXCLUDED. GO TO SIMIRON.COM FOR ADDITIONAL ROKREZ TERMS & CONDITIONS.

SIMIRON
32700 Industrial Drive,
Madison Heights, MI 48071
866.515.8775 SIMIRON.COM

made in THE USA

40004262 TAN
7 34840 00426 2

ROKREZ

THE ULTIMATE GARAGE FLOOR COATING KIT

COMPLETE ALL-IN-ONE KIT

PACKAGE INCLUDES

- ROKREZ ACTIVATOR (0.3 GAL)
- ROKREZ BASE (0.6 GAL)
- DECORATIVE CHIP
- SLIP RESISTANT ADDITIVE
- CONCENTRATED CLEANER
- PADDLE MIXER
- 9" ROLLER COVER
- APPLICATION INSTRUCTIONS

OTHER SUPPLIES NEEDED

- STIFF BRISTLE BROOM OR SCRUB BRUSH
- ROLLER (9.5") FRAME & TRAY
- EXTENSION POLE
- PROTECTIVE GLOVES
- HEAVY-DUTY DEGREASER (OPTIONAL)
- ROKREZ CONCRETE PATCH & REPAIR (OPTIONAL)
- PAINTERS TAPE
- DRILL

PROJECT DETAILS AT A GLANCE

BEST FOR	GARAGES, BASEMENTS, WORKSHOPS, LAUNDRY ROOMS, AND MORE
KIT COVERAGE	400 — 500 SQ. FT.
GARAGE SIZE	2 ½ CAR
WALK-ON READY	18 — 24 HOURS
DRIVE READY	3 DAYS
COATS NEEDED	1 COAT
TOOL CLEAN-UP	ACETONE, XYLENE, OR DENATURED ALCOHOL
APPLY WHEN WEATHER IS	60° F – 85° F | 80% HUMIDITY | 5° DEW POINT

⚠ WARNING
VAPOR HARMFUL

192 FL.OZ.
(1.5 US GAL)

2½ CAR GARAGE
COVERS 400-500 SQ. FT.

EASY 3-STEP APPLICATION PROCESS

1 – PREPARE SURFACE.

2 – MIX IN KIT BUCKET.

3 – APPLY COATING.

403210 07/18