

SAFETY DATA SHEET

Issuing Date 06-Oct-2011

Revision Date 23-Jan-2015

Revision Number 0



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publicly available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name LR6 ALKALINE AA AM3

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Alkaline battery

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Name ZHEJIANG MUSTANG BATTERY CO., LTD.
Supplier Address NO.818 RONGJI ROAD, ZHENHAI
NINGBO
ZHEJIANG
315202
CN
Supplier Phone Number Phone:0086 13586700016
Fax:0086 574 86593227
Contact Phone0086 574 86653999
Supplier Email trade-6@mustangbattery.com

Emergency telephone number

Company Emergency Phone Number 0086 13586700016

2. HAZARDS IDENTIFICATION

Classification

This product is an article which is a sealed battery and as such does not require an MSDS per the OSHA hazard communication standard unless ruptured. The hazards indicated are for a ruptured battery.


Acute toxicity - Oral	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 4



Skin corrosion/irritation	Category 1 Sub-category A
Serious eye damage/eye irritation	Category 1
Specific target organ toxicity (repeated exposure)	Category 2

GHS Label elements, including precautionary statements

Emergency Overview

Signal word	Danger		
Hazard Statements			
Harmful if swallowed			
Harmful if inhaled			
Causes severe skin burns and eye damage			
May cause damage to organs through prolonged or repeated exposure			
			
Appearance	Silver	Physical State	Solid Solid/Powder
		Odor	No information available

Precautionary Statements - Prevention

- Wash face, hands and any exposed skin thoroughly after handling
- Do not eat, drink or smoke when using this product
- Use only outdoors or in a well-ventilated area
- Do not breathe dust/fume/gas/mist/vapors/spray
- Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response

- Immediately call a POISON CENTER or doctor/physician
- Specific treatment (see supplemental first aid instructions on this label)

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 Immediately call a POISON CENTER or doctor/physician

Skin

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
 Wash contaminated clothing before reuse

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 Immediately call a POISON CENTER or doctor/physician

Ingestion

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell
 Rinse mouth
 Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up



Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

23% of the mixture consists of ingredient(s) of unknown toxicity

Other information

Very toxic to aquatic life with long lasting effects

Interactions with Other Chemicals

No information available.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%	Trade Secret
Manganese dioxide	1313-13-9	30 - 60	*
Zinc	7440-66-6	10 - 30	*
Potassium hydroxide	1310-58-3	3 - 7	*
Graphite	7782-42-5	1 - 5	*

*The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

First aid measures**General Advice**

First aid is upon rupture of sealed battery. Immediate medical attention is required. Show this safety data sheet to the doctor in attendance.

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Seek immediate medical attention/advice.

Skin Contact

Immediate medical attention is required. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.

Inhalation

Remove to fresh air. Get medical attention immediately if symptoms occur. If breathing is difficult, (trained personnel should) give oxygen. If not breathing, give artificial respiration. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Delayed pulmonary edema may occur.

Ingestion

Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.



Self-protection of the first aider Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid contact with skin, eyes or clothing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required. Wear personal protective clothing (see section 8). Do not breathe dust.

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and Effects Burning sensation. Coughing and/ or wheezing. Difficulty in breathing.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood pressure may occur with moist rales, frothy sputum, and high pulse pressure.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

CAUTION: Use of water spray when fighting fire may be inefficient.

Specific Hazards Arising from the Chemical

The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of irritating gases and vapors.

Hazardous Combustion Products

Carbon oxides.

Explosion Data

Sensitivity to Mechanical Impact No.

Sensitivity to Static Discharge No.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions In case of rupture: Attention! Corrosive material. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Avoid generation of dust. Do not breathe dust.

Other Information Refer to protective measures listed in Sections 7 and 8.

Environmental Precautions

Environmental Precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Should not be released into the environment. Do not allow to enter into soil/subsoil. Prevent product from entering drains.

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling In case of rupture: Handle in accordance with good industrial hygiene and safety practice. Use only with adequate ventilation and in closed systems. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Do not breathe dust. Avoid generation of dust.

Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from moisture. Store locked up. Keep out of the reach of children. Store away from other materials.

Incompatible Products Acids. Bases. Oxidizing agent.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
---------------	-----------	----------	------------



Manganese dioxide 1313-13-9	TWA: 0.02 mg/m ³ Mn TWA: 0.1 mg/m ³ Mn	(vacated) Ceiling: 5 mg/m ³ Ceiling: 5 mg/m ³ Mn	IDLH: 500 mg/m ³ Mn TWA: 1 mg/m ³ Mn STEL: 3 mg/m ³ Mn
Zinc 7440-66-6	STEL: 10 mg/m ³ respirable fraction TWA: 2 mg/m ³ respirable fraction	TWA: 5 mg/m ³ fume TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction	IDLH: 500 mg/m ³ Ceiling: 15 mg/m ³ dust TWA: 5 mg/m ³ dust and fume STEL: 10 mg/m ³ fume
Potassium hydroxide 1310-58-3	Ceiling: 2 mg/m ³	(vacated) Ceiling: 2 mg/m ³	Ceiling: 2 mg/m ³
Graphite 7782-42-5	TWA: 2 mg/m ³ respirable fraction all forms except graphite fibers	TWA: 15 mg/m ³ total dust synthetic TWA: 5 mg/m ³ respirable fraction synthetic (vacated) TWA: 2.5 mg/m ³ respirable dust natural (vacated) TWA: 10 mg/m ³ total dust synthetic (vacated) TWA: 5 mg/m ³ respirable fraction synthetic TWA: 15 mppcf natural	IDLH: 1250 mg/m ³ TWA: 2.5 mg/m ³ respirable dust

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits NIOSH IDLH Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters

Appropriate engineering controls

Engineering Measures Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection None required for consumer use. If there is a risk of contact: Tight sealing safety goggles.

Skin and Body Protection None required for consumer use. If there is a risk of contact: Impervious gloves. Impervious clothing.

Respiratory Protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. For environmental protection, remove and wash all contaminated protective equipment before re-use. Do not breathe dust.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical State	Solid, Solid/Powder	Odor	No information available
Appearance	Silver	Odor Threshold	No information available
Color	No information available		



<u>Property</u>	<u>Values</u>	<u>Remarks</u>	<u>Method</u>
pH	No data available	None known	
Melting / freezing point	No data available	None known	
Boiling point / boiling range	No data available	None known	
Flash Point	No data available	None known	
Evaporation Rate	No data available	None known	
Flammability (solid, gas)	No data available	None known	
Flammability Limit in Air			
Upper flammability limit	No data available		
Lower flammability limit	No data available		
Vapor pressure	No data available	None known	
Vapor density	No data available	None known	
Specific Gravity	No data available	None known	
Water Solubility	Partially soluble	None known	
Solubility in other solvents	No data available	None known	
Partition coefficient: n-octanol/water	No data available	None known	
Autoignition temperature	No data available	None known	
Decomposition temperature	No data available	None known	
Kinematic viscosity	No data available	None known	
Dynamic viscosity	No data available	None known	
Explosive properties	No data available		
Oxidizing Properties	No data available		

Other Information

Softening Point	No data available
VOC Content (%)	No data available
Particle Size	No data available
Particle Size Distribution	

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Exposure to air or moisture over prolonged periods. Excessive heat.

Incompatible materials

Acids. Bases. Oxidizing agent.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure**Product Information**

In case of rupture:.

Inhalation

Specific test data for the substance or mixture is not available. Corrosive by inhalation. (based on components). Inhalation of corrosive fumes/gases may cause coughing, choking, headache, dizziness, and weakness for several hours. Pulmonary edema may occur with tightness in the chest, shortness of breath, bluish skin, decreased blood pressure, and increased heart rate. Inhaled corrosive substances can lead to a toxic edema of the lungs. Pulmonary edema can be fatal. May cause irritation of respiratory tract. Harmful by inhalation.

Eye Contact

Specific test data for the substance or mixture is not available. Causes burns. (based on components). Corrosive to the eyes and may cause severe damage including blindness. Causes serious eye damage. May cause irreversible damage to eyes.

Skin Contact

Specific test data for the substance or mixture is not available. Corrosive. (based on components). Causes burns.

Ingestion

Specific test data for the substance or mixture is not available. Causes burns. (based on components). Ingestion causes burns of the upper digestive and respiratory tracts. May cause severe burning pain in the mouth and stomach with vomiting and diarrhea of dark blood. Blood pressure may decrease. Brownish or yellowish stains may be seen around the mouth. Swelling of the throat may cause shortness of breath and choking. May cause lung damage if swallowed. May be fatal if swallowed and enters airways. May be harmful if swallowed.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Manganese dioxide 1313-13-9	= 9000 mg/kg (Rat)	-	-
Potassium hydroxide 1310-58-3	= 214 mg/kg (Rat)	-	-
Graphite 7782-42-5	> 10000 mg/kg (Rat)	-	-

Information on toxicological effects**Symptoms**

Erythema (skin redness). Burning. May cause blindness. Coughing and/ or wheezing.

Delayed and immediate effects as well as chronic effects from short and long-term exposure**Sensitization**

No information available.

Mutagenic Effects

No information available.

Carcinogenicity

Contains no ingredient listed as a carcinogen.

Reproductive Toxicity

No information available.

STOT - single exposure

No information available.

STOT - repeated exposure

Causes damage to organs through prolonged or repeated exposure. Based on classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from chronic or repeated exposure. (STOT RE).

Chronic Toxicity

Chronic exposure to corrosive fumes/gases may cause erosion of the teeth followed by jaw necrosis. Bronchial irritation with chronic cough and frequent attacks of pneumonia are common. Gastrointestinal disturbances may also be seen. Avoid repeated exposure. Prolonged exposure may cause chronic effects. May cause adverse effects on the bone marrow and blood-forming system. May cause adverse liver effects.

Target Organ Effects

Respiratory system. Eyes. Skin. Gastrointestinal tract (GI). Blood. Central Nervous System (CNS). Central Vascular System (CVS). Kidney. Liver. Cardiovascular system.

Aspiration Hazard

No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)

837.00 mg/kg

ATEmix (inhalation-dust/mist)

2.89 mg/l

ATEmix (inhalation-vapor)

21.18 ATEmix

12. ECOLOGICAL INFORMATION

Ecotoxicity

Very toxic to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Zinc 7440-66-6	96h EC50: 0.11 - 0.271 mg/L (Pseudokirchneriella subcapitata) 72h EC50: 0.09 - 0.125 mg/L (Pseudokirchneriella subcapitata)	96h LC50: 2.16 - 3.05 mg/L (Pimephales promelas) 96h LC50: 0.211 - 0.269 mg/L (Pimephales promelas) 96h LC50: = 2.66 mg/L (Pimephales promelas) 96h LC50: = 30 mg/L (Cyprinus carpio) 96h LC50: = 0.45 mg/L (Cyprinus carpio) 96h LC50: = 7.8 mg/L (Cyprinus carpio) 96h LC50: = 3.5 mg/L (Lepomis macrochirus) 96h LC50: = 0.24 mg/L (Oncorhynchus mykiss) 96h LC50: = 0.59 mg/L (Oncorhynchus mykiss) 96h LC50: = 0.41 mg/L (Oncorhynchus mykiss)		48h EC50: 0.139 - 0.908 mg/L
Potassium hydroxide 1310-58-3		96h LC50: = 80 mg/L (Gambusia affinis)		

Persistence and Degradability

No information available.

Bioaccumulation

No information available

Chemical Name	Log Pow
Manganese dioxide 1313-13-9	<0
Potassium hydroxide 1310-58-3	0.83

Other adverse effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

Contaminated Packaging Dispose of contents/containers in accordance with local regulations.

California Hazardous Waste Codes 181

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Zinc 7440-66-6	Ignitable powder Toxic
Potassium hydroxide 1310-58-3	Toxic Corrosive

14. TRANSPORT INFORMATION

DOT
 Proper Shipping Name NOT REGULATED
 Hazard Class NON REGULATED
 N/A

TDG Not regulated

MEX Not regulated

ICAO Not regulated

IATA
 Proper Shipping Name NOT REGULATED
 Hazard Class N/A

IMDG/IMO
 Hazard Class Not regulated
 N/A

RID Not regulated

ADR Not regulated

ADN Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA Complies



DSL All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Manganese dioxide - 1313-13-9	1313-13-9	30 - 60	1.0
Zinc - 7440-66-6	7440-66-6	10 - 30	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	No
Chronic Health Hazard	No
Fire Hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Zinc 7440-66-6		X	X	
Potassium hydroxide 1310-58-3	1000 lb			X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Zinc 7440-66-6	1000 lb		RQ 454 kg final RQ RQ 1000 lb final RQ
Potassium hydroxide 1310-58-3	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Manganese dioxide 1313-13-9			X	X	X
Zinc 7440-66-6	X	X	X	X	
Potassium hydroxide 1310-58-3	X	X	X	X	



Graphite 7782-42-5	X	X	X		
-----------------------	---	---	---	--	--

International Regulations

Mexico

National occupational exposure limits

Component	Carcinogen Status	Exposure Limits
Manganese dioxide 1313-13-9 (30 - 60)		Mexico: TWA= 0.2 mg/m ³
Graphite 7782-42-5 (1 - 5)		Mexico: TWA= 2 mg/m ³

Mexico - Occupational Exposure Limits - Carcinogens

Canada

WHMIS Hazard Class

Non-controlled

16. OTHER INFORMATION

NFPA	Health Hazards 0	Flammability 0	Instability 0	Physical and Chemical Hazards -
HMIS	Health Hazards 0	Flammability 0	Physical Hazard 0	Personal Protection X

Prepared By Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-6501

Issuing Date 06-Oct-2011

Revision Date 23-Jan-2015

Revision Note No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet





PASSION. PARTNERSHIP. POSSIBILITIES.

SAFETY DATA SHEET

SECTION 1: PRODUCT IDENTIFICATION

Product: Sting Relief Pad

Product Label Name: Sting Relief Pad

Company Name and Address: Dukal Corporation
2 Fleetwood Court
Ronkonkoma, NY 11779

Emergency Telephone Number: 631-656-3800

SECTION 2: HAZARDOUS IDENTIFICATION

Hazard Class/Category: Flammable Liquid – 3
Eye Irritation – 2A
STOT (Single Exposure) - 3

Hazard Symbol:



Signal Word:

Warning

Hazard Statements:

Flammable liquid and vapor. (H226)
Causes serious eye irritation. (H319)
May cause drowsiness or dizziness. (H336)

Precautionary statements:

General:

Keep out of reach of children. (P102)

Eyes:

IF IN EYES: Rinse cautiously with water for several minutes.
If eye irritation persists: Get medical advice/attention.
(P305+P338) (P337+P313)

Respiratory:

Avoid breathing fumes/mist/vapors. (P261)

SECTION 3: INFORMATION ON INGREDIENTS

Component Name	CAS #	Concentration	R Phrase
Isopropyl Alcohol	67-63-0	60%	R11
Benzocaine	94-09-7	6%	

Chemical Formula:

NH₂C₆H₄COOC₂H₅ / CH₃CHOHCH₃

OSHA Standard Format



SAFETY DATA SHEET

SECTION 4: FIRST-AID MEASURES

Emergency first aid procedures by route of exposure:

Inhalation: If symptoms are experienced, remove source of contamination or move victim to fresh air. If affected person is not breathing, apply artificial respiration. If breathing is difficult, give oxygen. Seek medical attention.

Ingestion: Do not induce vomiting. If the material is swallowed have victim drink 1-3 glasses of water to dilute stomach contents. Seek medical attention or advice.

Skin: If irritation is experienced, discontinue use. If irritation persists, seek medical attention.

Eyes: Rinse eyes with cool water for 15 minutes holding the eye open. Seek medical attention if irritation persists

SECTION 5: FIRE-FIGHTING MEASURES

Flash Point: 68.5°F, TOC Method

Flammable Limits: 750°F

Extinguishing Media: Use methods appropriate for the surrounding fire. Suggested: CO₂, dry chemical powder, or alcohol resistant foam.

Products of Combustion: Upon decomposition this product may emit carbon dioxide, carbon monoxide and/or low molecular weight hydrocarbons.

Fire Fighting Equipment/Instructions: Wear protective clothing and equipment suitable for the surrounding fire, including helmet, facemask, and self contained breathing apparatus.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: For large spills wear gloves, safety glasses and when levels exceed OSHA PEL use appropriate NIOSH approved respiratory protection. Keep unnecessary personnel away. Eliminate all sources of ignition or flammables that may come into contact with a spill of this material.

Environmental Precautions: Prevent discharge to open waters.

Method for Containment: Absorb spilled liquid in suitable non-flammable inert material such as clay, vermiculite or diatomaceous earth.

Methods for Clean-Up: Ventilate area of leak or spill. Use spark-proof tools to sweep or scrape up and containerize in approved chemical waste container. Wash spill area with water.



SAFETY DATA SHEET

SECTION 7: HANDLING AND STORAGE

Handling: Keep away from heat, sparks and flame. Prevent contact with eyes. Use in well ventilated area.

Storage: Keep the container tightly closed and in a cool, well ventilated place.

SECTION 8: EXPOSURE CONTROLS

Isopropyl Alcohol (67-63-0)

ACGIH OEL: 200 ppm TWA

OSHA OEL: 400 ppm TWA; 980 mg/m³ TWA

Engineering Controls: Normal room ventilation is usually adequate under normal use.

Personal Protective Equipment (PPE):

Eye/Face Protection: None needed under normal use – Wear goggles if exposed to unusual amount and splashing

Skin Protection: None needed under normal use -- Wear overalls or apron if splashing is possible

Respiratory Protection: May be needed if vapor concentrations are high.

General Hygiene Considerations: None needed under normal use.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Individually sealed Sting Relief Packet. No free liquid inside packaging.

Appearance/Color: White Non-Woven cloth saturated with clear solution

Odor: Alcohol

PH: Not Available.

Vapor Pressure: Not Available.

Flammability Properties (see section 5)

Solubility (in water): Chemical Is Soluble, Pad Not Soluble

Specific Gravity @ 25°C: 0.8405

Evaporation Rate: Not Available

Auto-ignition temperature: Not Available

Decomposition temperature: Not Available



PASSION. PARTNERSHIP. POSSIBILITIES.

SAFETY DATA SHEET

SECTION 10: STABILITY AND REACTIVITY

Stability: Stable under normal ambient temperatures 70°C (21°C)

Condition to Avoid: Avoid excessive heat or sources of ignition.

Incompatible Materials: This product reacts with strong acid, strong bases, and oxidizing agents.

Hazardous Decomposition: Not Available.

Hazardous Reactions: Hazardous polymerization will not occur.

SECTION 11: TOXICOLOGICAL INFORMATION

ACUTE EFFECTS:

A: General Product information

Product contains isopropyl alcohol.

B: Acute Toxicity

Low order of acute toxicity is possible.

CHRONIC EFFECTS: Component

Isopropyl Alcohol (67-63-0) -- This product is not expected to cause long term adverse effects

Carcinogenicity: Not Classifiable as a Human Carcinogen

Reproductive: This product is not expected to cause reproductive health effects

Developmental: This product is not expected to cause reproductive health effects.

Target Organs: When consumed, isopropyl alcohol can target the respiratory system, skin, eyes, CNS, liver, blood and reproductive system.

SECTION 12: ECOLOGICAL INFORMATION

Mixtures of alcohols are toxic to aquatic life at moderate to low concentrations. No long-term ecological effects are likely. Concentrated solutions of alcohols and surfactants may cause damage to aquatic and terrestrial plants.

SECTION 13: DISPOSAL CONSIDERATIONS

Dispose in accordance with federal state and local regulations. Labels should not be removed from containers until they have been cleaned. Do not cut, puncture or weld near container. Do not incinerate closed containers. Empty containers may contain hazardous residues. Dispose of containers with care.

SECTION 14: TRANSPORTATION INFORMATION

DOT	Not Regulated as Hazardous Material under DOT 49 CFR 172.102 Special Provision 47
Proper Shipping Name	Solids containing Flammable Liquid. n.o.s. (Isopropanol)
Hazard Class	4.1
Packing Group	II
Description	Solids Containing Flammable Liquid n.o.s. (Isopropanol)
UN#	UN3175



PASSION. PARTNERSHIP. POSSIBILITIES.

SAFETY DATA SHEET

UN-No.	UN3175
Proper Shipping Name	Solids Containing Flammable Liquid n.o.s. (Isopropanol)
Hazard Class	4.1
Packing Group	II
Description	Solids Containing Flammable Liquid n.o.s. (Isopropanol)

IATA Not Regulated as Hazardous Material under IATA Sec. 4.4 Special Provision A46

UN-No.	UN3175
Proper Shipping Name	Solids Containing Flammable Liquid n.o.s. (Isopropanol)
Hazard Class	4.1
Packing Group	II
Description	Solids Containing Flammable Liquid n.o.s. (Isopropanol)
Marine Pollutant	No

IMDG/IMO Not Regulated as Hazardous Material under IMDG Ch. 3.3 Special Provision 216

UN-No.	UN3175
Proper Shipping Name	Solids Containing Flammable Liquid n.o.s. (Isopropanol)
Hazard Class	4.1
Packing Group	II
Description	Solids Containing Flammable Liquid n.o.s. (Isopropanol)
Marine Pollutant	No

Special Provisions Verbiage: (DOT) Mixtures of solids that are not subject to this subchapter and flammable liquids may be transported under this entry without first applying the classification criteria of Division 4.1, provided there is no free liquid visible at the time the material is loaded or at the time the packaging or transport unit is closed. Except when the liquids are fully absorbed in solid material contained in sealed bags, for single packagings, each packaging must correspond to a design type that has passed a leakproofness test at the Packing Group II level. Small inner packagings consisting of sealed packets and articles containing less than 10 mL of a Class 3 liquid in Packing Group II or III absorbed onto a solid material are not subject to this subchapter provided there is no free liquid in the packet or article. (UN: ARD/RID/ADN) SP216: Mixtures of solids which are not subjects to these Regulations and flammable liquids may be transported under this entry without first applying the classification criteria of Division 4.1, provided there is no free liquid visible at the time the substance is loaded or at the time the packaging or cargo transport unit is closed. Each cargo transport unit shall be leakproof when used as a bulk packaging. Sealed packets and articles containing less than 10 ml of a packing group II or III flammable liquid absorbed into a solid are not subject to these Regulations provided there is no free liquid in the packet or article. SP313: Sealed packets and articles containing less than 10 ml of an environmentally hazardous liquid, absorbed into a solid material but with no free liquid in the packet or article, or containing less than 10 g of an environmentally hazardous solid, are not subject to these Regulations. (IATA) Small inner packagings consisting of sealed packets or articles containing less than 10 mL of a Packing Group II or III flammable liquid absorbed into a solid material are not subject to these Regulations



PASSION. PARTNERSHIP. POSSIBILITIES.

SAFETY DATA SHEET

provided there is no free liquid in the packet or article (IACAO) Mixtures of solids which are not subject to these Instructions and flammable liquids may be transported under this entry without first applying the classification criteria of Division 4.1, providing there is no free liquid visible at the time the substance is packaged and the packaging must pass a leakproofness test at the Packing Group II level. Small inner packagings consisting of sealed packets or articles containing less than 10 mL of a Packing Group II or III flammable liquid absorbed into a solid material are not subject to these Instructions provided there is no free liquid in the packet or articles. (IMDG) Sealed packets containing 10 ml or less of Class 3 flammable liquids in Packing Group II or III which are absorbed into a solid with no free liquid at the time of shipment are not regulated.

SECTION 15: REGULATORY INFORMATION

DOT / USA

Product Description: Solid Containing Flammable Liquid n.o.s. (Isopropanol)

SECTION 16: OTHER INFORMATION

Issue Date: 03-26-2014

Revision Date: 08-19-2019

Disclaimer:

The information provided in this SDS is correct and is to the best of our knowledge, at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.



SAFETY DATA SHEET

SECTION 1: PRODUCT IDENTIFICATION

PRODUCT: BZK Prep Pads and Towelette

Product Label Name: BZK Prep Pads and Towelette

Company Name and Address: Dukal Corporation
2 Fleetwood Court
Ronkonkoma, NY 11779

Emergency Telephone Number: 631-656-3800

Recommended use: First Aid Antiseptic.

SECTION 2: HAZARDOUS IDENTIFICATION

Hazard Class/Category: Eye Irritant – 2B
Skin Irritant – 3

Hazard Symbol: No Symbol

Signal Word: Warning

Hazard Statements: Causes eye irritation (H320)
Causes mild skin irritation (H316)

Precautionary statements:

Eyes: IF IN EYES: Rinse cautiously with water for several minutes. If eye irritation persists: Get medical advice/attention. (P305+P351) (P337+P313)

Skin: If skin irritation occurs: Wash with plenty of soap and water. (P332+P352)

SECTION 3: INFORMATION ON INGREDIENTS

Ingredient list	Cas #	%
Benzalkonium Chloride	8001-54-5	0.50%
Sodium bicarbonate	144-55-8	0.05%
Purified Water	7732-18-5	QS to 100

SECTION 4: FIRST-AID MEASURES

First aid procedures

Inhalation:	Not a normal route of exposure. May cause respiratory tract irritation.
Ingestion	Not a normal route of exposure. May cause stomach distress, nausea or vomiting.
Target organs:	Eyes. Skin.
Chronic effects	Prolonged or repeated exposure can cause drying, defatting and dermatitis.
Signs and symptoms	Symptoms may include redness, edema, drying, defatting and cracking of the skin.
Overexposure:	Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Eye contact:	Rinse cautiously with water for several minutes. If eye irritation persists: Get medical advice/attention.
Skin contact:	In case of skin irritation, wash with plenty of soap and water. Discontinue use of product.
Inhalation:	Not a normal route of exposure. If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention.
Ingestion:	Not a normal route of exposure. Do not induce vomiting. Never give anything by mouth if victim is unconscious, or is convulsing. Obtain medical attention.
Note to Physician:	Symptoms may be delayed.
General Advice:	If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Keep out of reach of children. Avoid contact with eyes.

SECTION 5: FIRE-FIGHTING MEASURES

Flammable properties	Not flammable by OSHA criteria
Suitable extinguishing media	Treat for surrounding material.
Specific hazards arising from the chemical:	Not available
Protective equipment for firefighters	Firefighters should wear full protective clothing including self-contained breathing apparatus.
Hazardous combustion products	May include and are not limited to: Oxides of carbon. Hydrogen chloride.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions	Keep unnecessary personnel away. Do not touch or walk through spilled material. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep people away from and upwind of spill/leak.
Methods for containment	Prevent entry into waterways, sewers, basements or confined areas.
Methods for cleaning up	Pick up and discard towel.

SECTION 7: HANDLING AND STORAGE

Handling	Use good industrial hygiene practices in handling this material.
Storage	Keep out of reach of children. Store in a closed container away from incompatible materials.

SECTION 8: EXPOSURE CONTROLS

Engineering controls	General ventilation normally adequate.
Personal protective equipment	
Eye / face protection	Follow standard industrial hygiene practices.



PASSION. PARTNERSHIP. POSSIBILITIES.

SAFETY DATA SHEET

Hand protection	Not required.
Skin and body protection	As required by employer code.
Respiratory protection	Where exposure guideline levels may be exceeded, use an approved NIOSH respirator.
General hygiene considerations	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Liquid saturated on wipe
Color	Clear liquid
Form	Liquid saturated on wipe.
Odor	Characteristic
Odor threshold	Not available
Physical state	Solid
pH	Not available
Melting point	Not available
Freezing point	Not available
Boiling point	101.11 °C (214 °F)
Flash point	Not available
Evaporation rate	Not available
Flammability limits in air, lower	Not available
Flammability limits in air, upper	Not applicable
Vapor pressure	Not available
Vapor density	Not available
Specific gravity	Not available
Octanol/water coefficient	Not available
Solubility (H₂O)	Not available
Auto-ignition temperature	Not available
VOC (Weight %)	Not available
Viscosity	Not available
Percent volatile	Not available

SECTION 10: STABILITY AND REACTIVITY

Chemical stability	Stable under recommended storage conditions.
Conditions to avoid	Do not mix with other chemicals.
Incompatible materials	Caustics. Acids. Oxidizers.
Hazardous decomposition products	May include and are not limited to: Oxides of carbon. Hydrogen chloride.

OSHA Standard Format



PASSION. PARTNERSHIP. POSSIBILITIES.

SAFETY DATA SHEET

Possibility of hazardous reactions Hazardous polymerization does not occur.

SECTION 11: TOXICOLOGICAL INFORMATION

Effects of acute exposure

Eye	May cause irritation.
Skin	In case of skin irritation, discontinue use of the product.
Inhalation	Not a normal route of exposure. May cause respiratory tract irritation.
Ingestion	Not a normal route of exposure. May cause stomach distress, nausea or vomiting.
Sensitization	Non-hazardous by WHMIS/OSHA criteria.
Chronic effects	Non-hazardous by WHMIS/OSHA criteria.
Carcinogenicity	Non-hazardous by WHMIS/OSHA criteria.
Mutagenicity	Non-hazardous by WHMIS/OSHA criteria.
Reproductive effects	Non-hazardous by WHMIS/OSHA criteria.
Teratogenicity	Non-hazardous by WHMIS/OSHA criteria.

SECTION 12: ECOLOGICAL INFORMATION

None available

SECTION 13: DISPOSABLE INFORMATION

Waste codes	Not available
Disposal instructions	Discard after single use. Review federal, state/provincial, and local government requirements prior to disposal. Discard with solid waste. Dispose in accordance with all applicable regulations.
Waste from residues / unused	Not available
Contaminated packaging	Not available

SECTION 14: TRANSPORTATION INFORMATION

U.S. Department of Transportation	Not regulated as dangerous goods.
Transportation of Dangerous Goods	Not regulated as dangerous goods.

SECTION 15: REGULATORY INFORMATION

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous No chemical



PASSION. PARTNERSHIP. POSSIBILITIES.

SAFETY DATA SHEET

SECTION 16: OTHER INFORMATION

Issue Date: 06-18-2014
Revision Date: 06-13-2016

Disclaimer:

The information provided in this SDS is correct and is to the best of our knowledge, at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.