

# allure **CONTRACT**

## INSTALLATION

### SPECIFICATIONS:

HD Installable	Yes
Connection Type	Adhesive GripStrip
Free Floating Floor	Yes. DO NOT screw or nail moldings, transitions, cabinetry or vents through ANY <b>allure</b> flooring
Acclimation Period	48 hours minimum required in room prior to installation
Temperature Range During Acclimation & Install	65°F to 85°F required in room of installation After installation temps should stay between 55F to 85F
Interior Product Only	Yes. See limitations/exclusions below
Storage	Horizontally
Dye Lots	Yes. Install from a minimum of 3 to 4 different boxes and dye lots at one time. See page 3 of Owner's Manual for more information
Expansion Space	Yes. For room perimeters and fixed objects please leave 1/8" minimum space, 1/4" optimum space
Floor Flatness Tolerances	1/4" over 10', Use floor leveler when exceeding tolerance
Hand Roller Required	Yes
75 lb min. Floor Roller	Yes
Moisture Reading Guidelines; OVER CONCRETE Scale 0 to 5% Scale 5% to 6%	Based on Tramex Concrete Moisture Encounter Plus Meter (scale 0 to 6%) 6 mil poly barrier necessary 6 mil poly barrier necessary; over 6% recommend Dricore
Moisture Reading Guidelines; OVER WOOD Scale 0 to 13%	Never use 6 mil poly over wooden subfloors OK to install. Do not install above 13% moisture levels
Primer Over Wooden Subfloors	No
Basement Proofer over Concrete	No
Moisture Barrier (6 mil poly)	Yes
Installs Over Radiant Flooring	Yes. Electric or hydronic approved — best practice recessed min 1/2" below finished floor. Do not turn thermostat above 85°F
Suspended Wood Floors	Yes. 18" minimum well ventilated crawl space Use moisture barrier over ground/dirt Especially for mobile home installations
Foam/Cushioned Underlayment	No. Voids warranty if used in any application
Approved Subfloors - See Below	Must be smooth, solid, dry and no deflection
Wood	Yes. Solid, engineered, parquet
Plywood	Yes. OSB & particleboard are approved for <b>allure</b> products only Luan is approved for all products
Vinyl	Yes, install over 1 layer of vinyl only. Linoleum, VCT, LVT, peel & stick
Concrete	Yes. Sealed, unsealed, poured in place gypsum On grade or below grade (see moisture guidelines)
Tile (Stone)	Yes. Ceramic, Terrazzo, stone tile (grout lines of less than 1/4" is optimum)
Dricore	Yes
Subfloors Not Approved	Carpet (any type), foam underlayment, cushioned back vinyl, rubber, cork, laminates
Subfloor Approved Products	Primer - Henry 336, Basement Proofer - Custom Building Products RedGuard or TM Basement Proofer, Floor Leveler - Henry 554 & 555 Level Pro
Limitations/Exclusions	These types of installations will NOT be covered under warranty: All exterior installations & seasonal porches, boats/campers/RV's, sunrooms/solariums, non-temperature controlled rooms or homes
Steam Cleaner	DO NOT USE
Vertical Surfaces & Staircases	Not covered under warranty. Can be done using high quality construction adhesive. Product not intended for this usage
Limited Warranties	Lifetime residential, 6-year light commercial