



Dependable. Reliable. Professional.

RESIDUE FREE POLY HANGING TAPE

SPECIALTY TAPE



- Backing:** Polyethylene Film
- Adhesive:** Rubber
- Liner:** N/A
- Specifications:** N/A
- Colors:** Red, Teal
- Available Size:** 1.89 in x 54.7 yd (48 mm x 50 m)

Applications

- Ideal for hanging, patching, and seaming poly sheeting
- Masking windows and doors for paint projects
- Non-residue adhesive is also repositionable on many surfaces
- Removes cleanly for up to 7 days

Features

Benefits

Rubber Adhesive	<ul style="list-style-type: none"> • Clean release, no residue • High tack for a secure bond • Repositionable
Polyethylene Film Backing	<ul style="list-style-type: none"> • Solvent and moisture resistant • Conformable to bond to curves and around corners
Serrated Edge	<ul style="list-style-type: none"> • Hand-tearable for ease of use
Low VOC Content	<ul style="list-style-type: none"> • Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	7.0 mils	178 µm	ASTM D-1000
Adhesion to Steel	75 oz/in	8.21 N/cm	PSTC-101
Tensile Strength	25 lb/in	43.78 N/cm	ASTM D-1000
Operating Temperature	20 to 200 °F	-7 to 93 °C	
VOC Content	< 1 g/L		
Recommended Storage Conditions: 60 - 80 °F at 40-60% RH			
Standard Shelf Life (at 25 °C): 36 months from date of manufacture			

The information presented herein was prepared at BERRY GLOBAL, INC. (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To BERRY's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.

Berry 25 Forge Parkway Franklin, MA 02038
 1-800-343-7875 Fax 1-800-328-4822
 www.nashuatape.com