

In-Wall Timer - Spring Wound Countdown Timer - Decorator Style

Item SW30MWK / EAN-Code



APPLICATIONS

- ▶ Bathroom Fans
- ▶ Spas
- ▶ Hot Tubs
- ▶ Storage Closets
- ▶ Garage Lights

TECHNICAL DATA

General

Application Compatibilities	Incandescent
	Fluorescent
	Compact Fluorescent
	LED
Warranty	1-year limited
Mechanism Type	Analog/Mechanical
UPC Code	078275143487
Description	Spring Wound Countdown Timer - Decorator Style
Model Number	SW30MWK
Brand	Intermatic
Harmonized Code	9107.00.4080
Country of Origin (Intermatic)	TUNISIA

Mechanical Specifications

Wall Plate Configurations	Single-Gang
	Multi-Gang

Electrical Specifications

Neutral Connection Required	False
Wiring Configurations	Single
Input Voltages	125-277 VAC, 50 Hz;125-277 VAC, 60 Hz
Switch Type	SPST

Material Specifications

Includes Wall Plate	False
Color	White
Shipping Weight (kg)	0.159
Shipping Weight (lbs)	0.35

Control Specifications

Hold Mode Included	False
--------------------	-------

Operation Mode	Countdown
Countdown Time	30 min

Environmental Specifications

Operating Temperature Min (°C)	0
Operating Temperature Min (°F)	32
Operating Temperature Max (°C)	40
Operating Temperature Max (°F)	104
California Proposition 65	DEHP

Load Ratings

Incandescent Load Ratings (Single-Gang)	7 A, 125 VAC, 50 Hz
	7 A, 125 VAC, 60 Hz
Incandescent Load Ratings (Multi-Gang)	7 A, 125 VAC, 50 Hz; 7 A, 125 VAC, 60 Hz
Resistive	20 A, 125 VAC, 50 Hz; 10 A, 250-277 VAC, 50 Hz; 20 A, 125 VAC, 60 Hz; 10 A, 250-277 VAC, 60 Hz
Motor	1 HP, 125 VAC, 50 Hz; 2 HP, 250 VAC, 50 Hz; 1 HP, 125 VAC, 60 Hz; 2 HP, 250 VAC, 60 Hz
Resistive Range(s)	20 A, 125 VAC, 50/60 Hz; 10 A, 250/277 VAC, 50/60 Hz
Motor Range(s)	1 HP, 125 VAC, 50/60 Hz; 2 HP, 250 VAC, 50/60 Hz
Incandescent SingleGang LoadRatings Range(s)	7 A, 125 VAC, 50/60 Hz
Incandescent MultiGang LoadRatings Range(s)	7 A, 125 VAC, 50/60 Hz

Standards and Certifications

Other Certifications	cRUus
CSA Certification	cCSAus

Dimensions

Dimension	44.5x104.8x31.8mm
Product Width (in)	1.75
Product Height (in)	4.125
Product Height (mm)	104.8
Product Depth (mm)	31.8
Product Depth (in)	1.25
Unit Carton Height (in)	7
Unit Carton Width (in)	4
Unit Carton Length (in)	2.5