# **Grout Pen**



## **Section 1: Chemical Product And Company Identification**

Identity: Miracle Grout Pen (water-based marker)

Item: Bulk or Carded Stock

Colors: All colors Formula: SKM121

Manufacturers Name: Miracle Sealants Company
Address: 12318 Lower Azusa Road

Emergency Phone: 800-350-1901
City: Arcadia
State: CA

Phone: 626-443-6433
Date Prepared: 04 - 2011

## **Section 2: Composition/Information On Ingredients**

1-Methoxy-2-Propanol (107-98-2)-0.5% 2-Butoxyethanol (111-76-2) -0.5% Titanium Dioxide (13463-67-1)

## **Section 3: Hazards Identification**

Acute hazard: None. KEEP OUT OF REACH OF CHILDREN. Direct contact may cause skin or eye irritation.

#### **Section 4: First Aid Measures**

Eyes - Immediately flush eyes with plenty of water for at least fifteen (15) minutes. Get medical attention immediately.

Inhalation: Remove to fresh air. If breathing is irregular seek medical attention. No adverse effects are anticipated from inhalation.

Skin Contact: Remove contaminated clothing. Wash skin thoroughly with soap and water or use a proprietary skin cleaner.

Ingestion: If accidentally swallowed rinse mouth with water and obtain immediate medical attention.

#### **Section 5: Fire Fighting Measures**

2000

Flammability Limits (% by volume): Non-flammable

Unusual Fire Explosion Hazards: none

### **Section 6: Accidental Release Measure**

"In case of spill or accidental release, treat as water based paint."

### **Section 7: Handling And Storage**

Handling: No special handling requirements. Storage: KEEP OUT OF REACH OF CHILDREN.

## **Section 8: Exposure Controls/Personal Protection**

Eye Protection None under normal use conditions.
Clothing None under normal use conditions.
Respirator None under normal use conditions.
Ventilation None under normal use conditions.

#### **Section 9: Physical And Chemical Properties**

For ink unless otherwise specified.

Boiling Point ---->100 C

Specific Gravity ( $H_O = 1$ ) @ 70 F Greater than one (1) Vapor Pressure (mm-Hg @ 70 F): No Data Melting Point: No Data Vapor Density (AIR = 1) Greater than one (1) Evaporation Rate (Butyl Acetate=1) Less than one (1) Solubility in Water 100% PH No Data

Appearance and Odor - White opaque think viscosity liquid with paint odor.

## **Section 10: Stability And Reactivity**

Chemical Unstable

Conditions to Avoid: Large volume ingestion.
Stability Stable X
Incompatibility (Materials to Avoid): None.
Hazardous Decomposition or By-products: None.

Hazardous May Occur Conditions to Avoid: No Data

Polymerization Will not Occur X

#### **Section 11: Toxilogical Information**

None.

#### **Section 12: Ecological Information**

Not Available.

## **Section 13: Disposal Information**

"Dispose of in accordance with all applicable local, state and federal regulations."

#### Section 14: Transport Information (Not Meant To Be All Inclusive.)

Non-flammable liquid paint.

## Section 15: Regulatory Information (Not Meant To Be All Inclusive - Selected Regulations Represented)

TSCA INVENTORY: The product on this Material Safety Data Sheet is not listed on the Toxic Substances Control Act Inventory. All ingredients used to manufacture this product are listed on the TSCA Inventory.

#### **Section 16: Other Information**

"Miracle Sealants has been advised by attorney that the OSHA Hazard Communication Standard does not apply to the Miracle Sealants products listed in this MSDS. The explanation for the exemption is contained in 29 CFR 1910.1200(b)(6)(ix) as amended July 1, 2002 per the code of Federal Regulations. This information contained in this MSDS is forwarded to you for your information, but is not meant to imply that the Hazard Communication Standard covers the product nor is this MSDS meant to comply with all requirements of the Hazard Communication Standard."

"These markers and inks contained within conform to ASTM D-4236 and have been examined by certified toxicologist in a program of toxicologic evaluation to assure they are in compliance with the Federal Hazardous Substance Act (FHSA), Labeling of Hazardous Art Materials Act (LHAMA), ans ASTM D-4236."