



# DRYWAY



**UV RESISTANT**



**LONG LASTING**



**PENETRATES**



**REPELS**



**NO-SLIP**



**SALT GUARD**



**ULTRA LOW VOC**



**FREEZE GUARD**

**USES:** Outdoor concrete, concrete blocks, cinder blocks, limestone, sandstone, split-face blocks, terra cotta, brick, mortar, and pavers.

**APPLICATIONS:** Driveways, garage floors, patios, sidewalks, retaining walls, facades, shop floors, industrial warehouse, kennels, pool decks, parking areas.

**EXCLUSIONS:** Stamped, polished concrete floors, modified hydraulic cement, fiber-reinforced concrete.

**COVERAGE (approximate):**

- Poured Concrete: 150-200 sq. ft. per gallon
- Concrete Blocks: 80-120 sq. ft. per gallon
- Bricks & Pavers: 120-150 sq. ft. per gallon

**CONDITIONS:** Concrete should be **DRY** prior to application. Concrete may require several days to dry after heavy rain or pressure washing. Avoid rain for 12 hours after sealer application. Ambient air and surface temperatures must be above 40° F during the application and for 72 hours after. Avoid applying in excessive heat (over 90° F) and to hot surfaces in direct sunlight, or in strong winds and excessive humidity. New concrete should be allowed to cure for at least 28 days.

**PREP:** Surfaces must be clean, bare and porous. Vacuum or blow off excessive dust and loose particles. Repair cracks and joints prior to application. Mask surfaces not intended to be sealed. Remove paints, sealers, curing compounds, adhesives, oil, grease, mold, efflorescence and other contaminants that might interfere with the penetration of the sealer. If acid is used, it must completely be neutralized before application. **The surface must be porous enough to readily absorb the sealer. Hard-troweled concrete surfaces, require chemical etching or mechanical abrasion to increase porosity.** Use PowerEtch™ Concrete Etcher & Cleaner to obtain a proper surface profile.

**TESTING:** Concrete varies greatly in composition, finishing techniques and surface porosity. Apply DryWay™ to a small test area to confirm surface suitability, aesthetics, and ensure sealer penetration.

**STORAGE:** Store in a dry location out of direct sunlight. Do not store at temperatures above 90 °F. Avoid freezing. **SHELF LIFE:** 1 year. **FINISH APPEARANCE:** Clear.

**APPLICATION:** Apply using a hand-pump sprayer equipped with fan tip nozzle (recommended). Alternatively, a paint roller can be used if spraying is not feasible.

**STEP 1:** Agitate container thoroughly before use.

**STEP 2:** Spray DryWay™ uniformly to the surface, maintaining a sufficient continuous wetting film. For vertical surfaces, apply from bottom up allowing 4-6" rundown.

**STEP 3:** More porous surfaces may require two applications. While the concrete is still damp, apply a second wet-on-wet application to the surface about 10 minutes after the first application.

**DO NOT OVERAPPLY.** Avoid pooling or excessive rundown. Broom, roll, or brush away puddles until the sealer has fully penetrated.

**CLEAN UP:** Rinse tools with water and liquid detergent immediately after use. Remove overspray with a wet towel before it dries. Dispose of unused material and empty containers in accordance with local regulations.

**DRYING:** Treated surfaces will begin to appear dry in 3-6 hours. Avoid foot and vehicular traffic until dry. Water repellency will develop over a period of 4+ days after application.

**CONTENTS:** Triethoxy(octyl)silane CAS#: 2943-75-1, Dimethyl siloxane with aminoethylaminopropyl silsesquioxane, hydroxy-term CAS#: 68554-54-1, Ethoxylated lauryl alcohol CAS#: 9002-92-0

**CAUTION! KEEP OUT OF THE REACH OF CHILDREN. DO NOT TAKE INTERNALLY. MAY CAUSE EYE OR SKIN IRRITATION. AVOID CONTACT WITH SKIN AND EYES.**

**FIRST AID: EYE CONTACT:** Flush with water for at least 15 minutes. If irritation persists, seek medical attention. **SKIN CONTACT:** Wash thoroughly with soap and water.

**INGESTION:** If swallowed, do not induce vomiting. Seek medical attention.

**DISCLAIMER:** Novion Inc. shall not be liable for any injury, loss, direct, indirect, or consequential damages arising out of the use of this product. The buyer shall determine the suitability of the product for the intended use and assumes all risk and liability in connection with the use of this product.

5-GAL (18.9 L)

Visit [www.radonseal.com](http://www.radonseal.com) for tips on sealing various cementitious materials and knowledgeable advice.

RadonSeal® • 494 Bridgeport Ave, 101 • Shelton, CT 06484 • 800-472-0603 • sales@radonseal.com • MADE IN USA

