



BEHR PREMIUM® Solid Color Concrete Stain

No. 800 White Base

No. 830 Deep Base

- Interior/Exterior Flat Finish
- Siliconized 100% Acrylic
- Weather Resistant
- Weather & Household Stain Resistant Finish



Spread Rate:
Rough 37-47 m²
Smooth 47-56 m²



Dry Time:
2 Hr. Dry to Touch
2-4 Hr. Recoat



Clean-Up:
Soap & Water



Protect
from Freezing

CAUTION: Stained surfaces may become slippery when wet. Follow all label instructions.

WHERE TO USE

Properly prepared Interior/Exterior surfaces such as: Concrete, Masonry Walls, Patios, Walkways, Driveways*, Garage Floors*, Pool Decks**, Tennis Courts, Cement Blocks, Pillars and Brick. Not for use on surfaces subject to hydrostatic pressure. * Driveways and Garage Floors - Lack of proper surface preparation and/or over-application can lead to automobile tires lifting the product from the surface. ** Light and pastel colored concrete stains should be used over pool deck surfaces. DARK COLOURS RETAIN HEAT.

PREPARATION†

Uncoated Concrete or Masonry Surfaces: Allow new surfaces to cure 30 days. Clean and etch surface using a product such as BEHR PREMIUM No. 991 Concrete & Masonry Cleaner & Etcher to achieve a textured profile similar to 150 grit sandpaper. Apply a product such as Behr Premium No. 880 Concrete & Masonry Bonding Primer to increase adhesion of topcoat to the surface.

Painted Surfaces-Concrete: For a painted surface in sound condition, use a product such as BEHR PREMIUM No. 990 Concrete & Masonry Degreaser & Cleaner to clean and prepare the surface. If the coating is failing or peeling, use a paint stripper such as BEHR PREMIUM No. 992 Concrete & Masonry Paint Stripper to remove old coating or scrape/sand down to a sound concrete surface. Scuff sand glossy surfaces. Clean and spot etch any exposed concrete using a product such as BEHR PREMIUM No. 991 Concrete & Masonry Cleaner & Etcher. Remove all dust with a damp cloth, allow to dry. Spot prime all uncoated areas with a product such as BEHR PREMIUM No. 880 Concrete & Masonry Bonding Primer to increase adhesion of topcoat to the surface. Follow all label instructions.

LIMITED WARRANTY If this product is found to be defective upon inspection by an expert, Behr Process Corporation will, at its option, and upon presentation of proof-of-purchase (the original receipt), either furnish an equivalent amount of new product or refund the original purchase price of this product to you. This warranty is not transferable. If you believe this product is defective, contact Behr Process Corporation at 2750 Centre Avenue N.E., Calgary, AB T2A2L3. The cost of transportation or shipping, if any, are to be assumed by the consumer. The clause of limitation of liability which follows is inapplicable in Quebec: **This warranty excludes (1) labour and costs of labour for the application or removal of any product, and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** The above provisions are not intended to operate where prohibited by law. This limited warranty is the only warranty provided by Behr Process Corporation unless extended by a provincial consumer statute.

To consult with a Behr Certified Coatings Professional, call 1-800-661-1591.

APPLICATION

Intermix all cans of same product to ensure colour uniformity. Stir stain before and occasionally during application. Use product when air and surface temperatures are between 10-32° C. Apply a thin, even coat using a 6-10 mm nap roller cover, pad applicator, a nylon/polyester brush or an airless sprayer with an adjustable tip (.015"-.019", 60 mesh filter). Use long, even strokes in one direction to avoid lap lines. Spread rate varies, depending on the surface texture, porosity and application method. Do not thin if using a roller or brush; however, if using a sprayer and thinning is required, thin with water at a rate of no more than 236 ml per 3.79 L. Additional coats may be required for optimal hide and durability. Periodic touch-ups may be necessary.

DRY TIME

Longer dry time required in cooler temperatures and higher humidity. Allow 24 hours for light foot traffic. Allow 72 hours before subjecting surface to automotive tires, repositioning planters or furniture. Park tires on corrugated cardboard for 14 days after applying stain. After 30 days, dry stained surface may be cleaned with a mild, non-abrasive liquid detergent.

DISPOSAL

Properly dispose of all soiled rags. To recycle or properly dispose of product in your community, contact your household refuse collection service.

† **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead

CAUTION! IRRITANT! HARMFUL IF SWALLOWED. MAY IRRITATE EYES AND SKIN. Avoid contact with eyes, skin and clothing. Do not breathe fumes. Wear eye protection and protective clothing. Use only with adequate ventilation. **FIRST AID TREATMENT:** Contains ETHYLENE GLYCOL. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes rinse with water for 20 minutes. If on skin rinse well with water. If inhaled, move person to fresh air.

CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.

BEHR
A Masco Company

©2016 Behr Process Corporation
Santa Ana, CA 92704 U.S.A. • behr.com
V.O.C. (C.O.V.) <100 g/L • REV. 08/16