



Finish Black

Lamping

Number of Bulbs	3	
Light Type	Incandescent	
Bulb Type	CA	
Max Bulb Wattage	60	
Max Fixture Wattage	180	
Rated Life	±1,500 Hours	
Rated Lumens	±2,016	
Color Temp	±2,700 K	
Bulb(s)	Not Included	
Light Up/Down	N/A	
Beam Spread	N/A	
CRI	N/A	
Photo Cell Included	N/A	
Ballast/Driver/Transformer	No	
Dimmable	Standard Dimmer	

1029BK


3-Light Outdoor Ceiling Mount

Glass/Shade Clear

Measurements Width 11.00 Height 6.50 Length N// Extension N// **Back Plate Width** N/ **Back Plate Height** N// нсо N// Min Overall Height 0.00 Max Overall Height N/ Hanging Weight 3.35 lb Height Adjustable N/ Slope N// **Chain Length** N// Wire Length N// Canopy Width N/A **Canopy Height** N/A **Canopy Length** N/A

Product Specifications - 1029BK

Job Name:	Job Type:
Quantity:	Comments



Product Category Outdoor Flush Mount

	Shipping	
0"	Carton Weight	4.20 lbs
D "	Carton Width	11"
Ά	Carton Height	8"
Ά	Carton Length	13"
Ά	Carton Cubic Feet	0.73
Ά	Master Pack	6
Ά	Master Pack Weight	23.50 lbs
D "	Master Pack Width	13.58"
Ά	Master Pack Height	18.31"
os	Master Pack Length	35.24"
Ά	Master Cubic Feet	5.07
Ά	UPS Shippable	Yes
Ά		
Ά		

Certification		Other		Equivalents	
Safety Rating	Damp	UPC Code	783209102903	Incandescent Watts	N/A
Energy Star	No	Shades Included	N/A	Fluorescent Watts	N/A
CA Title 24	No	Crystals Included	N/A		
CA Title 20	No	Diffuser Included	N/A		
ADA	No	Conversion Kit	N/A		
Dark Sky	N/A	Material	Aluminum		

Maxim Lighting International and all designs, logos and images © 2016 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.