

CONTENTS: Acetone (67-64-1), Toluene (108-88-3), Propane (74-98-6), Butane (106-97-8), Proprietary Resin, Graphite (7782-42-5), n-Heptane (142-82-5), Silica (14808-60-7).

⚠ WARNING: Cancer and Reproductive Harm – www.P65Warnings.ca.gov

HAZARD STATEMENTS AND PRECAUTIONARY MEASURES: Vapor harmful. May affect the brain or nervous system, causing dizziness, headache, or nausea. Causes severe eye irritation. Causes skin, mouth, throat, and stomach irritation. Causes respiratory tract irritation. May cause kidney or liver damage. Cancer hazard. Contains material which can cause cancer. Prolonged exposure to respirable crystalline quartz silica may cause delayed chronic injury (silicosis). May cause birth defects. Vapors may ignite explosively. Turn off engine before using this product. Keep away from heat, sparks and open flame. No smoking. **USE ONLY IN WELL-VENTILATED AREAS.** Ensure adequate ventilation, especially in confined areas. Prevent buildup of vapors by opening all windows and doors to achieve cross-ventilation. Do not store above 120 degrees F (49 degrees C). Empty containers may contain product residue, including flammable or explosive vapors. Do not cut, puncture or weld on or near container. All label warnings must be observed until the container has been commercially cleaned or reconditioned. Avoid contact with eyes, skin, and clothing. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Notice - Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

FIRST AID: In the event of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention. If medical assistance is not immediately available, flush an additional 15 minutes. For skin contact, wash off immediately with plenty of water for at least 15 minutes. Get medical attention. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

DIRECTIONS: Shake well before use. Spray light film on dry surface. Product is more effective if allowed to dry 5-10 minutes before use. Formula will cause staining of clothing and other fabrics.


WARRANTY: MANUFACTURER MAKES NO WARRANTIES WITH RESPECT TO THIS PRODUCT, EXPRESS OR IMPLIED. MANUFACTURER DISCLAIMS ALL IMPLIED WARRANTIES, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE. MANUFACTURER WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.

KEEP OUT OF REACH OF CHILDREN

• Medical Emergency Number 1-888-345-5732

* **MINIMUM APPLICATION TEMPERATURE 40° FAHRENHEIT**

** **RESULTS MAY VARY DEPENDING ON SURFACE PREPARATION AND USAGE CONDITIONS.**




APPLY UNDER DECK



APPLY INSIDE CHUTE



APPLY ON AUGERS



777X46284B



by **ARNOLD**

NON-STICK SPRAY

**FOR MOWERS, TRACTORS
AND SNOW BLOWERS**

**AEROSOL
ANTIADHERENTE
PARA CORTACÉSPEDES,
TRACTORES Y MÁQUINAS QUITANIEVES**



**FLAT BLACK FINISH
LONG-LASTING ANTI-STICK
GRAPHITE SPRAY***

ACABADO NEGRO MATE
AEROSOL ANTIADHERENTE DE
GRAFITO DE LARGA DURACIÓN*

**One
Application**

Works Up to a Season Long**

Una aplicación dura hasta
toda una temporada**

See website for helpful installation videos
www.arnoldparts.com



Helps improve mower
discharging, bagging and
mulching performance by
preventing grass clipping
buildup in mowing deck.



Also helps improve snow
blowing performance by
preventing snow buildup
on the augers, impeller
and snow blower chute.

Arnold
305 Mansfield Ave., Shelby, OH 44875
www.arnoldparts.com
C.O.O.: U.S.A.

DANGER!

EXTREMELY FLAMMABLE LIQUID AND VAPOR.
VAPOR MAY CAUSE FLASH FIRE. VAPOR HARMFUL.
CONTENTS UNDER PRESSURE.
READ OTHER CAUTIONS ON BACK PANEL.

NET WT. 5.25 OZ./149 G

490-900-0062