

MATERIAL SAFETY DATA SHEET

Tire Sealant

Prepared to U.S. OSHA, CMA, ANSI, Canadian WHMIS, Australian WorkSafe, Japanese Industrial Standard JIS Z 7250:2000, and European Union REACH Regulations



SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: **Tire Sealant**
CHEMICAL FAMILY NAME: None
PRODUCT USE: This tire sealant is inserted into the tube prior to tube inflation and is used to seal tire punctures.
U.N. NUMBER: NA
U.N. DANGEROUS GOODS CLASS: Non-Regulated
SUPPLIER/MANUFACTURER'S NAME: Marathon Industries
ADDRESS: 7925 South 196th Street, Kent, WA 98032 USA
EMERGENCY PHONE: **800-424-9300 (Chemtrec)**
BUSINESS PHONE: 253-893-7014
FAX NUMBER: 253-893-7021
DATE OF PREPARATION: July 25, 2011
DATE OF LAST REVISION: New

SECTION 2 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: This product is a liquid provided in various colors with a slight odor. Exposure can be irritating to eyes and skin. This product is harmful if swallowed. Based on product use exposure is unlikely. It is a non-flammable liquid, but will support combustion above the flash point. The environmental effects of this product have not been investigated.

US DOT SYMBOLS

Non-Regulated

CANADA (WHMIS) SYMBOLS



EUROPEAN and (GHS) Hazard Symbols



Signal Word: **Warning!**

EU LABELING AND CLASSIFICATION:

Classification of the substance or mixture according to Regulation (EC) No1272/2008 Annex 1
EC# 231-791-2 This substance is not classified in the Annex I of Directive 67/548/EEC
EC# 203-473-3 Index # 603-027-00-1
EC# 232-674-9 This substance is not classified in the Annex I of Directive 67/548/EEC

GHS Hazard Classification(s):

Acute Toxicity Category 4

Hazard Statement(s):

H302: Harmful if swallowed

Precautionary Statement(s):

P264: Wash hands thoroughly after handling
P270: Do not eat, drink or smoke when using this product

Hazard Symbol(s):

[Xn] Harmful

Risk Phrases:

R22: Harmful if swallowed.

Safety Phrases:

S2: Keep out of the reach of children
S46: If swallowed, seek medical advice immediately and show label

HEALTH HAZARDS OR RISKS FROM EXPOSURE:

ACUTE: Exposure to this product may cause irritation of the eyes with redness and tearing. Contact with skin may cause irritation. Inhalation of this product may cause irritation to the respiratory tract. Ingestion may cause gastrointestinal irritation including pain, vomiting or diarrhea. The substance may be toxic to kidneys, liver, and central nervous system (CNS). Repeated or prolonged exposure to the substance can produce target organs damage.

CHRONIC: Repeated exposure to a highly toxic material may produce general deterioration of health by an accumulation in one or many human organs.

MATERIAL SAFETY DATA SHEET

Tire Sealant

TARGET ORGANS:

ACUTE: Eye, respiratory System, Skin

CHRONIC: Kidneys, liver, Central nervous system

SECTION 3 - COMPOSITION and INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENTS:	CAS #	EINECS #	ICSC #	WT %	HAZARD CLASSIFICATION; RISK PHRASES
Water	7732-18-5	231-791-2	Not Listed	45 -55%	HAZARD CLASSIFICATION: None RISK PHRASES: None
Ethylene Glycol	107-21-1	203-473-3	0270	35 - 45%	HAZARD CLASSIFICATION: [Xn] Harmful RISK PHRASES: R22
Crumb Rubber	Mixture	Mixture	Not Listed	<5%	HAZARD CLASSIFICATION: None RISK PHRASES: None
Cellulose Fibers	9004-34-6	232-674-9	Not Listed	<2%	HAZARD CLASSIFICATION: None RISK PHRASES: None
Balance of other ingredients are non-hazardous or less than 1% in concentration (or 0.1% for carcinogens, reproductive toxins, or respiratory sensitizers).					

NOTE: ALL WHMIS required information is included in appropriate sections based on the ANSI Z400.1-2004 format. This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR, EU Directives and the Japanese Industrial Standard *JIS Z 7250: 2000*.

SECTION 4 - FIRST-AID MEASURES

Contaminated individuals of chemical exposure must be taken for medical attention if any adverse effect occurs. Rescuers should be taken for medical attention, if necessary. Take copy of label and MSDS to health professional with contaminated individual.

EYE CONTACT: If product enters the eyes, open eyes while under gentle running water for at least 15 minutes. Seek medical attention if irritation persists or blurred vision occurs.

SKIN CONTACT: Wash skin thoroughly after handling. Seek medical attention if irritation develops and persists. Remove contaminated clothing. Launder before re-use.

INHALATION: If breathing becomes difficult, remove victim to fresh air. If necessary, use artificial respiration to support vital functions. Seek medical attention.

INGESTION: If product is swallowed, call physician or poison control center for most current information. If professional advice is not available, do not induce vomiting. Never induce vomiting or give diluents (milk or water) to someone who is unconscious, having convulsions, or who cannot swallow. Seek medical advice. Take a copy of the label and/or MSDS with the victim to the health professional.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Pre-existing skin, or eye problems may be aggravated by prolonged contact. Persons with pre-existing kidney, respiratory, eye, or neurological problems might be more sensitive to Ethylene Glycol.

RECOMMENDATIONS TO PHYSICIANS: Treat symptoms and reduce over-exposure.

SECTION 5 - FIRE-FIGHTING MEASURES

FLASH POINT:

May be combustible at high temperature.

AUTOIGNITION TEMPERATURE:

Not Available

FLAMMABLE LIMITS (in air by volume, %):

Lower (LEL): Not Applicable Upper (UEL): Not Applicable

FIRE EXTINGUISHING MATERIALS:

As appropriate for surrounding fire. Carbon dioxide, foam, dry chemical, halon, or water fog.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

None known

Explosion Sensitivity to Mechanical Impact:

No

Explosion Sensitivity to Static Discharge:

No


SPECIAL FIRE-FIGHTING PROCEDURES:

Incipient fire responders should wear eye protection. Structural firefighters must wear Self-Contained Breathing Apparatus and full protective equipment. Isolate materials not yet involved in the fire and protect personnel. Move containers from fire area if this can be done without risk; otherwise, cool with carefully applied water spray. If possible, prevent runoff water from entering storm drains, bodies of water, or other environmentally sensitive areas.

MATERIAL SAFETY DATA SHEET

Tire Sealant

NFPA RATING SYSTEM



HMIS RATING SYSTEM

HAZARDOUS MATERIAL IDENTIFICATION SYSTEM			
HEALTH HAZARD (BLUE)	1		
FLAMMABILITY HAZARD (RED)	1		
PHYSICAL HAZARD (YELLOW)	0		
PROTECTIVE EQUIPMENT			
EYES	RESPIRATORY	HANDS	BODY
	See Sect 8		See Sect 8
For Routine Industrial Use and Handling Applications			

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic hazard

SECTION 6 - ACCIDENTAL RELEASE MEASURES

SPILL AND LEAK RESPONSE: Personnel should be trained for spill response operations.

SPILLS: Contain spill if safe to do so. Prevent entry into drains, sewers, and other waterways. Soak up with an absorbent material and place in an appropriate container for disposal. Dispose of in accordance with applicable Federal, State, and local procedures (see Section 13, Disposal Considerations).

SECTION 7 - HANDLING and STORAGE

WORK PRACTICES AND HYGIENE PRACTICES: As with all chemicals, avoid getting this product ON YOU or IN YOU. Wash thoroughly after handling this product. Do not eat, drink, smoke, or apply cosmetics while handling this product. Avoid breathing vapors. Use in a well-ventilated location. Remove contaminated clothing.

STORAGE AND HANDLING PRACTICES: Containers of this product must be properly labeled. Store containers in a cool, dry location.

SECTION 8 - EXPOSURE CONTROLS - PERSONAL PROTECTION

EXPOSURE LIMITS/GUIDELINES:

Chemical Name	CAS#	ACGIH TWA	OSHA TWA	SWA
Water	7732-18-5	Not Listed	Not Listed	Not Listed
Ethylene Glycol	107-21-1	100 mg/m ³	125 mg/m ³	100 mg/m ³
Crumb Rubber	Mixture	Not Listed	Not Listed	Not Listed
Cellulose Fibers	9004-34-6	Not Listed	Not Listed	Not Listed

Currently, International exposure limits are not established for the components of this product. Please check with competent authority in each country for the most recent limits in place.

VENTILATION AND ENGINEERING CONTROLS: Use with adequate ventilation to ensure exposure levels are maintained below the limits provided below. Use local exhaust ventilation to control airborne dust. Ensure eyewash/safety shower stations are available near areas where this product is used.

The following information on appropriate Personal Protective Equipment is provided to assist employers in complying with OSHA regulations found in 29 CFR Subpart I (beginning at 1910.132) or equivalent standard of Canada, or standards of EU member states (including EN 149 for respiratory PPE, and EN 166 for face/eye protection), and those of Japan. Please reference applicable regulations and standards for relevant details.

MATERIAL SAFETY DATA SHEET

Tire Sealant

RESPIRATORY PROTECTION: Maintain airborne contaminant concentrations below guidelines listed above, if applicable. If necessary, use only respiratory protection authorized in the U.S. Federal OSHA Respiratory Protection Standard (29 CFR 1910.134), equivalent U.S. State standards, Canadian CSA Standard Z94.4-93, the European Standard EN149, or EU member states.

EYE PROTECTION: Safety glasses. If necessary, refer to U.S. OSHA 29 CFR 1910.133 or appropriate Canadian Standards.

HAND PROTECTION: Use chemical resistant gloves to prevent skin contact. If necessary, refer to U.S. OSHA 29 CFR 1910.138 or appropriate Standards of Canada.

BODY PROTECTION: Use body protection appropriate to prevent contact (e.g. lab coat, overalls). If necessary, refer to appropriate Standards of Canada, or appropriate Standards of the EU, Australian Standards, or relevant Japanese Standards.

SECTION 9 - PHYSICAL and CHEMICAL PROPERTIES

PHYSICAL STATE:	Liquid
APPEARANCE & ODOR:	This product is a liquid provided in various colors with a slight odor.
ODOR THRESHOLD (PPM):	Not Available
VAPOR PRESSURE (mmHg):	>80 mm @ 100°F
VAPOR DENSITY (AIR=1):	1.8
BY WEIGHT:	Not Available
EVAPORATION RATE (nBuAc = 1):	Not Available
BOILING POINT (C°):	>100°C (212°F)
FREEZING POINT (C°):	-38°C
pH:	8.25
SPECIFIC GRAVITY 20°C: (WATER =1)	1.08 g/cm ³
SOLUBILITY IN WATER (%):	80% solubility

SECTION 10 - STABILITY and REACTIVITY

STABILITY: Product is stable

DECOMPOSITION PRODUCTS: When heated to decomposition this product produces Oxides of carbon (COx) and Hydrocarbons

MATERIALS WITH WHICH SUBSTANCE IS INCOMPATIBLE: Strong oxidizing agents.

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: Contact with incompatible materials.

SECTION 11 - TOXICOLOGICAL INFORMATION

TOXICITY DATA: Toxicity data is not available for mixture:

CAS# 107-21-1 LD50 Oral (Rat) 4700 mg/kg

SUSPECTED CANCER AGENT: None of the ingredients are found on the following lists: FEDERAL OSHA Z LIST, NTP, CAL/OSHA, IARC and therefore is not considered to be, nor suspected to be a cancer-causing agent by these agencies.

IRRITANCY OF PRODUCT: Prolonged contact with this product can be irritating to exposed skin, eyes and respiratory system.

SENSITIZATION OF PRODUCT: This product is not considered a sensitizer.

REPRODUCTIVE TOXICITY INFORMATION: No information concerning the effects of this product and its components on the human reproductive system.

SECTION 12 - ECOLOGICAL INFORMATION

ALL WORK PRACTICES MUST BE AIMED AT ELIMINATING ENVIRONMENTAL CONTAMINATION.

ENVIRONMENTAL STABILITY: No Data available at this time.

EFFECT OF MATERIAL ON PLANTS or ANIMALS: No evidence is currently available on this product's effects on plants or animals.

EFFECT OF CHEMICAL ON AQUATIC LIFE: No evidence is currently available on this product's effects on aquatic life.

SECTION 13 - DISPOSAL CONSIDERATIONS

PREPARING WASTES FOR DISPOSAL: Waste disposal must be in accordance with appropriate Federal, State, and local regulations, those of Canada, Australia, EU Member States and Japan.

MATERIAL SAFETY DATA SHEET

Tire Sealant

SECTION 14 - TRANSPORTATION INFORMATION

US DOT; IATA; IMO; ADR:

THIS PRODUCT IS NOT HAZARDOUS AS DEFINED BY 49 CFR 172.101 BY THE U.S. DEPARTMENT OF TRANSPORTATION.

PROPER SHIPPING NAME: Non-Regulated Material

HAZARD CLASS NUMBER and DESCRIPTION: None

UN IDENTIFICATION NUMBER: Not Applicable

PACKING GROUP: Not Applicable

DOT LABEL(S) REQUIRED: None

NORTH AMERICAN EMERGENCY RESPONSE GUIDEBOOK NUMBER (2004): None

MARINE POLLUTANT: None of the ingredients are not classified by the DOT as a Marine Pollutant (as defined by 49 CFR 172.101, Appendix B)

U.S. DEPARTMENT OF TRANSPORTATION (DOT) SHIPPING REGULATIONS:

This product is not classified as dangerous goods, per U.S. DOT regulations, under 49 CFR 172.101.

TRANSPORT CANADA, TRANSPORTATION OF DANGEROUS GOODS REGULATIONS:

This product is not classified as Dangerous Goods, per regulations of Transport Canada.

INTERNATIONAL AIR TRANSPORT ASSOCIATION (IATA):

This product is not classified as Dangerous Goods, by rules of IATA.

INTERNATIONAL MARITIME ORGANIZATION (IMO) DESIGNATION:

This product is not classified as Dangerous Goods by the International Maritime Organization.

EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY ROAD (ADR):

This product is not classified by the United Nations Economic Commission for Europe to be dangerous goods.

SECTION 15 - REGULATORY INFORMATION

UNITED STATES REGULATIONS

SARA REPORTING REQUIREMENTS: This product is subject to the reporting requirements of Sections 302, 304 and 313 of Title III of the Superfund Amendments and Reauthorization Act., as follows: Ethylene Glycol CAS# 107-21-1<45%

TSCA: All components in this product are listed on the US Toxic Substances Control Act (TSCA) inventory of chemicals.

SARA 311/312:

Acute Health: Yes Chronic Health: No Fire: Yes Reactivity: No

U.S. SARA THRESHOLD PLANNING QUANTITY: There are no specific Threshold Planning Quantities for this product. The default Federal MSDS submission and inventory requirement filing threshold of 10,000 lb (4,540 kg) may apply, per 40 CFR 370.20.

U.S. CERCLA REPORTABLE QUANTITY (RQ): Ethylene glycol CAS# 107-21-1: 5000 lbs. (2268 kg)

CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT (PROPOSITION 65): None of the ingredients are on the California Proposition 65 lists.

CANADIAN REGULATIONS:

CANADIAN DSL/NDL INVENTORY STATUS: All of the components of this product are on the DSL Inventory

CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA) PRIORITIES SUBSTANCES LISTS: No component of this product is on the CEPA First Priorities Substance Lists.

CANADIAN WHMIS CLASSIFICATION and SYMBOLS: This product is categorized as a Controlled Product, Hazard Class D2B as per the Controlled Product Regulations

EUROPEAN ECONOMIC COMMUNITY INFORMATION:

EU LABELING AND CLASSIFICATION:

Classification of the mixture according to Regulation (EC) No1272/2008. See section 2 for details.

AUSTRALIAN INFORMATION FOR PRODUCT:

AUSTRALIAN INVENTORY OF CHEMICAL SUBSTANCES (AICS) STATUS: All components of this product are listed on the AICS.

STANDARD FOR THE UNIFORM SCHEDULING OF DRUGS AND POISONS: Not applicable.

JAPANESE INFORMATION FOR PRODUCT:

JAPANESE MINISTER OF INTERNATIONAL TRADE AND INDUSTRY (MITI) STATUS: The components of this product are not listed as Class I Specified Chemical Substances, Class II Specified Chemical Substances, or Designated Chemical Substances by the Japanese MITI.

MATERIAL SAFETY DATA SHEET

Tire Sealant

INTERNATIONAL CHEMICAL INVENTORIES:

Listing of the components on individual country Chemical Inventories is as follows:

Asia-Pac:	Listed
Australian Inventory of Chemical Substances (AICS):	Listed
Korean Existing Chemicals List (ECL):	Listed
Japanese Existing National Inventory of Chemical Substances (ENCS):	Listed
Philippines Inventory of Chemicals and Chemical Substances (PICCS):	Listed
Swiss Giftlist List of Toxic Substances:	Listed
U.S. TSCA:	Listed

SECTION 16 - OTHER INFORMATION

PREPARED BY: Paul Eigbrett

MSDS Authoring Services

Disclaimer: To the best of Marathon Industries knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type either express or implied are provided. The information contained herein relates only to this specific product.