



# EAGLE

## PAVER SEALER

For Concrete Brick Pavers

**PAVER SEALER** is a tough, high solids acrylic copolymer sealer in a solvent base. It is designed to protect and beautify concrete pavers to prevent water penetration, vegetation, surface staining, and efflorescence. **PAVER SEALER** contains UV absorbers and blockers to prevent yellowing, increase the life span of the film, and restore or maintain the original color. Paver joints will be stabilized and concrete paver will be sealed. Not suitable for clay bricks.



★ **Wet Look**

★ **U.V. Resistant**

★ **Resists Staining & Color Fade**

★ **Restores Color**

★ **Locks Paver Sand**

★ **Enhances & Protects**

★ [www.eaglesealer.com](http://www.eaglesealer.com) ★

# PAVER SEALER

## DESCRIPTION

**EAGLE PAVER SEALER** is a high solids non-yellowing solvent-based sealer designed to enhance and protect pavers. This modified acrylic resists water blushing and adds UV protection to prevent sun fade. It acts as a joint stabilizer to reduce erosion and vegetation. Multiple coats will add gloss. **EAGLE PAVER SELAER** will darken and highlight the color of concrete pavers.

## TOOLS & MATERIALS REQUIRED

- ★ EAGLE CLEANER DEGREASER & NEUTRALIZER
- ★ EAGLE ETCH & CLEAN
- ★ Solvent resistant pump-up sprayer
- ★ Solvent resistant roller of appropriate nap

## PREPARATION

Clean dirt, wax, grease, oil and other contaminants from the surface. Be sure to remove any foreign coating unless previous coating is same or similar solvent-based sealer. Make sure the surface is clean, dry and sound. Clean oily concrete with **EAGLE CLEANER DEGREASER & NEUTRALIZER**. Use a bristle brush for heavily oiled spots. Rinse well with a pressure washer. Sweep away any loose sand. Allow 24 hours to dry. Apply only when surface and air temperatures are above 50° F and below 90° F. Do not apply to excessively hot surfaces as rapid drying may cause bubbles or streaking to form.

## APPLICATION

For exterior application only. Perform test to ensure compatibility. Brush may be used where roller won't reach. Do not pour directly from can to pavers. Apply evenly from can or other metal container with appropriate roller. Use a medium nap roller. Keep roller soaked by dipping on every stroke. Every few feet turn perpendicular to the first coat, and cross roll without re-dipping. Wait until the surface is tack-free before applying a second coat. The continual dipping with the first coat gives a heavy application and the cross-rolling allows for an even application. If spraying, use a solvent resistant sprayer and clean up immediately with aromatic solvent such as Xylene or Lacquer Thinner. Do not thin product. Foot traffic should be avoided for 4 hours. Vehicle traffic should be avoided for 48 hours. Do not apply if rain is imminent. Cooler temperatures or increased humidity will slow the drying time.

**WARNING:** Strong solvent smell.

## NET COVERAGE RATE

Two thin coats are recommended. Apply to pavers at a rate of 100 ft<sup>2</sup> per gallon. To build desired level of gloss, additional coats may be required.

## MAINTENANCE

Clean sealed surface with water only. Reseal surface as needed, but no more often than every two years to prevent buildup of sealer.

## CLEANUP

Clean up tools with Xylene or Lacquer Thinner.

## TECHNICAL DATA

VOC: standard <700 g/L  
Flash Point: 105° F

HMIS			
Health	2	Flammability	2
Reactivity	0	Protection	B

**DISCLAIMER:** Since manufacturer has no control over handling, use or storage; no guarantee expressed or implied, is offered. The suitability of the product for use shall be solely up to the user. Manufacturer retains the right to venue.

Made in USA  
**EAGLE IFP COMPANY**  
[www.eaglesealer.com](http://www.eaglesealer.com)