

# Troubleshooting

Problem	Solution
The fan will not start.	<ul style="list-style-type: none"><li><input type="checkbox"/> Check the main and branch circuit fuses or breakers.</li><li><input type="checkbox"/> Check the line wire connections to the fan and switch wire connections in the switch housing.</li><li><input type="checkbox"/> Check the battery in the remote control.</li><li><input type="checkbox"/> Ensure you are in the normal range of 10-20 feet.</li><li><input type="checkbox"/> Remember to turn off the power supply before checking the dip switch settings.</li></ul>
The fan is noisy.	<ul style="list-style-type: none"><li><input type="checkbox"/> Ensure all motor housing screws are snug.</li><li><input type="checkbox"/> Ensure the screws that attach the fan blade bracket to the motor hub are tight.</li><li><input type="checkbox"/> Ensure the wire nut connections are not rattling against each other or the interior wall of the switch housing.</li><li><input type="checkbox"/> Allow a 24-hour “breaking in” period. Most noises associated with a new fan disappear during this time.</li><li><input type="checkbox"/> If you are using the Ceiling Fan light kit, ensure the screws securing the glassware are tight. Check that the light bulbs are also secure.</li><li><input type="checkbox"/> Ensure the canopy is a short distance from the ceiling. It should not touch the ceiling.</li><li><input type="checkbox"/> Ensure your outlet box is secure and rubber isolator pads were used between the mounting plate and outlet box.</li></ul>
The fan wobbles.	<ul style="list-style-type: none"><li><input type="checkbox"/> Check that all blade and blade arm screws are secure.</li><li><input type="checkbox"/> Most fan wobble problems are caused when blade levels are unequal. Check this level by selecting a point on the ceiling above the tip of one of the blades. Measure from a point on the center of the blade to the point on the ceiling. Rotate the fan until the next blade is positioned for measurement, and measure from the same point on each blade to the ceiling. Repeat for each blade. Any measurement deviation should be within 1/8 in. Run the fan for ten minutes. If the fan continues to wobble please contact Home Decorators Collection Customer Service and a balancing kit will be sent to you at no charge.</li></ul>
The light are not dimming.	<ul style="list-style-type: none"><li><input type="checkbox"/> Remove the battery cover from the back of the remote control and verify that the “ON/DIM” dip switch is set to “DIM”. You must use incandescent light bulbs (60-watt max.) in order to use the dimming function.</li></ul>
The lights are flickering.	<ul style="list-style-type: none"><li><input type="checkbox"/> If you are using CFL light bulbs, open the back of the remote control and verify that the “ON/DIM” dip switch is set to the “ON” position. If you wish to use the “DIM” feature, change the light bulbs to 60-watt max. incandescent bulbs.</li></ul>
The wiring diagram is confusing or incorrect.	<ul style="list-style-type: none"><li><input type="checkbox"/> Download the current generation of the wiring diagram located in the installation manual.</li></ul>
The receiver is clicking.	<ul style="list-style-type: none"><li><input type="checkbox"/> Recheck the wire connections.</li></ul>