CANARM[®] **CP - COMMERCIAL CEILING FANS**

MODEL: CP36

ENERGY SAVINGS

COST EFFECTIVE

Note: Blades must be mounted a

minimum of 10' off floor.

15.125

EFFICIENT

MMMM

22"

Features

- Ideally suited for circulating air in Industrial and Commercial Applications.
- Canarm's "CP" Fans help save energy year round.
- 36" blade sweep
- Variable speed motor (all motors are impedance protected, PSC type variable speed with permanently lubricated ball bearing motors).
- When used with our MC series speed controls the speed range is infinite.
- Painted steel blades with curved ends deliver maximum airflow over wide areas. •
- All models are reversible. •
- Reversible motor provides both winter destratification and summer time cooling.
- Standard Installation is with a 3/8" J-Hook.

Note: To mount in a ceiling fan approved electrical box, use the the R-B-CPU Clamp sold as an optional accessory.

Performance Data & Specifications



Model Number	Colour	Airflow	Fan Size	Max RPM	Air Velocity 5' from fan	Air Delivery @ Floor	Amps High	Amps Low	Watts High	Watts Low	Downrod Length	Shipping Weight (Lbs.)	SP.
CP36	White	Up/Downdraft	36"	380	750 ft/min	7,100 cfm	0.7	0.25	76	28	16"	12	c Us

CEILING FAN SPEED CONTROLS

MODELS: "MC" CONTROL & "FRMC5" CONTROL

"MC" CONTROL

- Available in 4 models: 3 amp, 5 amp, 10 amp and 12 amp.
- The MC15 can operate up to 10 fans on a single control.
- Infinite speed adjustment
- Minimum speed adjustment screw.
- Designed to fit a standard 3" x 5" electrical box.
- Mount in a dry location such as the control room.

"FRMC5" CONTROL

- A slide switch is provided to change the direction of the fan from updraft to downdraft.
- 5 amp rating for all reversible models.
- Up to 4 fans can operate on a single control.
- Infinite speed adjustment.
- Minimum speed adjustment screw.
- Designed to fit a standard 3" x 5" electrical box.
- Mount in a dry location such as the control room.

		MODEL	MAX # OF FANS/CONTROL	VARIABLE SPEED OPERATION	POWER SUPPLY	AMPERAGE RATING		
		MC-3	2	Manual	120V/1/60HZ	2.5	HIGH	\sim
		MC-5	4			5		HIGH (/) L
		MC-10	8			10		
		MC-15	10			12		OFF
∛ CANARM [•]		FRMC5	4	Manual c/w Forward/Reverse Switch		5		⊘ ∛CANARN

CANARM LTD. - Corporate Office 2157 Parkedale Ave., PO Box 367 Brockville, ON Canada K6V 5V6 Tel: (613) 342-5424 Fax: 1-800-263-4598 Subject to change without notice. 11/17

CANARM LTD. - USA Warehouse 808 Commerce Park Drive Ogdensburg, New York, USA 13669 Tel: 1-800-267-4427 Fax: 1-800-263-4598

Arthur Manufacturing Facility #7686 Concession 16, RR 4 Arthur, ON Canada NOG 1A0 Tel: (519) 848-3910 Fax: (519) 848-3948

www.canarm.com

F-Mail: hvacsales@canarm.ca

6.875