

# KRUD KUTTER® TOUGH TASK REMOVER

### **DESCRIPTION AND USES**

Krud Kutter® Tough Task Remover is a water-based biodegradable, non-toxic cleaner designed to remove really tough soils quickly and effectively from many different surfaces. It can be used full strength or diluted with water for use on most indoor, outdoor, automotive and marine surfaces. It is color fast, fabric safe and leaves no residue.

It is formulated to safety and easily remove chewing gum, bumper stickers, labels, masking tape, most glues, marker and pen ink, dried latex paint, paint overspray, tape residue, fireplace soot, bird droppings, smoke damage, printer's ink, crayon, lipstick, shoe polish, tar and asphalt, brake dust, oil, grease, soap scum, mildew stains, scuff marks, candle wax, cosmetics, perspiration, food and drink stains, blood stains, pet stains, sun tan oil and more.

The heavy cleaning (full strength) removes dirt, oil, and grease from BBQ grills and ovens, hoods and exhaust fans, tubs, sinks and showers, tools and equipment, machinery, tile and grout, whitewalls, driveways, engines, and floor wax removal.

An all purpose formula (1½ cups of concentrate to 1 gallon of water) cleans and degreases appliances, mini-blinds, canvas, chrome, silver, brass, copper, porcelain, plastic, fiberglass, linoleum, aluminum, vinyl, patio furniture, walls and baseboards, carpets, upholstery, stainless steel and wheels.

For reflective surfaces such as computer and TV screens, glass mirrors, windows, display case, crystal, lights and car finishes, add 1½ ounces of concentrate to 1 gallon of water.

Krud Kutter is recommended for exterior siding (wood, vinyl, aluminum), roofing of all types (asphalt shingles, fiberglass shingles, cedar, tile), gutters, wood fences and decks, stucco, brick and cement block, masonry, concrete driveways, walkways and walls, RV's patio furniture and boats. Do not use on varnished surfaces or leather.

PRODUCTS	
Description	
8 oz. Flip Top Bottle	
12 oz. Foam Spray	
32 oz. Trigger Sprayer	
32 oz. Trigger Sprayer	
64 oz. Trigger Sprayer	
1-Gallon Bottle	
5-Gallons	

# PRODUCT APPLICATION

#### **DIRECTIONS**

Always test on an inconspicuous area first. Do not mix with other chemicals. For older, more difficult jobs, apply a generous amount of cleaner and allow to penetrate briefly. Wipe off with a clean cloth or towel.

## PRODUCT APPLICATION (cont.)

#### **DIRECTIONS**

For older, more difficult jobs apply a generous amount of cleaner and allow to stand for a few minutes before wiping dry. For extremely tough jobs, such as the removal of old, dried latex paint, scrub with a brush or scouring pad, and wash off with a wet rag. For engine cleaning, use on a cold dry engine. Do not mix this product with any other chemicals.

#### PRESSURE WASHER APPLICATION

Contains anti-corrosive agents to safeguard pressure washer parts (bleach can erode O-rings). Please be aware that water pressure alone may remove paint or highlight existing discoloration caused by sun exposure.

Rinse surrounding plants with water before and after application. Wet the surface to be cleaned prior to applying the product. Place detergent application siphon tube and screen filter directly into container. Open the meter valve (if applicable) for maximum product flow. For reservoir machines, pour product (full strength) into pressure washer. Spray at low pressure onto a wet surface. On vertical surfaces, always spray from the top down. Allow product to remain on the surface for 3 to 5 minutes to penetrate. Do not allow product to dry on surface. Remove siphon tube from solution and rinse surface with high-pressure spray thoroughly. Flush siphon tube with clean water prior to storage.

#### **CARPET CLEANING AND STAIN REMOVAL**

Krud Kutter Tough Task Remover is safe for all carpet types, including synthetic as well as stain resistant carpets. Test in an inconspicuous area first. The concentrated formula will clean six 9' x 12' (2.5m x4.0m) carpets. Coverage may vary depending on type and condition of carpet. Vacuum the carpet thoroughly. Pretreat any stubborn spots or stains by using the undiluted concentrate as a stain remover prior to cleaning carpet. Add concentrate to the receiving/waste tank of the machine to reduce buildup. Add 4 ounces of concentrate for each gallon of water in the dispensing/fill tank. For heavy traffic areas or heavily soiled carpets, add 6 ounces of concentrate for each gallon of water. Use hot (not boiling) or cold water according to the carpet manufacturer's cleaning directions. Read machine instructions carefully. Do not overfill.

**CAUTION! EYE AND SKIN IRRITANT.** In case of contact with eyes or skin, flush with water for at least 15 minutes. If irritation persists, seek medical attention. If swallowed, take large amounts of water. **Do not induce vomiting.** Get medical attention.

KEEP OUT OF REACH OF CHILDREN.

1

Form: GDH-532 Rev.: 032317



# **TECHNICAL DATA**

# KRUD KUTTER® TOUGH TASK REMOVER

# PHYSICAL PROPERTIES

	TOUGH TASK REMOVER
Composition	Proprietary Blend of Biodegradable Surfactants, Detergents and Emulsifiers
pH	<12.2
VOC	0%
Practical Coverage	Heavy Soils (Full Strength) – 200-300 sq.ft./gal.
	Medium Soils (10 to 1) – 2,200-3,300 sq.ft./gal.
	Light Soils (30 to 1) - 6,200-9,300 sq.ft./gal.
Shelf Life	NA
Flash Point	Non-flammable
Caution!	CAUTION! EYE AND SKIN IRRITANT. In case of contact with eyes or skin, flush with water for at least 15 minutes. If irritation persists, seek medical attention. If swallowed, take large amounts of water. Do not induce vomiting. Get medical attention.  KEEP OUT OF REACH OF CHILDREN.
Safety Information	For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Phone: 877•385•8155 www.rustoleum.com Form: GDH-532 Rev.: 032317