



**AUTO INTERIOR  
WATER REPELLING TREATMENT**

**DESCRIPTION AND USES**

Rust-Oleum® NeverWet® Auto Interior is a one-step, superhydrophobic, liquid repelling treatment designed to keep automobile fabrics dry longer. This crystal clear formula allows fabrics to breathe, while dramatically repelling liquids from the surface. NeverWet Auto Interior protects fabrics against damaging liquids and stains without changing the look or feel.

NeverWet Auto Interior is ideal for use on leather, cloth, and synthetic & natural fibers. It is suitable for use on automotive upholstery, floor mats, carpets and car seats.

**FEATURES**

- Repels liquids and stains
- Breathable
- Invisible protection

**PRODUCTS**

SKU (11 ounce spray)	Description
280884	NeverWet Auto Interior

**SPRAYING CONDITIONS**

Use outdoors or in a well ventilated area. Open all car doors during application. Use when temperature is above 50°F (10°C) and humidity is below 85% to ensure proper drying. Avoid spraying in very windy and dusty conditions.

**PRODUCT APPLICATION**

**SURFACE PREPARATION**

Apply to a clean, dry surface.

**PRODUCT APPLICATION (cont.)**

**APPLICATION**

Do not shake. A test spray is recommended to obtain a feel for the spray pattern. Test in an inconspicuous area before application for colorfastness. NeverWet Auto Interior may enrich light materials with a slightly darker tone. NeverWet Auto Interior is odorless when dry. Rotate nozzle to "ON" position. Spray coating 12-16" from the surface; coating the entire object until wet. Do not soak or allow to puddle. **NOTE:** If bubbles appear, lightly dab with a clean, lint-free rag. Re-apply periodically or when needed.

**DRY & RECOAT**

Dry and recoat times are based on 70°F and 50% relative humidity and will vary depending on fabric on the automotive interior. Allow to dry for 24 hours before exposing to liquids.

**COVERAGE**

Coverage will vary depending on the fabric: 50 square feet on smooth/light fabrics to 20 square feet on textured/heavy fabrics.

**CLEAN-UP**

When finished spraying, wipe off tip before storing. Properly discard empty container.

**TECHNICAL DATA****AUTO INTERIOR WATER REPELLING TREATMENT****PHYSICAL PROPERTIES**

		AUTO INTERIOR WATER REPELLING TREATMENT
Resin Type		Acrylic
Pigment Type		NA
Solvents		Water
Weight	Per Gallon	8.44 lbs.
	Per Liter	1.01 kg
Fill Weight		11 ounces
VOC		64 g/l (0.53 lbs./gal.)
Practical Coverage at Recommended DFT (assumes 15% material loss)		Coverage will vary depending on fabric 50 sq.ft. on smooth/light fabrics; 20 sq.ft. on textured/heavy fabrics
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity	Touch	Varies depending on fabric
	Handle	Varies depending on fabric
	Full Cure	Allow to dry 24 hours before exposing to liquids
Shelf Life		2 years
Flash Point		212°F (100°C)
Safety Information		For additional information, see MSDS.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.