## SAFETY DATA SHEET

Issuing Date 11-Apr-2019 Revision Date 11-Apr-2019 Revision Number 3



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

# 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

**Product identifier** 

Product Name 56V Battery 5.0AH

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use LITHIUM ION BATTERIES

Uses advised against No information available

Details of the supplier of the safety data sheet

**Supplier Name** Chervon North America, Inc.

**Supplier Address** 975 Cobb Place Blvd NW

Suite 214 Kennesaw GA 30144 US

Supplier Phone Number Phone:888-826-2285

Fax:770-514-7784

Supplier Email phartwick@chervon-na.com

Emergency telephone number

**Company Emergency Phone** 

Number .

336-209-2024

## 2. HAZARDS IDENTIFICATION

#### Classification

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200). This product is an article which is a sealed battery and as such does not require an MSDS per the OSHA hazard communication standard unless ruptured. The hazards indicated are for a ruptured battery.

Acute toxicity - Oral Category 4



Acute toxicity - Dermal	Category 4
Skin corrosion/irritation	Category 1 Sub-category B
Serious eye damage/eye irritation	Category 1
Skin sensitization	Category 1
Carcinogenicity	Category 1A
Specific target organ toxicity (repeated exposure)	Category 1

#### GHS Label elements, including precautionary statements

#### **Emergency Overview**

Signal word Danger

#### Hazard Statements

Harmful if swallowed

Harmful in contact with skin

Causes severe skin burns and eye damage

May cause an allergic skin reaction

May cause cancer

Causes damage to organs through prolonged or repeated exposure



This product is an article which contains a chemical substance. Safety information is given for exposure to the article as sold. Intended use of the product should not result in exposure to the chemical substance. This is a battery. In case of rupture: the above hazards exist. .

Appearance Green Physical state Solid Odor Odorless

#### **Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Do not breathe dust/fume/gas/mist/vapors/spray

Contaminated work clothing should not be allowed out of the workplace

Wear protective gloves

#### **Precautionary Statements - Response**

Specific treatment (see supplemental first aid instructions on this label)

Immediately call a POISON CENTER or doctor/physician

#### **Eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Immediately call a POISON CENTER or doctor/physician

#### Skin

Call a POISON CENTER or doctor/physician if you feel unwell

Wash contaminated clothing before reuse

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

If skin irritation or rash occurs: Get medical advice/attention



#### Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing Immediately call a POISON CENTER or doctor/physician

#### Ingestion

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

Rinse mouth

Do NOT induce vomiting

#### **Precautionary Statements - Storage**

Store locked up

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### **Hazards not otherwise classified (HNOC)**

Not applicable

#### **Unknown Toxicity**

15 % of the mixture consists of ingredient(s) of unknown toxicity

#### Other information

Very toxic to aquatic life with long lasting effects

Repeated or prolonged skin contact may cause allergic reactions with susceptible persons

#### **Interactions with Other Chemicals**

Use of alcoholic beverages may enhance toxic effects.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

.

Chemical name	CAS No.	Weight-%	Trade Secret
Supplier Trade Secret	Trade Secret	10 - 30	*
Supplier Trade Secret	Trade Secret	10 - 30	*
Supplier Trade Secret	Trade Secret	7 - 13	*
Supplier Trade Secret	Trade Secret	5 - 10	*
Supplier Trade Secret	Trade Secret	5 - 10	*

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret

## 4. FIRST AID MEASURES

#### First aid measures

**General Advice** First aid is upon rupture of sealed battery.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep

eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present

and easy to do. Continue rinsing. Seek immediate medical attention/advice.

**Skin contact** Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes. Seek immediate medical attention/advice. May cause an allergic skin

reaction. Remove and isolate contaminated clothing and shoes.

**(U)** 

**Inhalation** Remove to fresh air. If breathing has stopped, give artificial respiration. Get medical

attention immediately. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur. Get medical attention

immediately if symptoms occur.

Ingestion Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water. Never give

anything by mouth to an unconscious person. Call a physician or poison control center

immediately.

Self-protection of the first aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination. Avoid contact with skin, eyes or clothing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required. Wear personal protective clothing (see

section 8).

Most important symptoms and effects, both acute and delayed

**Most Important Symptoms and** 

**Effects** 

Itching. Rashes. Hives. Burning sensation.

Indication of any immediate medical attention and special treatment needed

**Notes to Physician** Product is a corrosive material. Use of gastric lavage or emesis is contraindicated.

Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood pressure may occur with moist rales, frothy sputum, and high pulse pressure. May cause

sensitization in susceptible persons. Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

**Suitable Extinguishing Media** 

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Dry chemical, CO2, water spray or regular foam. Move containers from fire area if you can do it without risk.

Large Fire Move containers from fire area if you can do it without risk.

Unsuitable extinguishing media

CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of irritating gases and vapors. Product is or contains a sensitizer. May cause sensitization by skin contact.

**Hazardous Combustion Products** 

Carbon oxides.

**Explosion Data** 

Sensitivity to Mechanical Impact No.

Sensitivity to Static Discharge No.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Move containers from fire area if you can do it without risk.



## 6. ACCIDENTAL RELEASE MEASURES

## Personal precautions, protective equipment and emergency procedures

Personal precautions Attention! Corrosive material. Avoid contact with skin, eyes or clothing. Ensure adequate

ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Do not touch or walk through spilled

material.

Other Information Refer to protective measures listed in Sections 7 and 8. ELIMINATE all ignition sources (no

smoking, flares, sparks or flames in immediate area).

**Environmental precautions** 

**Environmental precautions** Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage

if safe to do so. Should not be released into the environment. Do not allow to enter into

soil/subsoil. Prevent product from entering drains.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so. Absorb with earth, sand or other

non-combustible material and transfer to containers for later disposal.

**Methods for cleaning up** Pick up and transfer to properly labeled containers.

## 7. HANDLING AND STORAGE

## Precautions for safe handling

**Handling** In case of rupture: Handle in accordance with good industrial hygiene and safety practice.

Avoid contact with skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Use only with adequate ventilation and in closed systems. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash

before reuse.

Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from

moisture. Store locked up. Keep out of the reach of children. Store away from other

materials.

Incompatible Products Acids. Bases. Oxidizing agent.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Control parameters**

**Exposure Guidelines** The following ingredients are the only ingredients of the product above the cut-off level (or

level that contributes to the hazard classification of the mixture) which have an exposure limit applicable in the region for which this safety data sheet is intended or other

recommended limit. At this time, the other relevant constituents have no known exposure

#### limits from the sources listed here

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Supplier Trade Secret	TWA: 2.5 mg/m <sup>3</sup> F	TWA: 2.5 mg/m <sup>3</sup> F	IDLH: 250 mg/m <sup>3</sup> F
	_	(vacated) TWA: 2.5 mg/m <sup>3</sup>	-
Supplier Trade Secret	TWA: 0.02 mg/m <sup>3</sup> Co	-	
Supplier Trade Secret	TWA: 0.2 mg/m <sup>3</sup>	TWA: 1 mg/m³ Ni	IDLH: 10 mg/m <sup>3</sup> Ni
		(vacated) TWA: 1 mg/m³ Ni	TWA: 0.015 mg/m <sup>3</sup> except Nickel
			carbonyl Ni
Supplier Trade Secret	TWA: 0.2 mg/m³ fume	TWA: 0.1 mg/m³ fume	IDLH: 100 mg/m <sup>3</sup> dust, fume and mist
	_	TWA: 1 mg/m <sup>3</sup> dust and mist	TWA: 1 mg/m <sup>3</sup> dust and mist
		(vacated) TWA: 0.1 mg/m <sup>3</sup> Cu dust,	TWA: 0.1 mg/m <sup>3</sup> fume
		fume, mist	
Supplier Trade Secret	TWA: 1 mg/m³ respirable particulate	TWA: 15 mg/m³ total dust	TWA: 10 mg/m <sup>3</sup> total dust
	matter	TWA: 5 mg/m³ respirable fraction	TWA: 5 mg/m³ respirable dust
		(vacated) TWA: 15 mg/m³ total dust	
		(vacated) TWA: 5 mg/m³ respirable	
		fraction	

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits NIOSH IDLH Immediately Dangerous to Life or Health

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992) See section 15 for national exposure control parameters

**Appropriate engineering controls** 

Engineering Measures Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

**Eye/face protection** Face protection shield.

**Skin and body protection** Wear protective gloves and protective clothing. Long sleeved clothing. Chemical resistant

apron. Impervious gloves.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are

exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice. Avoid contact with

skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Take off contaminated clothing and wash before

reuse.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

#### **Physical and Chemical Properties**

Physical state Solid

Appearance Green Odor Odorless

Color No information available Odor Threshold No information available

Property <u>Values</u> <u>Remarks Method</u>

pH No data available None known



Melting / freezing pointNo data availableNone knownBoiling point / boiling rangeNo data availableNone knownFlash PointNo data availableNone knownEvaporation RateNo data availableNone knownFlammability (solid, gas)No data availableNone known

Flammability Limit in Air

Upper flammability limit
Lower flammability limit
No data available
No data available
No data available

Vapor pressureNo data availableNone knownVapor densityNo data availableNone knownSpecific GravityNo data availableNone known

Water Solubility Insoluble

Solubility in other solvents No data available None known

Partition coefficient: n-octanol/waterN/A

Autoignition temperatureNo data availableNone knownDecomposition temperatureNo data availableNone knownKinematic viscosityNo data availableNone knownDynamic viscosityNo data availableNone known

Explosive properties No data available Oxidizing properties No data available

**Other Information** 

Softening Point
VOC Content (%)
Particle Size
No data available
No data available
No data available

**Particle Size Distribution** 

## 10. STABILITY AND REACTIVITY

#### Reactivity

No data available.

#### **Chemical stability**

Stable under recommended storage conditions.

#### **Possibility of Hazardous Reactions**

None under normal processing.

#### **Hazardous Polymerization**

Hazardous polymerization does not occur.

#### Conditions to avoid

Exposure to air or moisture over prolonged periods.

#### **Incompatible materials**

Acids. Bases. Oxidizing agent.

#### **Hazardous Decomposition Products**

Carbon oxides.

## 11. TOXICOLOGICAL INFORMATION

## Information on likely routes of exposure



**Product Information** Product does not present an acute toxicity hazard based on known or supplied information.

In case of rupture:.

**Inhalation** Specific test data for the substance or mixture is not available. Corrosive by inhalation.

(based on components). Inhalation of corrosive fumes/gases may cause coughing, choking, headache, dizziness, and weakness for several hours. Pulmonary edema may occur with tightness in the chest, shortness of breath, bluish skin, decreased blood pressure, and increased heart rate. Inhaled corrosive substances can lead to a toxic edema of the lungs.

Pulmonary edema can be fatal. May cause irritation of respiratory tract.

**Eye contact** Specific test data for the substance or mixture is not available. Causes burns. (based on

components). Corrosive to the eyes and may cause severe damage including blindness.

Causes serious eye damage. May cause irreversible damage to eyes.

**Skin contact** Specific test data for the substance or mixture is not available. Corrosive. (based on

components). Causes burns. May be absorbed through the skin in harmful amounts.

Harmful in contact with skin.

**Ingestion** Specific test data for the substance or mixture is not available. Causes burns. (based on

components). Ingestion causes burns of the upper digestive and respiratory tracts. May cause severe burning pain in the mouth and stomach with vomiting and diarrhea of dark blood. Blood pressure may decrease. Brownish or yellowish stains may be seen around the mouth. Swelling of the throat may cause shortness of breath and choking. May cause lung damage if swallowed. May be fatal if swallowed and enters airways. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea,

vomiting and diarrhea. Harmful if swallowed.

#### **Component Information**

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Supplier Trade Secret	= 159 mg/kg (Rat) = 202 mg/kg ( Rat)	-	-
Supplier Trade Secret	> 5000 mg/kg (Rat)	-	-

#### Information on toxicological effects

**Symptoms** Erythema (skin redness). Burning. May cause blindness. Coughing and/ or wheezing.

Itching. Rashes. Hives.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Sensitization** May cause sensitization by skin contact. May cause sensitization in susceptible persons.

Mutagenic Effects No information available.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Supplier Trade Secret	A3	Group 2B	Reasonably Anticipated	Х
Supplier Trade Secret	A1	Group 1	Known	Х

### Legend:

ACGIH (American Conference of Governmental Industrial Hygienists)

A1 - Known Human Carcinogen

A3 - Animal Carcinogen



IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

NTP (National Toxicology Program)

Known - Known Carcinogen

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity No information available.

**STOT - single exposure** No information available.

STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure. Based on

classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from

chronic or repeated exposure. (STOT RE).

Chronic Toxicity Chronic exposure to corrosive fumes/gases may cause erosion of the teeth followed by jaw

necrosis. Bronchial irritation with chronic cough and frequent attacks of pneumonia are common. Gastrointestinal disturbances may also be seen. Contains a known or suspected carcinogen. Avoid repeated exposure. Prolonged exposure may cause chronic effects. May

cause adverse liver effects.

Target Organ Effects Respiratory system. Eyes. Skin. Gastrointestinal tract (GI). Central Vascular System (CVS).

Kidney. Liver. Lungs. Nasal cavities. Blood. Digestive System. Endocrine system. Heart.

Thyroid.

**Aspiration Hazard** No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 847.50 mg/kg ATEmix (dermal) 1,214.30 mg/kg (ATE)



Revision Date 11-Apr-2019 1237913 - 56V Battery 5.0AH

## 12. ECOLOGICAL INFORMATION

### **Ecotoxicity**

Harmful to aquatic life. Very toxic to aquatic life with long lasting effects.

Chemical name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Supplier Trade Secret	72h EC50: > 127.3 mg/L	96h LC50: > 100 mg/L		48h EC50: > 100 mg/L
	(Pseudokirchneriella	(Brachydanio rerio)		
	subcapitata)			
Supplier Trade Secret	96h EC50: 0.031 - 0.054	96h LC50: 0.0068 - 0.0156		48h EC50: = 0.03 mg/L
	mg/L (Pseudokirchneriella	mg/L (Pimephales promelas)		
	subcapitata) 72h EC50:	96h LC50: < 0.3 mg/L		
	0.0426 - 0.0535 mg/L	(Pimephales promelas) 96h		
	(Pseudokirchneriella	LC50: = 0.2 mg/L		
	subcapitata)	(Pimephales promelas) 96h		
		LC50: = 0.3 mg/L (Cyprinus		
		carpio) 96h LC50: = 0.052		
		mg/L (Oncorhynchus		
		mykiss) 96h LC50: = 1.25		
		mg/L (Lepomis macrochirus)		
		96h LC50: = 0.112 mg/L		
		(Poecilia reticulata) 96h		
		LC50: = 0.8 mg/L (Cyprinus		
		carpio)		

## <u>Persistence and Degradability</u> No information available.

## **Bioaccumulation**

No information available

Other adverse effects
No information available.

Page 10/14

Revision Date 11-Apr-2019 1237913 - 56V Battery 5.0AH

## 13. DISPOSAL CONSIDERATIONS

#### Waste treatment methods

Disposal methods This material, as supplied, is not a hazardous waste according to Federal regulations (40

> CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local

regulations for additional requirements.

**Contaminated Packaging** Dispose of contents/containers in accordance with local regulations.

California Waste Codes 141

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste
Supplier Trade Secret	Toxic
Supplier Trade Secret	Toxic
Supplier Trade Secret	Ignitable powder

## 14. TRANSPORT INFORMATION

Note:

The transportation of primary lithium cells and batteries is regulated by the International Civil Aviation Organization, International Air Transport Association, International Maritime Dangerous Goods Code and the US Department of Transportation. The batteries must meet the following criteria for shipment: 1. Air shipments must meet the requirements listed in Special Provision A45 of the International Air Transport Association Dangerous Goods Regulations. 2. Meet the requirements for the US Department of Transportation listed in 49 CFR 173.185. 3. The transport of primary lithium batteries is prohibited aboard passenger aircraft. Refer to the Federal Register December 15, 2004 (Hazardous Materials; Prohibited on the Transportation of Primary Lithium Batteries and Cells Aboard Passenger Aircraft; Final Rule)

Lithium batteries shipped as "Lithium batteries", "Lithium batteries packed with equipment", or "Lithium batteries contained in equipment" may not be classified as "Dangerous Goods" when shipped in accordance with "special provision A45 of IATA-DGR" or "special provision 188 of IMO-IMDG Code"

NOT REGULATED DOT **Proper Shipping Name** NON REGULATED

**Hazard Class** N/A **Emergency Response Guide** 147

Number

UN-No. UN3480

**Proper Shipping Name** LITHIUM ION BATTERIES

**Hazard Class** 

Description UN3480, LITHIUM ION BATTERIES, 9

MEX

TDG

UN-No. UN3480

**Proper Shipping Name** LITHIUM ION BATTERIES



Hazard Class 9

**Description** UN3480, LITHIUM ION BATTERIES, 9

**ICAO** 

**UN-No.** UN3480

Proper Shipping Name LITHIUM ION BATTERIES

Hazard Class 9

**Description** UN3480, LITHIUM ION BATTERIES, 9

IATA

**UN-No.** UN3480

Proper Shipping Name LITHIUM ION BATTERIES

Hazard Class 9

**Description** UN3480, LITHIUM ION BATTERIES, 9

IMDG/IMO

**UN-No.** UN3480

Proper Shipping Name LITHIUM ION BATTERIES

Hazard Class 9

**EmS-No.** F-A, S-

**Description** UN3480, LITHIUM ION BATTERIES, 9

RID

**UN-No.** UN3480

Proper Shipping Name LITHIUM ION BATTERIES

Hazard Class 9

Classification code M4

**Description** UN3480, LITHIUM ION BATTERIES, 9

<u>ADR</u>

**UN-No.** UN3480

Proper Shipping Name LITHIUM ION BATTERIES

Hazard Class 9
Classification code M4
Tunnel restriction code (E)

**Description** UN3480, LITHIUM ION BATTERIES, 9

ADN

**UN-No.** UN3480

Proper Shipping Name LITHIUM ION BATTERIES

Hazard Class 9
Classification code M4

**Special Provisions** 188, 230, 310, 348, 636, 661

**Description** UN3480, LITHIUM ION BATTERIES, 9

Limited Quantity 0

## 15. REGULATORY INFORMATION

#### **International Inventories**

TSCA Not determined DSL Not determined

IECSC -

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

## **US Federal Regulations**

#### **SARA 313**



Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No.	Weight-%	SARA 313 - Threshold Values %
Supplier Trade Secret -		10 - 30	0.1
Supplier Trade Secret -		7 - 13	0.1
Supplier Trade Secret -		5 - 10	1.0
Supplier Trade Secret -		5 - 10	1.0

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications. Under the amended regulations at 40 CFR 370, EPCRA 311/312 Tier II reporting for the 2017 calendar year will need to be consistent with updated hazard classifications.

### **CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Supplier Trade Secret		Х		
Supplier Trade Secret		X	Х	

### CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Supplier Trade Secret	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Supplier Trade Secret			

## **US State Regulations**

### **California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65
Supplier Trade Secret -	Developmental
Supplier Trade Secret -	carcinogen, 7/1/1992
Supplier Trade Secret -	Carcinogen

#### **U.S. State Right-to-Know Regulations**

This product may contain substances regulated by state right-to-know regulations.

Chemical name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Supplier Trade Secret	X				
Supplier Trade Secret	Х	Х		Х	
Supplier Trade Secret	Х		Х	Х	Х
Supplier Trade Secret	Х	Х	Х	Х	Х
Supplier Trade Secret	Х	Х	Х	Х	
Supplier Trade Secret	Х	Х	Х	Х	Х



#### International Regulations

#### Mexico

National occupational exposure limits

Chemical name	Carcinogen Status	Exposure Limits
Supplier Trade Secret		Mexico: TWA= 1 mg/m <sup>3</sup>
		Mexico: TWA= 0.2 mg/m <sup>3</sup>
		Mexico: STEL= 2 mg/m <sup>3</sup>
Supplier Trade Secret		Mexico: TWA 10 mg/m <sup>3</sup>

Mexico - Occupational Exposure Limits - Carcinogens

#### Canada

#### **WHMIS Hazard Class**

Non-controlled

16. OTHER INFORMATION

NFPA Health Hazards 1 Flammability 0 Instability 0 Physical and Chemical Hazards - HMIS Health Hazards 0 Flammability 0 Physical Hazard 0 Personal Protection

Prepared By Product Stewardship

23 British American Blvd. Latham, NY 12110 1-800-572-6501

Issuing Date11-Apr-2019Revision Date11-Apr-2019

Revision Note No information available

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet** 

