



AIRGUARD

Premium Underlayment



For use under Laminate and Engineered Wood Flooring



The only underlayment that includes

PROTECTION THAT LIVES ON
MICROBAN



Featuring
Air Flow Technology
Air ventilation fights damage caused by trapped moisture

MADE IN USA



PROTECTION

4" film overlap for and adhesive strip seal out moisture for added protection

- 1 PREMIUM CUSHIONING**
Makes flooring softer to walk on
- 2 SOUND REDUCTION**
Provides deep, rich sound
- 3 MOISTURE PROTECTION**
Protects floors from moisture vapor
- 4 MOLD PROTECTION**
Constant air movement inhibits mold growth
- 5 RADIANT HEAT**
Added R-Value to chilly floors

SPECIFICATIONS

ITEM #	70-105-1
UNIT OF MEASURE	Roll
COVERAGE	630 sq. ft. per roll
WIDTH OF ROLL	40"
LENGTH OF ROLL	189 ft. (2268")
THICKNESS	2 mm (1/8")
WEIGHT PER ROLL	21 lbs.
DIAMETER OF ROLL	16-1/2"

TECHNICAL SPECIFICATIONS

IIC (Impact Sound Transmission Test)	68
STC (Sound Transmission Loss Test)	67
ΔDelta IIC	20.0
R-Value**	0.39

IIC measures sound such as moving furniture and walking, STC measures sound such as voices and television. Minimum sound rating required by most building codes and architects is 50. R-Value is the rating used to measure resistance to heat flow. ΔDelta Rating is the only true measurement of sound reduction from a product (not a floor assembly) in the industry.

*Compression Test Results - In a standardized test using 1,320 lbs. of pressure, ROBERTS Airguard Underlayment retained 96% of its original thickness after seven days, compared to only 57% by a leading 2-in-1 foam product.

Quality & Excellence Since 1938.

www.ROBERTSCONSOLIDATED.com

U.S. Headquarters
866 435 8665

Canada
800 840 9422

Europe/Middle East
0031 24 6485348

Australia
011 61 3 9797 1888

New Zealand
64 9 415 9700

N0618-11170