

Quick Color™ Sprays

DESCRIPTION A fast dry, VOC compliant all-purpose spray. A basic paint for a variety of quick jobs around the house.

APPEARANCE Flat and Gloss topcoats and primer.

RECOMMENDED PRIMER 2857 Gray Primer

PHYSICAL PROPERTIES (Calculated values are shown and may vary slightly from the actual manufactured material)

RESIN TYPE Acrylic Modified Alkyd.

SOLVENTS Naphtha, Xylene, Acetone

VOLATILE ORGANIC COMPOUNDS Maximum 65%

PRACTICAL COVERAGE Approximately 6 sq. ft./can (.54 M²/can)

DRY TIMES @ 70°F (21°C) and 50% RH

Tack Free 30 minutes

Handle 1 hour

Recoat Within 1 hour or after 24 hours. (Primer can be topcoated anytime)
(Lower temperatures or high humidity will extend dry times)

DRY HEAT RESISTANCE 200°F (94° C)

SHELF LIFE 5 Years

PACKAGING 10 oz can

SURFACE PREPARATION Remove all dirt, grease, oil, salt or other contaminants by washing the surface with detergent or other suitable cleaner. Rinse thoroughly with fresh water and allow to fully dry.

Scrape and wire brush or power tool clean to remove loose rust, scale, and deteriorated coatings. Scarify previously painted coatings or smooth surfaces to promote adhesion. Test for compatibility with existing coating.

Use in properly ventilated area. Spraying can produce a fog that will travel. Protect surrounding area, clothing and skin for overspray.

APPLICATION Apply only when air and surface temperatures are above 50°F (10°C) and humidity is less than 85% to ensure proper drying. Use outdoors or in areas with good ventilation.

Apply two or more light coats a few minutes apart.