

Irrigation Timer - Sprinkler/Irrigation Time Switch with 14-Day Skipper

Item T8845PV



PRODUCT DESCRIPTION

These irrigation timers are designed to permit one to 44 "ON" operations every 24 hours and provide watering increments down to 12 minutes or up to 20 hours and 45 minutes to ensure proper watering increments. These models also allow for biweekly scheduling with the convenient 14-day skipper for maximum water conservation and odd/even day compliance. These irrigation timers are designed to permit one to 44 "ON" operations every 24 hours and provide watering increments down to 12 minutes or up to 20 hours and 45 minutes to ensure proper watering increments. These models also allow for biweekly scheduling with the convenient 14-day skipper for maximum water conservation and odd/even day compliance.

FEATURES

- ▶ Up to 44 ON/OFF settings per day
- ▶ Water metering increments from 12 minutes to 20 hours and 45 minutes
- ▶ 14-Day skipper enables irrigation to be omitted on selected day(s)
- ▶ Provides for every other day operation
- ▶ ON/OFF/AUTO switch enables shutdown during rainy days and extended watering during dry periods without disturbing the cycle set on dial
- ▶ Type 3R plastic indoor/outdoor enclosure
- ▶ Up to 44 ON/OFF settings per day
- ▶ Water metering increments from 12 minutes to 20 hours and 45 minutes
- ▶ 14-Day skipper enables irrigation to be omitted on selected day(s)
- ▶ Allows for alternate-day scheduling
- ▶ ON/OFF/AUTO switch enables shutdown during rainy days and extended watering during dry periods without disturbing the cycle set on dial
- ▶ Type 3R plastic indoor/outdoor enclosure

APPLICATIONS

- ▶ Multi-Station Hydro-Indexing Valves
- ▶ Greenhouses, Lawn Sprinklers
- ▶ Irrigation Control
- ▶ Drip Irrigation Systems

TECHNICAL DATA

General

Model Number	T8845PV
Description	Sprinkler/Irrigation Time Switch with 14-Day Skipper
UPC Code	078275700741
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty	1-Year limited

Control Specifications

Minimum ON/OFF Times	12 min
Maximum ON/OFF Times	20 hours, 45 minutes
Maximum ON/OFF Operations	44
Tripper Actuating Time	12 min
Mechanism Type	Analog/Mechanical

Mechanical Specifications

Enclosure Type	Indoor/outdoor type 3R plastic
Number of Trippers Included	12

Dimensions

Product Dimensions (H x W x D) in	10 x 6.5 x 4 in
-----------------------------------	-----------------

Load Ratings

Motor	24 VAC, 60 Hz
Clock Motor Voltage	110/125 VAC, 60 Hz

Electrical Specifications

Switch Type	SPST
Load Voltage	24 VAC, 60 Hz
Amps (per pole)	20 VA

Packaging

Shipping Weight (lbs)	3.243
Unit Carton Dimensions (H x W x L) in	4.25 x 7.31 x 11.75 in

Environmental Specifications

Temperature (operation)	-40 °F to 130 °F / (-40 °C to 54 °C)
-------------------------	--------------------------------------

Standards and Certifications

CSA Certification	cCSAus
California Proposition 65	Lead

ACCESSORIES




156T1950A

Set of 12 Trippers for T1900, T2000, C8800, R8800 and T8800 Series



133T700A

Micro Switch for T8800 and R8800 Series



156T1954A

14 Skipper Pins for R8800, and T8800 Series



T104-20

Mechanical Water Heater Time Switch