

**LIQUID
NAILS®**
ADHESIVE

HEAVY DUTY

CONSTRUCTION ADHESIVE

LN-901/LNP-901

Interior & Exterior

A premium, versatile adhesive that creates a strong bond that will outlast your project.

**100%
SATISFACTION
GUARANTEED!**

PRODUCT DESCRIPTION

LIQUID NAILS® Heavy Duty Construction Adhesive, LN-901/LNP-901, bridges gaps, provides 10 minutes working time and produces a durable, flexible, and impact-resistant bond on the heaviest materials. With antioxidants added for superior all-weather performance.

RECOMMENDED FOR bonding common building materials (concrete, lumber, etc.) to:

- Plywood and waferboard*
- Treated lumber
- Drywall
- Brick veneers
- Tileboard
- Exterior foamboard
(when applied below 90°F)

*See installation instructions or www.liquidnails.com

NOT RECOMMENDED FOR flooring applications, ceramics, mirrors, granite, marble (real or cultured), plastic, vinyl, ceiling tile, subfloors/underlayment, or 1/8" medium density fiberboard paneling.

Please research all installation instructions and read entire label for safety, health & environmental information prior to use.

Look for other LIQUID NAILS products which are right for your specific project.

PRODUCT ADVANTAGES

- Strong bond will outlast project
- Bonds a wide range of construction materials
- 100% Satisfaction Guaranteed
- Exceptional holding power
- Waterproof & Weatherproof
- Interior & Exterior
- Strong, Durable and Flexible
- Exceeds ASTM C-557

DANGER! EXTREMELY FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. VAPORS MAY CAUSE FLASH FIRE.

Read Label and Material Safety Data Sheet Prior to Use.
See other cautions on last page. MDSF3-1100



DIRECTIONS:

Preparation: Surfaces must be clean, dry and structurally sound.

1. Cut nozzle at a 45° angle to desired size.
2. Puncture inner seal with nail or wire.

Cabinets and counter tops: Apply a 1/4" bead to contact areas on the back of cabinets or counter tops. Press firmly into place. Mechanical fasteners must also be used for installing wall cabinets.

Materials to furring strips or studs: Apply zigzag 1/4" bead to each strip or stud to be covered by panel. Position panel so edges meet at stud center; only severely warped materials require finishing nails at top and bottom.

CLEAN-UP

Use mineral spirits or an adhesive remover.

DISPOSAL

Contains organic solvents which may cause adverse effects to the environment if disposed of improperly. Place empty containers in normal refuse for disposal. Contact your sanitation department or household hazardous waste coordinator for information concerning possible re-use or disposal of unused solvent-containing adhesives and/or sealants. EAD-C9

LIMITED WARRANTY

Macco warrants satisfaction with this product when handled and applied according to label instructions. If this product is not as warranted, please call 1-800-634-0015 for refund or product replacement details. This warranty excludes labor or the cost of labor and is given as the exclusive warranty and remedy. No warranty of merchantability, fitness for purpose or other warranty, express or implied, is made. Macco shall not be liable for any special, incidental or consequential damages. Some states do not allow the exclusion of incidental or consequential damages, so the limitations may not apply. This warranty gives specific legal rights. You may also have other rights that vary from state to state.

DANGER! EXTREMELY FLAMMABLE.

CAUSES EYE AND SKIN BURNS. HARMFUL OR FATAL IF SWALLOWED. HARMFUL IF INHALED. MAY CAUSE CENTRAL NERVOUS SYSTEM EFFECTS, INCLUDING DIZZINESS, HEADACHE OR NAUSEA. CAUSES RESPIRATORY TRACT IRRITATION. USE ONLY WITH ADEQUATE VENTILATION. KEEP OUT OF THE REACH OF CHILDREN.

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Contains Crystalline Silica. If sanding, wear a dust mask to avoid breathing of sanding dust. Keep away from heat, sparks and flame. **Do not smoke. Vapors may ignite explosively.** Vapors may spread long distances. Extinguish all flames, burners, stoves, heaters and pilot lights and disconnect all electrical motors and appliances before use and until all vapors are gone. Do not breathe vapors. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Avoid contact with eyes and skin. Close container after use. **FIRST AID:** For skin contact, wash thoroughly with soap and water. If any product remains, gently rub with petroleum jelly, vegetable or mineral/baby oil, then wash again with soap and water. Repeat as needed. Remove contaminated clothing. For eye contact, flush immediately with plenty of water for at least 15 minutes. **Get medical attention.** If swallowed, **get medical attention immediately.** If inhalation causes physical discomfort, remove to fresh air. If discomfort persists or any breathing difficulty occurs, get medical attention. **For emergency information, customer service, MSDS or additional safety and chronic hazard information, call 1-800-634-0015. KEEP FROM FREEZING.** MDS63-1006

LN-901/LNP-901
TECHNICAL INFORMATION

Base: Synthetic rubber & resin

Type: Solvent

Color: Tan

Appearance: Smooth

Application Temperature:
40° to 100° F (5° to 38° C)

Service Temperature:
-20° to 140° F (-29° to 60° C)

Adhesion: Excellent

Consistency: Short buttery

Bridging Ability: Excellent

Extrudability: Easy

Shear Strength:

24 hours – 225 psi

48 hours – 300 psi

7 days – >425 psi

Durability: Excellent; 20 year life

Flexibility: Excellent

Water Resistance: Excellent

Exterior Weathering: Very good;
adhesive not recommended
for direct exposure to sunlight

Staining: May stain marble

Odor: Mild solvent

Working Time: 10 minutes

Weight Per Gallon: 9.4 pounds (1.12 kg/l)

Viscosity: 230,000 CPS

Volatiles: 35%

Solids: 65%

Flammability: Extremely flammable;
nonflammable when dry

Flash Point: 1°F (-17°C)

Coverage:

30 lineal ft. using 1/4" bead for 10 fl.oz.;

85 lineal ft. using 1/4" bead for 28 fl.oz.

Shelf Life: 12 months from date of purchase

Specifications: Exceeds ASTM C-557

MAX VOC: 401 GPL



15885 West Sprague Rd.
Strongsville, OH 44136

www.liquidnails.com

Customer Service 1-800-634-0015