



Buy it for looks. Buy it for life.®

# Specifications

## FAUCET DESCRIPTION

- Metal construction with various finishes identified by suffix
- High arc spout provides the height and reach to fill or clean large pots
- 2 or 4 hole-mount
- Flexible supply lines with 3/8" compression fittings
- 360° rotating spout
- Includes hose and side spray
- Duralock™ Quick Connect Installation

## OPERATION

- Single handle lever
- Temperature controlled by 100° arc of handle travel

## FLOW

- Aerator is limited to 1.5 gpm max (5.7 L/min)

## CARTRIDGE


- 1255™ Duralast™ cartridge
- Nonmetallic/nonferrous and stainless steel material

## STANDARDS

- Third party certified to ASME A112.18.1/CSA B-125.1 and all applicable requirements referenced therein
- Certified to NSF 61/9 & 372
- Meets CalGreen and Georgia SB370 requirements
- Complies with California Proposition 65 and with the Federal Safe Drinking Water Act
- ADA ♿ for lever handle

## WARRANTY

- Lifetime limited warranty against leaks, drips and finish defects to the original homeowner
  - 10 year limited warranty when used in a multifamily installation
  - 5 year limited warranty when used in a commercial installation
- Visit [www.moen.com/support](http://www.moen.com/support) for complete details and limitations



## Noell™ Single Handle High Arc Kitchen Faucet with Side Spray

Model: 87506 series

**NOTE:** THIS FAUCET IS DESIGNED TO BE INSTALLED THROUGH 2 OR 4 HOLES: 1-1/2" (38MM) MIN. DIA. HOLES FOR VALVE AND DECK PLATE (IF INSTALLED) AND A 1-1/4" (32MM) MIN. DIA. HOLE FOR SIDE SPRAY

4 HOLES ON 4" CENTERS  
WHEN INSTALLED WITH DECK PLATE  
2 HOLES ON 8" CENTERS  
WHEN INSTALLED WITHOUT PLATE

