

**SAFETY DATA SHEET**  
**KLEAN STRIP PAINT STRIPPER AFTER**  
**WASH**

Page: 1  
Printed: 04/20/2015  
Revision: 04/20/2015  
Supersedes Revision: 03/05/2015

**1. PRODUCT AND COMPANY IDENTIFICATION**

**Product Name:** KLEAN STRIP PAINT STRIPPER AFTER WASH  
**Company Name:** W. M. Barr  
2105 Channel Avenue  
Memphis, TN 38113  
**Phone Number:** (901)775-0100  
**Web site address:** www.wmbarr.com  
**Emergency Contact:** 3E 24 Hour Emergency Contact (800)451-8346  
**Information:** W.M. Barr Customer Service (800)398-3892  
**Intended Use:** Surface cleaner and conditioner  
**Synonyms:** QKSW94341  
**Additional Information** This product is regulated by the United States Consumer Product Safety Commission and is subject to certain labeling requirements under the Federal Hazardous Substances Act. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS). The product label also includes other important information, including directions for use, and should always be read in its entirety prior to using the product.

**2. HAZARDS IDENTIFICATION**

**Flammable Liquids, Category 2**  
**Acute Toxicity: Oral, Category 4**  
**Acute Toxicity: Skin, Category 3**  
**Acute Toxicity: Inhalation, Category 4**  
**Skin Corrosion/Irritation, Category 2**  
**Serious Eye Damage/Eye Irritation, Category 2A**  
**Specific Target Organ Toxicity (single exposure), Category 1**  
**Aspiration Toxicity, Category 1**



**GHS Signal Word:** **Danger**  
**GHS Hazard Phrases:** H225: Highly flammable liquid and vapor.  
H302: Harmful if swallowed.  
H304: May be fatal if swallowed and enters airways.  
H311: Toxic in contact with skin.  
H315: Causes skin irritation.  
H319: Causes serious eye irritation.  
H332: Harmful if inhaled.  
H370: Causes damage to organs.  
**GHS Precaution Phrases:** P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P233: Keep container tightly closed.  
P240: Ground/bond container and receiving equipment.  
P241: Use explosion-proof electrical/ventilating/lighting equipment.  
P242: Use only non-sparking tools.  
P243: Take precautionary measures against static discharge.  
P260: Do not breathe gas/mist/vapors/spray.  
P264: Wash hands thoroughly after handling.  
P270: Do not eat, drink or smoke when using this product.  
P271: Use only outdoors or in a well-ventilated area.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
**GHS Response Phrases:** P301+310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

# SAFETY DATA SHEET

## KLEAN STRIP PAINT STRIPPER AFTER WASH

Printed: 04/20/2015

Revision: 04/20/2015


Supersedes Revision: 03/05/2015

P312: Call a POISON CENTER or doctor/physician if you feel unwell.  
 P302+352: IF ON SKIN: Wash with plenty of soap and water.  
 P303+361+353: IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.  
 P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
 P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P307+311: IF exposed: Call a POISON CENTER or doctor/physician.  
 P321: Specific treatment see label.  
 P330: Rinse mouth.  
 P331: Do NOT induce vomiting.  
 P332+313: If skin irritation occurs, get medical advice/attention.  
 P337+313: If eye irritation persists, get medical advice/attention.  
 P361: Remove/Take off immediately all contaminated clothing.  
 P363: Wash contaminated clothing before reuse.  
 P370+378: In case of fire, use dry chemical powder to extinguish.  
 P403+235: Store in cool/well-ventilated place.  
 P405: Store locked up.  
 P501: Dispose of contents/container according to local, state and federal regulations.

### GHS Storage and Disposal Phrases:

### Hazard Rating System:

HEALTH	*	2
FLAMMABILITY	3	3
PHYSICAL	0	0
PPE	X	X



### HMIS:

### OSHA Regulatory Status:

This material is classified as hazardous under OSHA regulations.

### Potential Health Effects (Acute and Chronic):

#### Inhalation Acute Exposure Effects:

Vapor harmful. May cause dizziness; headache; watering of eyes; irritation of respiratory tract; weakness; drowsiness; nausea; numbness in fingers, arms and legs; depression of central nervous system; loss of appetite; fatigue; hallucinations; light headedness; visual disturbances; giddiness and intoxication; sleepiness; cough and dyspnea; cold, clammy extremities; diarrhea; vomiting; dilation of pupils; spotted vision. Severe overexposure may cause convulsions; unconsciousness; coma; and death. Intentional misuse of this product by deliberately concentrating and inhaling can be harmful or fatal.

#### Skin Contact Acute Exposure Effects:

May be absorbed through the skin. May cause irritation; numbness in the fingers and arms; drying of skin; and dermatitis. May cause increased severity of symptoms listed under inhalation.

#### Eye Contact Acute Exposure Effects:

This material is an eye irritant. May cause irritation; burns; conjunctivitis of eyes; and corneal ulcerations of the eye. Vapors may irritate eyes.

#### Ingestion Acute Exposure Effects:

Poison. Cannot be made non-poisonous. May be fatal or cause blindness. May cause dizziness; headache; nausea; vomiting; burning sensation in mouth, throat, and stomach; loss of coordination; depression of the central nervous system; narcosis; stupor; gastrointestinal irritation; liver, kidney, and heart damage; diarrhea; loss of appetite; coma and death. May produce symptoms listed under inhalation.

#### Chronic Exposure Effects:

**SAFETY DATA SHEET**  
**KLEAN STRIP PAINT STRIPPER AFTER**  
**WASH**

Page: 3  
Printed: 04/20/2015  
Revision: 04/20/2015  
Supersedes Revision: 03/05/2015

Reports have associated repeated and prolonged overexposure to solvents with neurological and other physiological damage. Prolonged or repeated contact may cause dermatitis. Prolonged skin contact may result in absorption of a harmful amount of this material. May cause conjunctivitis; gastric disturbances; insomnia; dizziness; headache; weakness; fatigue; nausea; heart palpitations; skin irritation; numbness in hands and feet; permanent central nervous system changes; some loss of memory; pancreatic damage; giddiness; visual impairment or blindness; kidney or liver damage; and death. May cause symptoms listed under inhalation.

**Medical Conditions Generally Aggravated By Exposure:** Diseases of the skin, eyes, liver, kidneys, central nervous system, cardiovascular system, and respiratory system.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS #	Hazardous Components (Chemical Name)	Concentration	RTECS #
67-64-1	Acetone {2-Propanone}	40.0 -60.0 %	AL3150000
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	20.0 -40.0 %	ZE2100000
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	10.0 -20.0 %	PC1400000
100-41-4	Ethylbenzene {Ethylbenzol; Phenylethane}	<10.0 %	DA0700000

**Additional Chemical Information** Specific percentage of composition is being withheld as a trade secret.

### 4. FIRST AID MEASURES

**Emergency and First Aid Procedures:** Inhalation:  
If user experiences breathing difficulty, move to air free of vapors, Administer oxygen or artificial medical assistance can be rendered.

Skin Contact:  
Wash with soap and large quantities of water and seek medical attention if irritation from contact persists.

Eye Contact:  
Flush with large quantities of water for at least 15 minutes and seek immediate medical attention.

Ingestion:  
Call your local poison control center, hospital emergency room or physician immediately for instructions to induce vomiting.

**Signs and Symptoms Of Exposure:** Primary Routes of Exposure:  
Inhalation, ingestion and dermal.

**Note to Physician:** Poison. This product contains methanol. Methanol is metabolized to formaldehyde and formic acid. These metabolites may cause metabolic acidosis, visual disturbances and blindness. Since metabolism is required for these toxic symptoms, their onset may be delayed from 6 to 30 hours following ingestion. Ethanol competes for the same metabolic pathway and has been used as an antidote. Methanol is effectively removed by hemodialysis. Call your local poison control center for further information.

**SAFETY DATA SHEET**  
**KLEAN STRIP PAINT STRIPPER AFTER**  
**WASH**

Page: 4  
Printed: 04/20/2015  
Revision: 04/20/2015  
Supersedes Revision: 03/05/2015

**5. FIRE FIGHTING MEASURES**

**Flammability Classification:** Class IB  
**Flash Pt:** 20.00 F Method Used: TAG Open Cup  
**Explosive Limits:** LEL: 1.00 UEL: No data.  
**Autoignition Pt:** No data.  
**Suitable Extinguishing Media:** Use carbon dioxide, dry powder, or foam.  
**Fire Fighting Instructions:** Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from heads of containers that have been exposed to intense heat or flame.  
**Flammable Properties and Hazards:** No data available.

**6. ACCIDENTAL RELEASE MEASURES**

**Steps To Be Taken In Case Material Is Released Or Spilled:** Clean up:  
Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut off ignition sources; keep flares, smoking or flames out of hazard area.  
  
Small spills:  
Take up with sand, earth or other noncombustible absorbent material and place in a plastic container where applicable.  
  
Large spills:  
Dike far ahead of spill for later disposal.  
  
Waste Disposal:  
Dispose in accordance with applicable local, state and federal regulations.

**7. HANDLING AND STORAGE**

**Precautions To Be Taken in Handling:** Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.  
**Precautions To Be Taken in Storing:** Keep container tightly closed when not in use. Store in a cool, dry place. Do not store near flames or at elevated temperatures.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
67-64-1	Acetone {2-Propanone}	PEL: 1000 ppm	TLV: 500 ppm STEL: 750 ppm	No data.
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	PEL: 100 ppm STEL: 500 ppm/(10min) CEIL: 300 ppm	TLV: 100 ppm STEL: 150 ppm	No data.
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	PEL: 200 ppm	TLV: 200 ppm STEL: 250 ppm	No data.

**SAFETY DATA SHEET**  
**KLEAN STRIP PAINT STRIPPER AFTER**  
**WASH**

Page: 5  
 Printed: 04/20/2015  
 Revision: 04/20/2015  
 Supersedes Revision: 03/05/2015

100-41-4	Ethylbenzene {Ethylbenzol; Phenylethane}	PEL: 100 ppm	TLV: 100 ppm STEL: 125 ppm	No data.
----------	---	--------------	-------------------------------	----------

<b>Respiratory Equipment (Specify Type):</b>	For OSHA controlled work place and other regular users. Use only with adequate ventilation under engineered air control systems designed to prevent exceeding appropriate TLV. For occasional use, where engineered air control is not feasible, use properly maintained and properly fitted NIOSH approved respirator for organic solvent vapors. A dust mask does not provide protection against vapors.
<b>Eye Protection:</b>	Safety glasses, goggles or face shields are recommended to safeguard against potential eye contact, irritation, or injury. Contact lenses should not be worn while working with chemicals.
<b>Protective Gloves:</b>	Wear impermeable gloves. Gloves contaminated with product should be discarded. Promptly remove clothing that becomes soiled with product.
<b>Other Protective Clothing:</b>	Various application methods can dictate use of additional protective safety equipment, such as impermeable aprons, etc., to minimize exposure. A source of clean water should be available in the work area for flushing eyes and skin. Do not eat, drink, or smoke in the work area. Wash hands thoroughly after use. Before reuse, thoroughly clean any clothing or protective equipment that has been contaminated by prior use. Discard any clothing or other protective equipment that cannot be decontaminated, such as gloves or shoes.
<b>Engineering Controls (Ventilation etc.):</b>	Use only with adequate ventilation to prevent build-up of vapors. Open all windows and doors. Use only with a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea, or eye-watering - Stop - ventilation is inadequate. Leave area immediately.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>Physical States:</b>	[ ] Gas    [ X ] Liquid    [ ] Solid
<b>Appearance and Odor:</b>	Clear, water white, thin liquid
<b>Melting Point:</b>	No data.
<b>Boiling Point:</b>	No data.
<b>Autoignition Pt:</b>	No data.
<b>Flash Pt:</b>	20.00 F    Method Used: TAG Open Cup
<b>Explosive Limits:</b>	LEL: 1.00                      UEL: No data.
<b>Specific Gravity (Water = 1):</b>	No data.
<b>Density:</b>	8.1 - 8.15 LB/GL at 7.7 F
<b>Bulk density:</b>	6.738 LB/GA
<b>Vapor Pressure (vs. Air or mm Hg):</b>	No data.
<b>Vapor Density (vs. Air = 1):</b>	No data.
<b>Evaporation Rate:</b>	No data.
<b>Solubility in Water:</b>	No data.
<b>Percent Volatile:</b>	100.0 % by weight.
<b>VOC / Volume:</b>	881.0000 G/L

**SAFETY DATA SHEET**  
**KLEAN STRIP PAINT STRIPPER AFTER**  
**WASH**

Page: 6  
Printed: 04/20/2015  
Revision: 04/20/2015  
Supersedes Revision: 03/05/2015

**10. STABILITY AND REACTIVITY**

**Stability:** Unstable [ ] Stable [ X ]

**Conditions To Avoid - Instability:** No data available.

**Incompatibility - Materials To Avoid:** Incompatible with strong oxidizing agents, strong acids, avoid contact with reactive metals such as aluminum and magnesium.

**Hazardous Decomposition Or Byproducts:** Decomposition may produce carbon monoxide, carbon dioxide, and other asphyxiants.

**Possibility of Hazardous Reactions:** Will occur [ ] Will not occur [ X ]

**Conditions To Avoid - Hazardous Reactions:** No data available.

**11. TOXICOLOGICAL INFORMATION**

**Toxicological Information:** This product has not been tested as a whole. Refer to section 2 for acute and chronic effects.

CAS# 67-64-1:  
Standard Draize Test, Eyes, Species: Rabbit, 20.00 MG, Severe.  
Result:  
Behavioral: Change in motor activity (specific assay).  
Behavioral: Alteration of classical conditioning.  
- American Journal of Ophthalmology., Ophthalmic Pub. Co., 435 N. Michigan Ave., Suite 1415, Chicago, IL 60611, Vol/p/yr: 29,1363, 1946

CAS# 1330-20-7:  
Acute toxicity, LC50, Inhalation, Rat, 5000. PPM, 4 H.  
Result:  
Behavioral: Muscle contraction or spasticity.  
Lungs, Thorax, or Respiration: Other changes.  
- Raw Material Data Handbook, Vol.1: Organic Solvents, 1974., National Assoc. of Printing Ink Research Institute, Francis McDonald Sinclair Memorial Labor, Lehigh Univ., Bethlehem, PA 18015, Vol/p/yr: 1,123, 1974

Standard Draize Test, Eyes, Species: Rabbit, 5.000 MG, 24 H, Severe.  
Result:  
Behavioral: General anesthetic.  
Behavioral: Somnolence (general depressed activity).  
Behavioral: Irritability.  
- "Sbornik Vysledku Toxixologickeho Vysetreni Latek A Pripravku," , Institut Pro Vychovu Vedoucicn P, Marhold, J.V., Institut Pro Vychovu Vedoucicn, Pracovniku Chemickeho, Prumyclu Praha Czechoslovakia, Vol/p/yr: -,24, 1972

CAS# 100-41-4:  
Tumorigenic Effects:, TCLo, Inhalation, Rat, 750.0 ppm.  
Result:  
Tumorigenic: Carcinogenic by RTECS criteria.  
Kidney, Ureter, Bladder: Tumors.

Standard Draize Test, Eyes, Species: Rabbit, 500.0 MG, Severe.

**SAFETY DATA SHEET**  
**KLEAN STRIP PAINT STRIPPER AFTER**  
**WASH**

Page: 7  
 Printed: 04/20/2015  
 Revision: 04/20/2015  
 Supersedes Revision: 03/05/2015

Result:  
 Effects on Fertility: Post-implantation mortality (e.g., dead and/or resorbed implants per total number of implants).  
 Effects on Fertility: Litter size (e.g.; # fetuses per litter; measured before birth).  
 Effects on Embryo or Fetus: Fetotoxicity (except death, e.g., stunted fetus).  
 - American Journal of Ophthalmology., Ophthalmic Pub. Co., 435 N. Michigan Ave., Suite 1415, Chicago, IL 60611, Vol/p/yr: 29,1363, 1946

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
67-64-1	Acetone {2-Propanone}	n.a.	n.a.	A4	n.a.
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	n.a.	3	A4	n.a.
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	n.a.	n.a.	n.a.	n.a.
100-41-4	Ethylbenzene {Ethylbenzol; Phenylethane}	n.a.	2B	A3	n.a.

## 12. ECOLOGICAL INFORMATION

**General Ecological Information:** No information available for this product as a whole.

## 13. DISPOSAL CONSIDERATIONS

**Waste Disposal Method:** Dispose in accordance with local, state, and federal regulations.

## 14. TRANSPORT INFORMATION

**LAND TRANSPORT (US DOT):**

**DOT Proper Shipping Name:** Paint Related Material, LTD QTY  
**DOT Hazard Class:** 3 FLAMMABLE LIQUID  
**UN/NA Number:** UN1263 **Packing Group:** II



**Additional Transport Information:** The shipper/supplier may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

## 15. REGULATORY INFORMATION

**This material meets the EPA 'Hazard Categories' defined for SARA Title III Sections 311/312 as indicated:**

<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No	Acute (immediate) Health Hazard
<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No	Chronic (delayed) Health Hazard
<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No	Fire Hazard
<input type="checkbox"/> Yes	<input checked="" type="checkbox"/> No	Sudden Release of Pressure Hazard
<input type="checkbox"/> Yes	<input checked="" type="checkbox"/> No	Reactive Hazard

CAS #	Hazardous Components (Chemical Name)	Other US EPA or State Lists
67-64-1	Acetone {2-Propanone}	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory, 4 Test; CA PROP.65: No
1330-20-7	Xylene (mixed isomers) {Benzene, dimethyl-}	CAA HAP,ODC: HAP; CWA NPDES: Yes; TSCA: Yes - Inventory; CA PROP.65: No
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	CAA HAP,ODC: HAP; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: Yes

**SAFETY DATA SHEET**  
**KLEAN STRIP PAINT STRIPPER AFTER**  
**WASH**

100-41-4 Ethylbenzene {Ethylbenzol; Phenylethane}

CAA HAP,ODC: HAP; CWA NPDES: Yes; TSCA: Yes -  
Inventory, 4 Test; CA PROP.65: Yes

**Regulatory Information Statement:** All components of this material are listed on the TSCA Inventory or are exempt.

**16. OTHER INFORMATION**

**Revision Date:** 04/20/2015

**Preparer Name:** W.M. Barr EHS Dept (901)775-0100

**Additional Information About This Product:** No data available.

**Company Policy or Disclaimer:** The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.