



# Safety Data Sheet

According to OSHA HCS 2012 (29 CFR 1910.1200)

| Section 1: Identification  |   |                                  |
|--|---|----------------------------------|
| <b>Product Identifier:</b>   | <b>Propane</b>  |                                  |
| <b>Other means of identification:</b>  | Commercial Propane (All)<br>Odorized Propane<br>Propane Commercial<br>Propane Motor Fuel<br>Stenched for Process  |                                  |
| <b>Intended for Use:</b>   | Fuel  |                                  |
| <b>Uses Advised Against:</b>   | All others  |                                  |
| <b>Emergency Health and Safety Number:</b>   | Chemtrec: 800-424-9300 (24 Hours)   |                                  |
| <b>Distributor:</b><br>Pinnacle Propane Express, LLC<br>PO BOX 140128<br>Irving, TX 75014  | <b>SDS Information:</b><br>Phone: 972-444-0300<br>URL: <a href="http://www.pinnaclepropaneexpress.com">www.pinnaclepropaneexpress.com</a><br><a href="http://www.pinnpropane.com">www.pinnpropane.com</a> |                                  |
| Section 2: Hazards Identification  |   |                                  |
| <b>Classified Hazard</b><br>H220 -- Flammable gases -- Category 1<br>H280 -- Gases under pressure -- Liquefied gas   | <b>Other Hazards</b><br>May displace oxygen and cause rapid suffocation   |                                  |
| Label Elements   |   |                                  |
|  <b>DANGER</b><br>Extremely Flammable Gas<br>Contains gas under Pressure. May explode if heated.  | May displace oxygen and cause rapid suffocation   |                                  |
|  Keep away from heat/sparks/open flames/hot surfaces. – No smoking; Take Precautionary measures against static discharge; Leaking gas fire: Do not extinguish, unless leak can be stopped safely; Eliminate all sources if safe to do so; Protect from sunlight. Store in a well ventilated place |   |                                  |
| Section 3: Composition/Information on Ingredients  |   |                                  |
| <b>Chemical Name:</b>  | <b>CASRN</b>  | <b>Concentration<sup>1</sup></b> |
| Propane  | 74-98-6   | 80-100                           |
| Propene  | 115-07-1  | <20                              |
| Ethane   | 74-84-0   | <6                               |
| Butane   | 106-97-8  | <5                               |
| Isobutane  | 75-28-5   | <2.5                             |

<sup>1</sup> All concentration are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume

Odorized products contain small quantities (<0.1%) ethyl mercaptan as an olfactory indicator.

| Section 4: First Aid Measures   |
|---|
| <b>Eye Contact:</b> For contact with the liquefied gas, remove contact lenses if present and easy to do, hold eyelids apart and gently flush the affected eye(s) with lukewarm water. Seek immediate medical attention. |

# Safety Data Sheet

According to OSHA HCS 2012 (29 CFR 1910.1200)

**Skin Contact:** Liquefied gases may cause cryogenic burns or injury. Treat burned or frostbitten skin by flushing or immersing the affected area(s) in lukewarm water. Do not rub affected area. Do not remove clothing that adheres due to freezing. After sensation has returned to the frostbitten skin, keep skin warm, dry, and clean. If blistering occurs, apply a sterile dressing. Seek immediate medical attention.

**Inhalation (Breathing):** If respiratory symptoms develop, move victim away from source of exposure and into fresh air in a position comfortable for breathing. If breathing is difficult, oxygen or artificial respiration should be administered by qualified personnel. If symptoms persist, seek medical attention.

**Ingestion (Swallowing):** This material is a gas under normal atmospheric conditions and ingestion is unlikely.


**Most important symptoms and effects, both acute and delayed:** Light hydrocarbon gases are simple asphyxiants and can cause anesthetic effects at high concentrations. Symptoms of overexposure, which are reversible if exposure is stopped, can include shortness of breath, drowsiness, headaches, confusion, decreased coordination, visual disturbances and vomiting. Continued exposure can lead to hypoxia (inadequate oxygen), rapid breathing, cyanosis (bluish discoloration of the skin), and numbness of the extremities, unconsciousness and death.

**Notes to Physician:** Epinephrine and other sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to high concentrations of hydrocarbon solvents (e.g., in enclosed spaces or with deliberate abuse). The use of other drugs with less arrhythmogenic potential should be considered. If sympathomimetic drugs are administered, observe for the development of cardiac arrhythmias

## Section 5: Fire-Fighting Measures

### NFPA 704 Hazard Class

**Health: 2 Flammability: 4 Instability: 0**



0 (Minimal)  
1 (Slight)  
2 (Moderate)  
3 (Serious)  
4 (Severe)

**Extinguishing Media:** Dry chemical or carbon dioxide is recommended. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces.

### **Specific hazards arising from the chemical**

**Unusual Fire & Explosion Hazards:** Extremely flammable. Contents under pressure This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe). Vapors may travel considerable distances to a source of ignition where they can ignite, flash back, or explode. May create vapor/air explosion hazard indoors, in confined spaces, outdoors, or in sewers. If container is not properly cooled, it can rupture in the heat of a fire. Drains can be plugged and valves made inoperable by the formation of ice if rapid evaporation of large quantities of the liquefied gas occurs. Do not allow run-off from fire fighting to enter drains or water courses – may cause explosion hazard in drains and may reignite.

**Hazardous Combustion Products:** Combustion may yield smoke, carbon monoxide, and other products of incomplete combustion. Oxides of nitrogen and sulfur may also be formed.

**Special protective actions for firefighters:** For fires beyond the initial stage, emergency responders in the immediate hazard area should wear protective clothing. When the potential chemical hazard is unknown, in enclosed or confined spaces, a self-contained breathing apparatus should be worn. In addition, wear other appropriate protective equipment as conditions warrant (see Section 8). Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. If this cannot be done, allow fire to burn. Move undamaged containers from immediate hazard area if it can be done safely. Stay away from ends of

# Safety Data Sheet

According to OSHA HCS 2012 (29 CFR 1910.1200)

container. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Cool equipment exposed to fire with water, if it can be done safely.

-----  
**See Section 9 for Flammable Properties including Flash Point and Flammable (Explosive) Limits**

## Section 6: Accidental Release Measures

**Personal precautions, protective equipment and emergency procedures:** Extremely flammable. Spillages of liquid product will create a fire hazard and may form an explosive atmosphere. Keep all sources of ignition and hot metal surfaces away from spill/release if safe to do so. The use of explosion-proof electrical equipment is recommended. Beware of accumulation of gas in low areas or contained areas, where explosive concentrations may occur. Prevent from entering drains or any place where accumulation may occur. Ventilate area and allow to evaporate. Stay upwind and away from spill/release. Avoid direct contact with material. For large spillages, notify persons downwind of the spill/release, isolate immediate hazard area and keep unauthorized personnel out. Wear appropriate protective equipment, including respiratory protection, as conditions warrant (see Section 8). See Sections 2 and 7 for additional information on hazards and precautionary measures.

**Environmental Precautions:** Stop spill/release if it can be done safely. Water spray may be useful in minimizing or dispersing vapors. If spill occurs on water notify appropriate authorities and advise shipping of any hazard.

**Methods and material for containment and cleaning up:** Notify relevant authorities in accordance with all applicable regulations.

Recommended measures are based on the most likely spillage scenarios for this material; however local conditions and regulations may influence or limit the choice of appropriate actions to be taken.

## Section 7: Handling and Storage

**Precautions for safe handling:** Keep away from ignition sources such as heat/sparks/open flame – No smoking. Take precautionary measures against static discharge. Use good personal hygiene practices and wear appropriate personal protective equipment (see section 8). Extremely Flammable. Contents under pressure Gas can accumulate in confined spaces and limit oxygen available for breathing. Use only with adequate ventilation The use of explosion-proof electrical equipment is recommended and may be required (see appropriate fire codes). Refer to NFPA-70 and/or API RP 2003 for specific bonding/grounding requirements. Electrostatic charge may accumulate and create a hazardous condition when handling or processing this material. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Do not enter confined spaces such as tanks or pits without following proper entry procedures such as ASTM D-4276 and 29CFR 1910.146. Cold burns may occur during filling operations. Containers and delivery lines may become cold enough to present cold burn hazard.

Propane and odorant are heavier than air and will collect and pool along the ground or floor. Odorant, therefore, may not be detectable above the location of propane storage or service (for example, odorant in propane released or leaked into the basement of a dwelling may not be detected above the basement).

WARNING - The intensity of the odorant may fade over prolonged storage or in the presence of rust, when placed initially in new or freshly-cleaned storage vessels, or when exposed to masonry.

**Conditions for safe storage:** Keep container(s) tightly closed and properly labeled. Use and store this material in cool, dry, well-ventilated areas away from heat, direct sunlight, hot metal surfaces, and all sources of ignition. Store only in approved containers. Post area "No Smoking or Open Flame." Keep away from any incompatible material (see Section 10). Protect container(s) against physical damage. Outdoor or detached storage is preferred. Indoor storage should meet OSHA standards and appropriate fire codes.

# Safety Data Sheet

According to OSHA HCS 2012 (29 CFR 1910.1200)

"Empty" containers retain residue and may be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury or death. Avoid exposing any part of a compressed-gas cylinder to temperatures above 125F (51.6C). Gas cylinders should be stored outdoors or in well ventilated storerooms at no lower than ground level and should be quickly removable in an emergency.

## Section 8: Exposure Controls/Personal Protection

| Chemical Name | ACGIH          | OSHA   | OTHER |
|---------------|----------------|--|-------|
| Propane       | ---            | TWA: 1000 PPM<br>TWA: 1800 MG/M <sup>3</sup> | ---   |
| Propene       | TWA: 500 PPM   | ---  | ---   |
| Butane        | STEL: 1000 PPM | ---  | ---   |
| Isobutane     | STEL: 1000 PPM | ---  | ---   |

**Note: State, local or other agencies or advisory groups may have established more stringent limits. Consult an industrial hygienist or similar professional, or your local agencies, for further information.**

**Engineering controls:** If current ventilation practices are not adequate to maintain airborne concentrations below the established exposure limits, additional engineering controls may be required.

**Eye/Face Protection:** The use of eye protection (such as splash goggles) that meets or exceeds ANSI Z.87.1 is recommended when there is potential liquid contact to the eye. Depending on conditions of use, a face shield may be necessary.

**Skin/Hand Protection:** Wear thermal insulating gloves and face shield or eye protection when working with materials that present thermal hazards (hot or cold).

**Respiratory Protection:** A NIOSH approved, self-contained breathing apparatus (SCBA) or equivalent operated in a pressure demand or other positive pressure mode should be used in situations of oxygen deficiency (oxygen content less than 19.5 percent), unknown exposure concentrations, or situations that are immediately dangerous to life or health (IDLH).

A respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 and ANSI Z88.2 should be followed whenever workplace conditions warrant a respirator's use.

**Suggestions provided in this section for exposure control and specific types of protective equipment are based on readily available information. Users should consult with the specific manufacturer to confirm the performance of their protective equipment. Specific situations may require consultation with industrial hygiene, safety, or engineering professionals.**

# Safety Data Sheet

According to OSHA HCS 2012 (29 CFR 1910.1200)

## Section 9: Physical and Chemical Properties

**Note:** Unless otherwise stated, values are determined at 20°C (68°F) and 760 mm Hg (1 atm). Data represent typical values and are not intended to be specifications.

|  |  |
|--|--|
| <p><b>Appearance:</b> Colorless<br/> <b>Physical Form:</b> Liquefied<br/> <b>Odor:</b> No distinct odor (or skunk, rotten egg or garlic if odorant added)<br/> <b>Odor Threshold:</b> No data<br/> <b>pH:</b> Not applicable<br/> <b>Vapor Density (air=1):</b> &gt;1<br/> <b>Upper Explosive Limits (vol % in air):</b> 9.5<br/> <b>Lower Explosive Limits (vol % in air):</b> 2.1<br/> <b>Evaporation Rate (nBuAc=1):</b> &gt;1<br/> <b>Particle Size:</b> N/A<br/> <b>Percent Volatile:</b> 100%<br/> <b>Flammability (solid, gas):</b> Extremely Flammable</p> | <p><b>Flash Point:</b> -156 °F / -104 °C<br/> <b>Test Method:</b> Tag Closed Cup (TCC), ASTM D56<br/> <b>Vapor Pressure:</b> 208 psia (Reid VP) @ 100°F / 37.8°C<br/> <b>Partition Coefficient (n-octanol/water) (Kow):</b> No data<br/> <b>Melting/Freezing Point:</b> -309 °F / -189 °C<br/> <b>Auto-ignition Temperature:</b> 842 °F / 450 °C<br/> <b>Decomposition Temperature:</b> No data<br/> <b>Specific Gravity (water=1):</b> 0.50-0.51 @ 60°F (15.6°C)<br/> <b>Bulk Density:</b> N/D<br/> <b>Viscosity:</b> N/D<br/> <b>Solubility in Water:</b> Negligible</p> |
|--|--|

## Section 10: Stability and Reactivity

**Reactivity:** Not chemically reactive.  
**Chemical stability:** Stable under normal ambient and anticipated conditions of use.  
**Possibility of hazardous reactions:** Hazardous reactions not anticipated.  
**Conditions to avoid:** Avoid all possible sources of ignition. Heat will increase pressure in the storage tank.  
**Incompatible materials:** Avoid contact with acids, aluminum chloride, chlorine, chlorine dioxide, halogens and oxidizing agents.  
**Hazardous decomposition products:** Not anticipated under normal conditions of use.

## Section 11: Toxicological Information

### Information on Toxicological Effects of Substance/Mixture

Substance/Mixture

| Acute Toxicity | Hazard                             | Additional Information  | LC50/LD50 Data |
|----------------|------------------------------------|---|----------------|
| Inhalation     | Unlikely to be harmful             | Asphyxiant High concentration in confined spaces may limit oxygen available for breathing. See Signs and symptoms | ➤ 20,000 PPM   |
| Dermal         | Skin Absorption is not anticipated |   | Not Applicable |
| Oral           | Ingestion is not anticipated       |   | Not Applicable |

**Aspiration Hazard:** Not applicable

**Skin Corrosion/Irritation:** Not expected to be irritating. Contact with the liquefied or pressurized gas may cause frostbite ("cold" burn).

# Safety Data Sheet

According to OSHA HCS 2012 (29 CFR 1910.1200)

**Serious Eye Damage/Irritation:** Not expected to be irritating. Contact with the liquefied or pressurized gas may cause momentary freezing followed by swelling and eye damage.

**Skin Sensitization:** Skin contact is not anticipated.

**Respiratory Sensitization:** Not expected to be a respiratory sensitizer.

**Specific Target Organ Toxicity (Single Exposure):** Not expected to cause organ effects from single exposure.

**Specific Target Organ Toxicity (Repeated Exposure):** Not expected to cause organ effects from repeated exposure.

**Carcinogenicity:** Not expected to cause cancer.

**Germ Cell Mutagenicity:** Not expected to cause heritable genetic effects.

**Reproductive Toxicity:** Not expected to cause reproductive toxicity.

**Other Comments:** High concentrations may reduce the amount of oxygen available for breathing, especially in confined spaces. Hypoxia (inadequate oxygen) during pregnancy may have adverse effects on the developing fetus. The odorant, ethyl mercaptan, can be irritating to the eyes, skin and respiratory tract. At high concentrations, a person can temporarily lose the ability to smell ethyl mercaptan. In addition, some individuals may have an impaired sense of smell, which inhibits the detection of the odorant.

## Information on Toxicological Effects of Components

**Propane Target Organs:** No systemic or neurotoxic effects were noted in rats exposed to concentrations of propane as high as 12,000 ppm for 28 days.

**Reproductive Toxicity:** No adverse reproductive or developmental effects were observed in rats exposed to propane; no observed adverse effect level = 12,000 ppm.

**Butane Target Organs:** No systemic or neurotoxic effects were noted in rats exposed to concentrations of butane as high as 9,000 ppm for 28 days.

**Reproductive Toxicity:** No adverse reproductive or developmental effects were observed in rats exposed to butane; no observed adverse effect level = 12,000 ppm.

**Isobutane Target Organs:** No systemic or neurotoxic effects were noted in rats exposed to concentrations of isobutane as high as 9,000 ppm for 28 days.

**Reproductive Toxicity:** No adverse developmental effects were observed in rats exposed to concentrations of isobutane as high as 9000 ppm. Fertility and mating indices may have been affected at 9000 ppm but no effects were observed at 3000 ppm (NOAEL).

## Section 12: Ecological Information

### GHS Classification:

No classified hazards

**Toxicity:** Petroleum gases will readily evaporate from the surface and would not be expected to have significant adverse effects in the aquatic environment.

**Persistence and Degradability:** The hydrocarbons in this material are expected to be inherently biodegradable. In practice, hydrocarbon gases are not likely to remain in solution long enough for biodegradation to be a significant loss process. Hydrogen sulfide, if present in refinery gas streams, will be rapidly oxidized in water and insoluble sulfides precipitated from water when metallic radicals are present.

**Bioaccumulative Potential:** Since the log K<sub>OW</sub> values measured for refinery gas constituents are below 3, they are not regarded as having the potential to bioaccumulate.

# Safety Data Sheet

According to OSHA HCS 2012 (29 CFR 1910.1200)

**Mobility in Soil:** Due to the extreme volatility of petroleum gases, air is the only environmental compartment in which they will be found. In air, these hydrocarbons undergo photodegradation by reaction with hydroxyl radicals with half-lives ranging from 3.2 days for n-butane to 7 days for propane.

**Other adverse effects:** None anticipated.

## Section 13: Disposal Consideration

This material is a gas and would not typically be managed as a waste.

## Section 14: Transport Information

### U.S. Department of Transportation (DOT)

**Shipping Description:** UN1978, Propane, 2.1,  
**Non-Bulk Package Marking:** Propane, UN1978  
**Non-Bulk Package Labeling:** Flammable Gas  
**Bulk Package/Placard Marking:** Flammable gas / 1978  
**Packaging - References:** 169570 – Propane 49 CFR: 173.306; 173.304; 173.314 & .315 (Exceptions; Non-bulk; Bulk)  
**Hazardous Substance:** See Section 15 for RQ's  
**Emergency Response Guide:** 115

**Note:** For domestic transportation only, UN1075 may be substituted for the UN number shown as long as the substitution is consistent on package markings, shipping papers, and emergency response information. See 49 CFR 172.102 Special Provision 19.

Containers of NON-ODORIZED liquefied petroleum gas must be marked either NON-ODORIZED or NOT ODORIZED as of September 30, 2006. [49 CFR 172.301(f), 326(d), 330(c) and 338(e)]

### International Maritime Dangerous Goods (IMDG)

**Shipping Description:** UN1978, Propane, 2.1  
**Non-Bulk Package Marking:** Propane, UN1978  
**Labels:** Flammable Gas  
**Placards/Marking (Bulk):** Flammable gas / 1978  
**Packaging - Non-Bulk:** P200  
**EMS:** F-D, S-U

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

### International Civil Aviation Org. / International Air Transport Assoc. (ICAO/IATA)

**UN/ID #:** UN1978  
**Proper Shipping Name:** Propane  
**Hazard Class/Division:** 2.1  
**Non-Bulk Package Marking:** Propane, UN1978  
**Labels:** Flammable Gas  
**ERG Code:** 10L  
**Note:** Special provision A1 applies to this product.

# Safety Data Sheet

According to OSHA HCS 2012 (29 CFR 1910.1200)

## Section 15: Regulatory Information

### **CERCLA/SARA - Section 302 Extremely Hazardous Substances and TPQs (in pounds):**

This material does not contain any chemicals subject to the reporting requirements of SARA 302 and 40 CFR 372.

### **CERCLA/SARA - Section 311/312 (Title III Hazard Categories)**

**Acute Health Hazard:** Yes  
**Chronic Health Hazard:** No  
**Fire Hazard:** Yes  
**Pressure Hazard:** yes  
**Reactive Hazard:** No

### **CERCLA/SARA - Section 313 and 40 CFR 372:**

This material contains the following chemicals subject to the reporting requirements of Section 313 of SARA Title III and 40 CFR 372:

| Chemical Name | Concentration <sup>1</sup> | de minimis |
|---------------|----------------------------|------------|
| Propene       | <20                        | 1.0%       |

### **EPA (CERCLA) Reportable Quantity (in pounds):**

EPA's Petroleum Exclusion applies to this material - (CERCLA 101(14)).

### **California Proposition 65:**

WARNING: Chemicals known to the State of California to cause cancer, birth defects or other reproductive harm are created by the combustion of propane.

### **Canada:**

#### **Canadian Regulations:**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the Regulations.

#### **WHMIS Hazard Class:**

A - Compressed gases  
B1 - Flammable gas

#### **National Chemical Inventories**

All components are either listed on the US TSCA Inventory, or are not regulated under TSCA.  
All components are either on the DSL, or are exempt from DSL listing requirements.

**U.S. Export Control Classification Number:** EAR99



# Safety Data Sheet

According to OSHA HCS 2012 (29 CFR 1910.1200)

## Section 16: Other Information

### Date of Issue:

5/12/2015

### Revised Sections or Basis for Revision:

Periodic review and update

### Precautionary Statement(s):

P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P243: Take precautionary measures against static discharge.

P381: Eliminate all ignition sources if safe to do so.

P377: Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

P410+P403: Protect from sunlight. Store in a well ventilated place.

### Guide to Abbreviations:

ACGIH = American Conference of Governmental Industrial Hygienists; CASRN = Chemical Abstracts Service Registry Number; CEILING = Ceiling

Limit (15 minutes); CERCLA = The Comprehensive Environmental Response, Compensation, and Liability Act; EPA = Environmental Protection

Agency; GHS = Globally Harmonized System; IARC = International Agency for Research on Cancer; INSHT = National Institute for Health and Safety at Work; IOPC = International Oil Pollution Compensation; LEL = Lower Explosive Limit; NE = Not Established; NFPA = National Fire

Protection Association; NTP = National Toxicology Program; OSHA = Occupational Safety and Health Administration; PEL = Permissible Exposure Limit (OSHA); SARA = Superfund Amendments and Reauthorization Act; STEL = Short Term Exposure Limit (15 minutes); TLV = Threshold Limit

Value (ACGIH); TWA = Time Weighted Average (8 hours); UEL = Upper Explosive Limit; WHMIS = Worker Hazardous Materials Information System (Canada)

### Disclaimer of Expressed and implied Warranties:

The information presented in this Safety Data Sheet is based on data believed to be accurate as of the date this Safety Data Sheet was prepared.

HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THE INFORMATION PROVIDED ABOVE, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE. No responsibility is assumed for any damage or injury resulting from abnormal use or from any failure to adhere to recommended practices. The information provided above, and the product, are furnished on the condition that the person receiving them shall make their own determination as to the suitability of the product for their particular purpose and on the condition that they assume the risk of their use. In addition, no authorization is given nor implied to practice any patented invention without a license.